



Technology ingrained in tradition...





www.radhetechnologies.com



The professional cnc router and laser cutting machine manufacturer in India. Our machines including ATC CNC router, Wood CNC Router, Stone CNC Router, Metal CNC Router, EPS CNC Router, 4 Axis CNC Router, 5 Axis CNC Router, Plasma Cutting Machine. We offer an engineered range of CNC Cutting Machines that is useful in cutting various kinds of material objects in several engineering industries. We manufacture these CNC Cutting Machines using high quality of machineries and are widely demanded due to dimensional accuracy, durability and toughness. These CNC Cutting Machines are provided as per the International Standards.

ALL TYPES OF CUSTOMISED CNC MACHINE





RT 1325 ES



CNC ROUTER MACHINE

RADHE TECHNOLOGIES RT

Machine also available in Size | 1300x2500 1500x3000

Mfg. of all type of **CNC Router Machine All Types Customised CNC** Machine



राभ

लाभ



(0) www.radhetechnologies.com +91 93 27 67 27 39

A REAL PROPERTY AND A REAL

WORK MATERIAL : WOOD, MDF, ACRYLIC, ACP, PVC, HARD WOOD, CORIAN, THERMOCAL



TECHNICAL SPECIFICATION

WORKING PARAMETERS		
Cutting Area	1300mm x 2500mm	
X-Axis Running Area	1300mm	
Y-Axis Running Area	2500mm	
Z-Axis Running Area	200mm	

MOTOR		
SERVO MOTOR	Company : Sigma / Aero Motion	
EASY MOTOR	Company : Leadshine / Yakotec	

ELECTRICAL REQUIREMENT				
Electric Voltage	380V / 220V			
Phase	Triphase / Singlephase			
Frequency/ Current	50Hz/60Amp			

AXIS MOVEMENT SYSTEM		
X And Y AXIS	Rack & Pinion (24mm, Company: YYC / Mimy Taiwan)	
Z axis	Ball Screw (25mm, Company: Hiwin Taiwan)	
AXIS SLIDER	Linear Motion Guide (25mm, Hiwin Taiwan)	

MACHINE PARAMETER		
Controller	NK 105 / A11	
Spindle 6kw / 3.5kw	6kw - 18000RPM - Air Cooling 3.5kw - 18000RPM - Air Cooling	
Machine Bed Structure	Heavy Structure Made Of Mild Steel 150x150mm 6mm pipe use	

DIMENSIONS				
Length	Width	Height		
3000mm	2000mm	1800mm		





NK 105 CONTROLLER

NK 105 Is a hand held, o ffline, and easy to operate controller. It is no need to connect with a PC during the machine working. It is easily operate and Learned, especially for the freshman.



ALUMINIUM ► T-SLOT TABLE

Work table with "T"-slot for mechanical fastening

The working table of the machine is made of panels of special reinforced aluminum separated by grooves to accommodate the clamps. A frequent step in the placement of the grooves makes it possible to fasten the workpiece of almost any size and does not require additional manipulation. The surface of the table, in the processing area, is covered with a special protective layer of wear-resistant plastic. In the event of errors and passing the tool below the workpiece zero point, the protective layer keeps the tool and the table from damage.





BASE FRAME

Heavy structure a 150x150mm 6mm pipe Body The base frame is fabricated from heavy-duty tubular steel that is welded, precision machined and stress relieved so that the foundation remains true and steady over the operational life of the machine.



HIWIN LINEAR GUIDE►

XYZ Axis Motion Square Rail, The Hiwin Square rail higher stability and rigidity, which makes the gantry moving and spindle moving at high speed with high precision. and hiwin square rail is more durable.





46 KW SPINDLE

6KW HQD Brand PowerFull Air Cooling Spindle. this precision spindle requires no maintainance. Fully programmable Speeds From 6,000 to 18,000RPM.





PLANETARY ► GEARBOX

Tornex Brand High Precision planetary GearBox Thase gear reducers are with high precision, and it can increase torque. therefore make the motor more powerful.





SERVO MOTOR

Radhe Technologies Brand AC Servo Motors. these motors require no regular maintenance therefore, reducing any maintenance downtime.



XY HELICAL **RACK & PINION**

is inverted to help keep dust and debris from building



Imperium CNC Router uses precision helical gear racks on the X and Y axis. The mounting of the rack

up on the drive system, this assures smooth motion and long term reliability. This eliminates gearbox stretch inaccuracies assuring high-speed machining while the system positions the spindle accurately.

PROXIMITY SENSOR LIMIT SWITCH

The limit sensor is the second limit protection. Tecnik EGT 12X04XAN024 PROXI is famous brand and the sensor is with high quality. The function of this device is to prevent the machine from overtraveling, and avoid unnecessary losses.

The sensor is installed on all XYZ axis.

OIL LUBRICATION SYSTEM

The machine comes the whole lubrication system to make sure all the transmission system will be well lubricated, which will make the machine service life longer.





AUTO LUBRICATION PUMP





OPTIONAL PARTS



DUST COLLECTOR

Big dust collector with 2 bags, which is powerful enough for collect the. It will make your workshop without dust.

OIL MIST COOLANT SYSTEM

The Oil mist Coolant System is ideal for coolant tools for cutting metal. The unit's microdispenser delivers a very small amount of high-performance vegetable-based lubricant to the cutting tool by atomizing the lubricant in a high-velocity air stream. The result is higher material removal rates, improved finish, tighter tolerances and increased productivity.





ROTARY AXIS

Imperium 4-Axis rotary table assembly comes complete with a 3-jaw chuck, tail stock, and linear guide track for easy tail stock movement and center alignment. The addition of Alpha's 4-axis rotary table assembly adds greater functionality to the machine's capabilities allowing for 4-axis cutting in both 2D and 3D carving and indexing functions.

(Alpha has 0-100mm, 0-150mm, 0-200mm, 0-250mm, 0-300mm diameter rotary axis for your choice)



1. X Y Z Axis 2. HIWIN SQUARE RAIL

The CNC Router has a 1 inch thick phenolic vacuum table surface mounted onto the steel base frame, keeping a rigid and consistent platform for your sheets and parts to be supported. The vacuum table surface is multi-zoned which allows the operator to easily switch from full sheet processing to smaller part processing, (which requires a smaller segmented area). Zones can be turned off easily via control valves on the front of the machine. Gasketing can also be routed to accommodate various material sizes and styles.

The APS Series Machine also includes a heavy-duty aluminum T-Slot profile in multiple locations across the table surface. This T-Slot accepts Alpha's square M6 T-nuts. 5.5kw/7.5kw dry Rotary Vane Vacuum Pump Comes standard with motor starter, vacuum gauge, primary and secondary filter, check valve and all necessary plumbing to connect to router.



VACUUM FUNCTION SWITCH



5.5KW/7.5KW VACUUM PUMP(FOR OPTION)







IMPERIUM APPLICATIONS

WALL DECORATION



SPEAKER MAKING



FOAM CUTTING



ACRYLIC PROCESSING



MUSICAL INSTRUMENT MAKING







IMPERIUM APPLICATIONS

SIGN MAKING

DOOR MAKING





CABINET MAKING



FURNITURE DECORATION



DECORATIVE PARTITION MAKING



