

AN ISO 9001:2015 CERTIFIED COMPANY

Flavour[®]



• PVC PIPE ADHESIVE • U-PVC PIPE ADHESIVE • C-PVC PIPE ADHESIVE

PVC TO PVC ADHESIVE



ML.	Units per case	Master Carton	MRP	RATE
10 ML	100 (Tube)	1400	12	5.70
25 ML	100 (Tube)	1200	20	11.50
50 ML	50 (Tube)	450	35	17.50
50 ML	30 (Tin)	480	60	31.00
100 ML	25 (Tube)	300	65	33.00
118 ML	24 (Tin)	288	100	56.00
237 ML	15 (Tin)	150	175	84.00
500 ML	12 (Tin)	72	300	140.00
1 Ltr.	6 (Tin)	48	450	250.00

Less.....% + GST

U-PVC ADHESIVE (Clear & Blue)



ML.	Units per case	Master Carton	MRP	RATE
10 ML	100 (Tube)	1400	20	14
25 ML	100 (Tube)	1200	35	24
50 ML	30 (Tin)	480	115	56
118 ML	24 (Tin)	288	180	100
237 ML	15 (Tin)	150	350	182
500 ML	12 (Tin)	72	650	336
1 Ltr.	6 (Tin)	48	950	590

Less.....% + GST

C-PVC ADHESIVE (Yellow)



ML.	Units per case	Master Carton	MRP	RATE
10 ML	100 (Tube)	1400	40	20
25 ML	100 (Tube)	1200	75	35
50 ML	30 (Tin)	480	160	70
118 ML	24 (Tin)	288	250	120
237 ML	15 (Tin)	150	400	220
500 ML	12 (Tin)	72	700	400
1 Ltr.	6 (Tin)	48	1300	725

Less.....% + GST

PVC SOLVENT CEMENT

- Regular Bodied, Fast Setting, High Strength Low VOC Solvent cement.
- For Potable Water, Plumbing, Irrigation, Conduit, Sewer, Drain, Waste and vent systems.
- Shelf Life 2 years.



U PVC SOLVENT CEMENT (Clear / Blue)

- Heavy Bodied, Fast Setting, High Strength Low VOC Solvent cement.
- For Potable Water, Plumbing, Irrigation, Conduit, Sewer, Drain, Waste and vent systems.
- Shelf Life 2 years.



C PVC SOLVENT CEMENT (Yellow)

- Heavy Bodied, Fast Setting, High Strength Low VOC Solvent cement.
- For Potable Water, Plumbing, Irrigation, Conduit, Sewer, Drain, Waste and vent systems.
- Shelf Life 2 years.



AN ISO 9001:2015
CERTIFIED COMPANY



QUALITY POLICY

Flavour Adhesive is Manufacturer and supplier of the finest quality solvent cement for PVC, UPVC and CPVC piping system. We offer complete Line of solvent cements in the industry with products specifically formulated. Quality of Solvent Cement plays an important role and influences the joint strength.

Why to use our Products ?

We Strongly believe in quality which goes hand and hand with customer's investment in our products. Each product is carefully tested to assure that consistent high quality is maintained.

Gas chromatography and additional in-depth testing ensures that each batch is manufactured according to the Standard define processes.

A batch identification code is stamped on the bottom of each can/tube and assure traceability of all materials and processes used in manufacturing of solvent cements.

Flavour products are backed by highly trained technical service and customer support programs.

Achievement of ISO 9001:2015 certification further strengthens our consistent quality and commitment to our customers.



Cutting



Deburring/Belveling



Fitting Preparation



Solvent Cement Application



Assembly



Set and Cure Times

APPLICATION

- Clean surrounding area of the leakage with cloth or rug.
- Cut appropriate size of provided flexible pvc sheet to cover the leak area.
- Cut the corners of flexible sheet in round shape for better bonding.
- Apply a layer of cement on pipe crack / leak area.
- Then apply layer of cement on flexible pvc piece, put the flexible pvc piece on crack / leak area. hold with hand pressure for 2-3 min.
- Let it dry for at least 4 hours before starting water. For better result let it dry for overnight.

Mfg .by:

Yamuna Industries

Ahmedabad, (India).

Email : yamunaindustries12@gmail.com

Web : www.durobondsolventcement.com