# NRG GLOBAL

**Manufacturer of :**
Flow, Level, Pressure and
Temprature Instruments

36, G.I.D.C. Industrial Estate,
B/h. Mona Furniture,
Opp. Bank of Baroda, Makarpura,
Vadodara-390010. Gujarat, (India)
Mo. No. : +91-9099029297
E-mail : salesnrgglobal@gmail.com
**GST No. : 24AARFN5355N1ZL**

# TANK MOUNTED VIEW GLASS ASSEMBLY



Product Description

With the consistent focus on our quality, we offer a high quality **Tank Mounted View Glass** to our customers. These are aesthetically designed and precision-engineered for their higher performance and durable work life. In addition to this, all these Tank Mounted View Glasses are rigidly checked on various quality parameters to deliver a flawless range in the market. Moreover, clients can get the offered assortment from us at very affordable prices and within given span of time.

**Features:**

Long working life

High efficiency

Light in weight

Optimum quality

**Ansi Flange Type Design:**

NRG MAKE  Sight Glasses of ANSI Flanged type are Bolt-on units designed for attachment to ANSI flanged nozzles or vessel studding outlets

The lower flange is a standard ANSI 150# Raised Face flange

Higher rated units are also available. (300 and 600)

Material certification is furnished with all the units

**Weld Neck Flange Type Design:**

NRG make Sight Glasses of Weld Neck Flange type are weld neck units designed to be welded on to pipe ends or into tanks or vessels

The lower flange is a standard ANSI 150# weld neck flange

Higher rated units are also available (300 and 600)

Material certification is furnished with all the units

**Performance:**

Temperature Ratings: Maximum Operating Temperature rating is 200o C

Connections: Flanged OR Socket Weld OR Butt Weld OR Weld Pad OR Weld Neck Flanged End Connection

Pressure Ratings: Maximum Pressure rating is 25 Kg / Cm2

Sizes: From 15 NB to 300 NB.

Materials of Construction:

Pad Flange: M.S, C.S. (A–105), S.S.304, S.S.316, or any other alloy

Cover Flange: M.S, C.S. (A–105), S.S.304, S.S.316, or any other alloy

Window: Toughened Borosilicate Glass./ Reflex etc

Fasteners: SS316 or SS304 or SA 193 Gr.B7

Gasket: CAF or PTFE