



ZUPER LED

Adds Unlimited Colours...

5-5-235/375 & 376 , Near Bommidi

Laitha Garden, Panama Singal ,

L B Nagar, Telangana -500070

Contact: 8985478418/8328467006

Email: sales@zuperled.com

Website: www.zuperled.in

www.zuperled.com

Technical Specifications of P4.8:

LED type	ZUPER _ P4.8 Outdoor
Placement(Outdoor)	Outdoor (MS/Die Cast - IP65)
Pixel Pitch(mm)	4.8mm
LED Configuration	SMD 3 in 1
Light type	SMD2727
	1R1G1B
Module Lamp	King Light / Nation Star
Driver IC	MBI 5124
Module Size(mm)	192x192
Module Resolution(dot)	40*40
Module Pixel	1600 dots
Pixel Density(dot/m ²)	43264dots/sqm
Best View distance	≥4.8m
Brightness	5500-6000nits
View Angle	140 - 140
Controllers used for the screen	NOVASTAR / LINSEN
Cabinet Size(mm)	576*576mm
Cabinet Resolution(dot)	120*120
Cabinet Weight(kg)	9kg
Gray Level	65536
Refresh Rate	1920 - 3840
Driving Mode	1/8 scan
Operation Power	110v~240v

Power Consumption (max/sqm)	$\geq 1000\text{W/sqm}$
Power Consumption (Avg)	350 - 600W
Running Temperature	$-20^{\circ}\text{C} \sim 70^{\circ}\text{C/RH}$
Storage Temperature	$-35^{\circ}\text{C} \sim +80^{\circ}\text{C}$
Humidity	10% $\sim$ 95%
Lifespan	100,000H
Suitable	Outdoor