ALN 300 Specifications

Engine Max. Torque Transmission	Cummins 6BT5.9-C125 developing 123 hp (92 kW) @ 2000 rpm, Direct Injection, turbo charged, water cooled Diesel engine 540 Nm @ 1400 rpm	Refill Capacities Fuel Tank: Engine Oil: Hydraulic Oil: Cooling System: Transmission Oil: Axle:	168 ltrs. 16.3 ltrs. 120 ltrs. 25 ltrs. 32 ltrs.
Hallsillission	constant mesh transmission with 4 forward and 2 reverse speeds.	Final drive (Each) : Front/Rear Axle :	8 ltrs.
Forward Speeds	I II III IV 7.5 13.5 24 40	Bucket Capacity	1.7m³ general purpose bucker with a width of 2430 mm.
Reverse Speeds	9 29.5	Operating weight	9,970 kg.
Axle	Front fixed, rear floating, heavy duty axle with spiral	Tyre	17.5 X 25-20 PR
	bevel gear	Turning Radius	
Max. Torque	Oscillation angle of rear axle is ± 12°.	Outside of Bucket	6470 mm.
Steering	Highly effective, Center	Outside of Rear Wheel	6000 mm.
	articulated frame steering with co-axis flow for immediate response and system pressure 10 Mpa.	Z-Bar Advantage	Z - bar design provides higher break out force and better working efficiency, ensuring faster working with minimum
Articulation	35° ± 1°		spillage
Brakes		Hydraulic	Tandem Gear pump with sys
Service Brake	Caliper Disc Brakes.	System	pressure of 16Mpa and flow 189 lpm.
Emergency Brake	Air assisted oil disc on 4 wheels.	Electrical System	24V Battery with negative earth and directive current.
Parking Brake	Soft shaft control, disc brake	MARKETING H.O.	
Cabin	Wide View, comfortable and air-conditioned cabin. Easy access. Vibration absorbing cabin for comfortable operation with noise reduction & well laid	5th Floor, "TDI Center", Jasola, New Delhi - 25 Ph.: +91-11-40549900 (30 Lines), Fax: 40549922 E-mail: marketing@ace-cranes.com, works@ace-cranes.com REGISTERED OFFICE Dudhola Link Road, Dudhola, Palwal-121102, Haryana Ph.: +91-1275-280111 , Fax: +91-1275-280133 CIN: L74899HR1995PLC053860	



Action Construction Equipment Ltd.

out instrument panel.

Contact:

ACE reserves the right to alter any specifications without prior notice. Dimensions, weights & capacitie are variable by \pm 5%. Accessories if shown are not part of the Standard Equipment.



WWW.ace-cranes.com

Itrs. Itrs. Itrs. Itrs. Itrs. Itrs. Itrs. m³ general purpose bucket a width of 2430 mm. 70 kg. X 25-20 PR 0 mm. 00 mm. bar design provides higher ak out force and better king efficiency, ensuring er working with minimum dem Gear pump with system ssure of 16Mpa and flow of

31, "Kalpataru Court", Chembur, Mumbai - 74 Ph.: +91-22-25206846, 25207070, Telefax: 25207071 E-mail: acemumbai@ace-cranes.com

"Forma Towers" 84-A, Second Floor, AJC Bose Road, Kolkata - 14. Ph.: +91-33-65012050 E-mail: acekolkatta@ace-cranes.com

1st Floor, "Alsa Regency", 165, Eldams Road, Alwar Pet, Chennai - 18 Ph.: +91-44-24314253, Telefax: 24314252 E-mail: acechennai@ace-cranes.com

Wheeled Loader

Capacity : 1.7 cu.m. Engine Power: 123 hp. Articulated & Rugged

loading machine.





Nothing beats an ACE