




Search Fluke



Home ▶ Products ▶ Building infrastructure ▶ HVAC tools

Fluke 931 Contact and Non-Contact Dual-Purpose Tachometers

★★★★★ (0) [Write a review](#)



Buy now

Key features

- 6-digit backlight display reads the data clearly
- Signal detection reminder avoids invalid detection actions
- Maximum/minimum/average value and final readings
- Setting/Turning off the automatic power-off function
- Small size and easy to hold
- Easy switching of the contact and non-contact measurement modes
- Different speed measuring heads and rotational speeds adapt to different measurement occasions
- 1-year warranty

⤴ [Read less](#)

⬇ [Download the product manual](#)

Product overview

Specifications

Models

Reviews + Q&A

Manuals + resources

Specifications: Fluke 931 Contact and Non-Contact Dual-Purpose Tachometers

Rotation speed measurement	
Range	Optical (non-contact) measurement: 1 to 99999 revolutions/minute Contact measurement: 1 to 19999 revolutions/minute (Fluke 931 only)
Precision	±0.02%RD+1
Sensing distance	(optical) 500 mm

Specifications

Battery type	(2) 1.5V LR6 (alkaline) AA battery
Battery life	About 40 hours
Operating temperature	0°C to 50°C
Storage temperature	-20°C to 70°C
Weight	250 g
Dimensions	175 × 60 × 28 mm
Warranty period	1 year

About Fluke

[About us](#)

[Careers](#)

[Press](#)

[Supplier handbook](#)

Contact us

[Contact us](#)

[Repair](#)

[Technical support](#)

Manuals + resources

[Promotions](#)

[Manuals](#)

[Product registration](#)

[Safety notices](#)

[Where to buy](#)

[Test tools catalog](#)



Fluke. *Keeping your world up and running.*[®]

[Privacy policy](#)

[Fluke terms of use](#)

[Fluke terms and conditions of sale](#)

[Fluke terms and conditions of service](#)

[Site map](#)

©1995 - 2024 Fluke Corporation