



united Engg. Co.
Nitobond SBR Latex

POSguard
LATEX BASED MORTAR AND SCREED MODIFIER & BONDING AGENT
Nitobond SBR Latex

Benefits:

- High compressive strength
- Excellent bonding capacity, prevents delamination of concrete
- Provides excellent resistance to abrasion
- Water resistant, water proofing
- Improved bond and crack resistance

Applications:

- For concrete repair and patching
- For concrete screed and floor
- For concrete wall and ceiling
- For concrete roof and waterproofing

Directions:

1. Mix the product with clean water in the ratio of 1:1 (by weight) to form a paste. Apply the paste on the surface to be treated. Allow it to dry for 24 hours before applying the next coat. For concrete repair, mix the product with clean sand in the ratio of 1:3 (by weight) to form a mortar. Apply the mortar on the surface to be treated. Allow it to dry for 24 hours before applying the next coat.

PRECAUTIONS:
Avoid contact with skin and eyes. If contact occurs, wash immediately with plenty of water. Store in a cool, dry place. Keep away from fire. Do not use in food or drink containers.

NET QUANTITY: 200 LITRES

SAFETY: HARMFUL

DATE OF MANUFACTURE: 15/08/2023

MRSA & DATE: 15/08/2023

DESTINATION: SITE

FOR CONCRETE REPAIRS | INDUSTRIAL FLOORING | PROTECTIVE COATINGS