

NEROLAC PERMA

CRACKFILL-PASTE

Highly flexible crack filler for internal and external plaster cracks.

DESCRIPTION

Crackfill-Paste is a highly flexible crack filler, ideally suited for effectively sealing nagging, moving plaster cracks whether internal or external.

PRIMARY USES

- Crackfill-Paste is ideally suited for repairing cracks in plasters, whether internal or external.
- Crackfill-Paste is useful in sealing cracks in the ceilings and at the junctions of brickwork, columns or beams.
- Crackfill-Paste is highly useful in waterproofing applications around door and window frames and around bath tub, wash basin etc.

ADVANTAGES



Clean the surface to remove any dust, dirt, spillovers of oil, grease or loose particles.



Remove the existing POP or the putty to expose the plaster surface.



Widen the crack to at least 2mm width and moisten the crack with water.



If the surface is porous or difficult apply a primer prepared by mixing Crackfill-Paste and water in the proportion of 1 : 1.



Apply Crackfill-Paste in the crack with a putty blade or spatula effectively making sure that it is totally filled up.



Tool the surface to obtain an even smooth and unbroken surface.



Allow it to cure. Upon full cure apply putty or pop whatever was removed before the application of Crackfill-Paste.

PROPERTIES

Appearance : Milky White Paste
Specific Gravity : 1.40 ± 0.05 Kg/ litre
Full Curing Time : 7 days

COVERAGE

1 kg of Crackfill-Paste seals 9.29 rmt of 6mm wide crack.

PACKING

Crackfill-Paste is available in 200 Gms, 400 Gms, 1 kg and 15 kg Pack.

SHELF LIFE

Crackfill-Paste has a shelf life of 24 months if stored in manufacturer's original packing in a cool and dry place away from moisture and heat.

DISCLAIMER

KANSAI NEROLAC PAINTS LTD. (KNPL) warrants that all products are free from any defects of manufacturing and comply with the specification given in their respective technical data sheet. No warranty can be given as to the results of use because conditions of use, such as site conditions, surface preparations, workmanship, weather, structural issues and other factors are beyond the control of NEROLAC. Purchaser agrees to seek the advice of qualified professionals to carry out tests and take trials to determine the suitability of products for their intended purpose, prior to full scale usage of **KNPL** products and assumes all risks.

The company does not assume any liability for unsatisfactory results, arising from the use of our products. Purchaser's sole liability is limited to the replacement of the product or refund of the purchase price paid, if any product is proven defective. No other warranties express or implied, shall apply including any warranty of merchantability or fitness for any particular purpose.

KNPL shall not be liable for any consequential damages arising from the use of our products for unsatisfactory results.

The information supplied in this data sheet is based on our experience through extensive research and is given in good faith in order to help prospective users. We reserve the right to update the information provided in our technical data sheet at any time without prior notice within the scope of technical progress or new developments.