



OPCIEAS™

SOLINGEN 39400-39406

Class: S2 according to PN-EN 14450-1

Multi-walled door with overall thickness 95 mm with plate thickness 28 mm, Door with 3-sided bolted. Rigid grasp door construction on the hinge side.

Standard option: Double bit key lock VdS class 1 with two keys (key length: 120 mm) Handle: metal, protruding 60 mm, External Hinges, Door opens to: 180 ° Bolt down holes: 2pcs in bottom (Ø 16mm)

Colour: RAL 7035 light grey		External dimensions in mm		Internal dimensions in mm		Door light		Weight kg			
Height	Width	Depth	Height	Width	Depth	Height	Width	Depth	Height	Width	Depth
39400	380	463	427	279	351	295	264	328	295	295	97.0
39401	440	463	427	339	351	295	324	328	295	295	104.0
39402	615	463	427	514	351	295	499	328	295	295	138.0
39403	775	463	427	674	351	295	659	328	295	295	156.0
39404	1137	704	471	1036	592	339	1021	569	339	339	315.0
39405	1322	704	471	1221	592	339	1206	569	339	339	340.0
39406	1507	704	471	1406	592	339	1391	569	339	339	375.0





OPCIEAS™

SOLINGEN OFFICE 39430-39444

Class: S2 according to PN-EN 14450-1

Multi-walled door with overall thickness 95 mm with plate thickness 28 mm, Door with 3-sided bolted. Rigid grasp door construction on the hinge side.

Standard option: Double bit key lock VdS class 1 with two keys (key length: 120 mm) Handle: metal, protruding 60 mm, External Hinges, Door opens to 180 ° Bolt down holes: 2pcs in bottom (Ø 16mm)

Colour: RAL 7035 light grey		External dimensions in mm			Internal dimensions in mm			Door light		Weight kg	
Height	Width	Depth		Height	Width	Depth	Height		Width	Depth	
39430	901	975	459	800	863	290	785	845	303	367.0	
39431	901	975	559	800	863	390	785	845	403	390.0	
39432	901	1128	459	800	1016	290	785	998	303	398.0	
39433	901	1128	559	800	1016	390	785	998	403	433.0	
39434	901	1282	459	800	1170	290	785	1152	303	439.0	
39435	901	1282	559	800	1170	390	785	1152	403	477.0	
39436	1045	975	506	944	863	337	929	845	350	410.0	
39437	1045	1128	506	944	1016	337	929	998	350	456.0	
39438	1045	1282	506	944	1170	337	929	1152	350	501.0	
39439	1189	975	459	1088	863	290	1073	845	303	429.0	
39440	1189	975	559	1088	863	390	1073	845	403	467.0	
39441	1189	1128	459	1088	1016	290	1073	998	303	477.0	
39442	1189	1128	559	1088	1016	390	1073	998	403	517.0	
39443	1189	1282	459	1088	1170	290	1073	1152	303	526.0	
39444	1189	1282	559	1088	1170	390	1073	1152	403	569.0	





OPCIEAS™

SOLINGEN SUPER 39450-39464

Class: S2 according to PN-EN 14450-1.

Multi-walled door with overall thickness 95 mm with plate thickness 28 mm, Door with 3-sided bolted. Rigid grasp door construction on the hinge side.

Standard option: Double bit key lock VdS class 1 with two keys (key length: 120 mm) Handle: metal, protruding 60 mm External Hinges, Door opens to 180 ° Bolt down holes: 2pcs in bottom (Ø 16mm)

Colour: RAL 7035 light grey CODE		External dimensions in mm			Internal dimensions in mm			Door light		Weight kg	
Height	Width	Depth	Height	Width	Depth	Height	Width	Depth	Height	Depth	
39450	1550	886	545	1449	774	390	1434	751	413	501.0	
39451	1550	886	445	1449	774	290	1434	751	313	466.0	
39452	1700	886	545	1599	774	390	1584	751	413	539.0	
39453	1700	886	445	1599	774	290	1584	751	313	502.0	
39454	1884	886	545	1783	774	390	1768	751	413	586.0	
39455	1884	886	445	1783	774	290	1768	751	313	545.0	
39456	1884	975	459	1783	863	290	1768	845	303	653.0	
39457	1884	975	559	1783	863	390	1768	845	403	696.0	
39458	1884	975	696	1783	863	527	1768	845	540	753.0	
39459	1884	1128	459	1783	1016	290	1768	998	303	740.0	
39460	1884	1128	559	1783	1016	390	1768	998	403	785.0	
39461	1884	1128	696	1783	1016	527	1768	998	540	846.0	
39462	1884	1282	459	1783	1170	290	1768	1152	303	833.0	
39463	1884	1282	559	1783	1170	390	1768	1152	403	880.0	
39464	1884	1282	696	1783	1170	527	1768	1152	540	945.0	





OPCIEAS™

DORTMUND 39500-39519

Wall thickness: 62 mm.

Multi-walled door with overall thickness 104 mm with plate thickness 42 mm Door with 3-sided bolted.

Rigid grasp door construction on the hinge side.

Standard option: Double bit key lock VdS class 1 with two keys (key length: 120 mm) External Hinges, door opens to 180 ° Bolt down holes: 2pcs in bottom (Ø 16mm)

Colour: RAL 7035 light grey CODE		External dimensions in mm			Internal dimensions in mm		Door light		Weight kg	
Height	Width	Depth	Height	Width	Depth	Height	Width	Depth	Width	Depth
39500	514	604	400	375	468	230	360	450	230	90.0
39501	606	636	510	467	500	340	452	482	340	134.0
39502	806	636	510	667	500	340	652	482	340	170.0
39503	906	636	510	767	500	340	752	482	340	180.0
39504	1006	636	510	867	500	340	852	482	340	191.0
39505	1206	636	510	1067	500	340	1052	482	340	231.0
39506	1506	806	550	1367	670	380	1352	652	380	310.0
39507	1806	806	550	1667	670	380	1652	652	380	356.0
39508	800	700	550	661	564	380	646	546	380	178.0
39509	1250	700	550	1111	564	380	1096	546	380	261.0
39510	1500	700	550	1361	564	380	1346	546	380	306.0
39511	1950	700	550	1811	564	380	1796	546	380	351.0
39512	1950	950	550	1759	814	358	1759	796	380	510.0
39513	1950	1260	550	1759	1124	358	1759	1106	380	622.0
39514	1806	1486	550	1615	1350	358	1615	1332	380	652.0
39515	1006	836	600	867	700	430	852	682	430	264.0
39516	1256	836	600	1117	700	430	1102	682	430	298.0
39517	1506	836	600	1367	700	430	1352	682	430	337.0
39518	1806	836	600	1667	700	430	1652	682	430	389.0
39519	1806	1200	600	1615	1064	408	1615	1046	430	689.0





OPCIEAS™

EMMERICH 39700-39711

Wall thickness:35 mm.

Multi-walled door with overall thickness 83 mm with plate thickness 21 mm, Door with 3-sided bolted. Rigid grasp door construction on the hinge side.

Standard option: Double bit key lock VdS class 1 with two keys (key length: 95 mm), Handle: metal, protruding 60 mm External Hinges, Door opens to 180°, Bolt down holes: 1 piece in the bottom (Ø 16 mm)

Colour: RAL 7035 light grey CODE		External dimensions in mm			Internal dimensions in mm			Door light		Weight kg	
Height	Width	Depth	Height	Width	Depth	Height	Width	Depth	Height	Width	Depth
39700	355	530	415	270	450	292	255	430	392		54.0
39701	455	455	415	370	375	292	355	355	292		50.0
39702	770	530	415	685	451	292	670	430	292		83.0
39703	1120	530	415	1035	451	292	1020	430	292		112.0
39704	1470	530	415	1385	451	292	1370	430	292		142.0
39705	1820	530	415	1735	451	292	1720	430	292		172.0
39706	770	870	495	685	791	372	670	770	372		127.0
39707	1120	870	495	1035	791	372	1020	770	372		172.0
39708	1470	870	495	1385	791	372	1370	770	372		216.0
39709	1820	870	495	1735	791	372	1720	770	372		261.0
39710	1120	1230	495	1035	1150	372	1020	1130	372		222.0
39711	1820	1230	495	1735	1150	372	1720	1130	372		337.0





OPCIEAS™

OSNABRÜCK 40550-40561

Wall thickness: 35 mm.

Multi-walled door with overall thickness 83 mm with plate thickness 21 mm, Door with 3-sided bolted. Rigid grasp door construction on the hinge side.

Standard option: Double bit key lock VdS class 1 with two keys (key length: 95 mm), Handle: metal, protruding 60 mm

External Hinges, Door opens to 180° Bolt down holes: 1 piece in the bottom (Ø 16 mm)

Colour: RAL 7035 light grey CODE		External dimensions in mm		Internal dimensions in mm		Door light		Weight kg		
Height	Width	Depth	Height	Width	Depth	Height	Width	Depth		
40550	355	530	415	270	450	292	255	430	292	60.0
40551	455	455	415	370	375	292	355	355	292	58.0
40552	770	530	415	685	450	292	670	430	292	95.0
40553	1120	530	415	1035	450	292	1020	430	292	128.0
40554	1470	530	415	1385	450	292	1370	430	292	161.0
40555	1820	530	415	1735	450	292	1720	430	292	194.0
40556	770	870	495	685	790	372	670	770	372	145.0
40557	1120	870	495	1035	790	372	1020	770	372	194.0
40558	1470	870	495	1385	790	372	1370	770	372	243.0
40559	1820	870	495	1735	790	372	1720	770	372	293.0
40560	1120	1230	495	1035	1150	372	1020	1130	372	250.0
40561	1820	1230	495	1735	1150	372	1720	1130	372	378.0





OPCIEAS™

DRESDEN 41000-41019

Wall thickness: 62 mm.

Multi-walled door with overall thickness 104 mm with plate thickness 42 mm, Door with 3-sided bolted.

Rigid grasp door construction on the hinge side.

Standard option: Double bit key lock VdS class 1 with two keys (key length: 120 mm), Handle: metal, protruding 60 mm

External Hinges, Door opens to 180 °, Bolt down holes: 1 piece in the bottom (Ø 16 mm)

Colour: RAL 7035 light grey CODE		External dimensions in mm			Internal dimensions in mm			Door light		Weight kg	
Height	Width	Depth	Height	Width	Depth	Height	Width	Depth	Width	Depth	
41000	514	604	400	375	468	230	360	450	230	111.0	
41001	606	636	510	467	500	340	452	482	340	148.0	
41002	806	636	510	667	500	340	652	482	340	180.0	
41003	906	636	510	767	500	340	752	482	340	199.0	
41004	1006	636	510	867	500	340	852	482	340	216.0	
41005	1206	636	510	1067	500	340	1052	482	340	249.0	
41006	1506	806	550	1367	670	380	1352	652	380	336.0	
41007	1806	806	550	1667	670	380	1652	652	380	422.0	
41008	800	700	550	661	564	380	646	546	380	202.0	
41009	1250	700	550	1111	564	380	1096	546	380	284.0	
41010	1500	700	550	1361	564	380	1346	546	380	329.0	
41011	1950	700	550	1811	564	380	1796	546	380	412.0	
41012	1950	950	550	1759	814	358	1759	796	380	521.0	
41013	1950	1260	550	1759	1124	358	1759	1106	380	648.0	
41014	1806	1486	550	1615	1350	358	1615	1332	380	672.0	
41015	1006	836	600	867	700	430	852	682	430	285.0	
41016	1256	836	600	1117	700	430	1102	682	430	337.0	
41017	1506	836	600	1367	700	430	1352	682	430	385.0	
41018	1806	836	600	1667	700	430	1652	682	430	452.0	
41019	1806	1200	600	1615	1064	408	1615	1046	430	598.0	





OPCIEAS™

DRESDEN-TORNA 41150-41155

Wall thickness: 62 mm.

Multi-walled door with overall thickness 104 mm with plate thickness 42 mm, Door with 3-sided bolted. Rigid grasp door construction on the hinge side.

Standard option:

Double bit key lock VdS class 1 with two keys (key length: 120 mm), Handle: metal, protruding 60 mm, External Hinges
Door opens to 180 °, Bolt down holes: 1 piece in the bottom (Ø 16 mm)

Colour: RAL 7035 light grey CODE		External dimensions in mm			Internal dimensions in mm			Door light		Weight kg	
Height	Width	Depth	Height	Width	Depth	Height	Width	Depth	Width	Depth	
41150	606	636	800	467	500	583	452	482	583	215.0	
41151	806	636	800	667	500	583	652	482	583	260.0	
41152	1006	636	800	867	500	583	852	482	583	315.0	
41153	1206	636	800	1067	500	583	1052	482	583	360.0	
41154	800	836	800	661	700	583	646	682	583	325.0	
41155	1250	836	800	1111	700	583	1096	682	583	430.0	





OPCIEAS™

DRESDEN-LAUSA 41200-41205

Wall thickness: 62 mm.

Multi-walled door with overall thickness 104 mm with plate thickness 42 mm, Door with 3-sided bolted. Rigid grasp door construction on the hinge side.

Standard option:

Double bit key lock VdS class 1 with two keys (key length: 78 mm), Handle: folding handle, plastic, protruding 12 mm

External Hinges, Door opens to 180°, Bolt down holes: 1 piece in the bottom (Ø 16 mm)

Colour: RAL 7035 light grey		External dimensions in mm			Internal dimensions in mm			Door light		Weight kg	
CODE	Height	Width	Depth	Height	Width	Depth	Height	Width	Depth		
	41200	606	740	895	460	409	724	438	403	724	262.0
	41201	806	740	895	660	409	724	638	403	724	313.0
	41202	1006	740	895	860	409	724	838	403	724	359.0
	41203	606	1260	860	460	736	694	438	738	694	367.0
	41204	806	1260	860	660	736	694	638	738	694	436.0
	41205	1006	1260	860	860	736	694	838	738	694	495.0





OPCIEAS™

BRÜSSEL 41400-41419

Fireproof class: LFS 30 P Class: S2 according to PN-EN 14450, Wall thickness: 62 mm. Multi-walled door with overall thickness 104 mm with plate thickness 42 mm, Door with 3-sided bolted. Rigid grasp door construction on the hinge side.

Standard option: Double bit key lock VdS class 1 with two keys (key length: 120 mm), Handle: metal, protruding 60 mm, External Hinges, Door opens to 180°, Bolt down holes: 1 piece in the bottom (Ø 16 mm) Stainless steel Color: RAL 7035 light grey

CODE	External dimensions in mm			Internal dimensions in mm			Door light			Weight kg		
	Height	Width	Depth	Height	Width	Depth	Height	Width	Depth	Height	Width	Depth
41400	514	604	400	375	468	230	360	450	230	108.0		
41401	606	636	510	467	500	340	452	482	340	146.0		
41402	806	636	510	667	500	340	652	482	340	183.0		
41403	906	636	510	767	500	340	752	482	340	201.0		
41404	1006	636	510	867	500	340	852	482	340	218.0		
41405	1206	636	510	1067	500	340	1052	482	340	256.0		
41406	1506	806	550	1367	670	380	1352	652	380	376.0		
41407	1806	806	550	1667	670	380	1652	652	380	445.0		
41408	800	700	550	661	564	380	646	546	380	204.0		
41409	1250	700	550	1111	564	380	1096	546	380	294.0		
41410	1500	700	550	1361	564	380	1346	546	380	341.0		
41411	1950	700	550	1811	564	380	1796	546	380	433.0		
41412	1950	950	550	1811	814	380	1796	796	380	537.0		
41413	1950	1260	550	1811	1124	380	1796	1106	380	663.0		
41414	1806	1486	550	1667	1350	380	1652	1332	380	709.0		
41415	1006	836	600	867	700	430	852	682	430	290.0		
41416	1256	836	600	1117	700	430	1102	682	430	350.0		
41417	1506	836	600	1367	700	430	1352	682	430	404.0		
41418	1806	836	600	1667	700	430	1652	682	430	477.0		
41419	1806	1200	600	1667	1064	430	1652	1046	430	624.0		





OPCIEAS TM

PARIS 41500-41519

Wall thickness: 52 mm.

Multi-walled door with overall thickness 109 mm with plate thickness 49 mm, Door with 3-sided bolted. Rigid grasp door construction on the hinge side.

Standard option: Double bit key lock VdS class 1 with two keys (key length: 145 mm) Handle: metal, protruding 60 mm External Hinges. Door opens to 180 °, Bolt down holes: 1 piece in the bottom (Ø 16 mm), Stainless steel, Colour: RAL 7035 light grey

CODE	External dimensions in mm			Internal dimensions in mm			Door light			Weight kg	
	Height	Width	Depth	Height	Width	Depth	Height	Width	Depth		
41500	514	604	400	395	488	234	380	470	234	230.0	
41501	606	636	510	487	520	344	472	502	344	319.0	
41502	806	636	510	687	520	344	672	502	344	394.0	
41503	906	636	510	787	520	344	772	502	344	430.0	
41504	1006	636	510	887	520	344	872	502	344	466.0	
41505	1206	636	510	1087	520	344	1072	502	344	541.0	
41506	1506	806	550	1387	690	384	1372	672	384	781.0	
41507	1806	806	550	1687	690	384	1672	672	384	910.0	
41508	800	700	550	681	584	384	666	566	384	439.0	
41509	1250	700	550	1131	584	384	1116	566	384	620.0	
41510	1500	700	550	1381	584	384	1366	566	384	719.0	
41511	1950	700	550	1831	584	384	1816	566	384	899.0	
41512	1950	950	550	1812	834	362	1278	816	384	1145.0	
41513	1950	1260	550	1812	1144	362	1278	1126	384	1368.0	
41514	1806	1486	550	1668	1370	362	1634	1352	384	1492.0	
41515	1006	836	600	887	720	434	872	702	434	618.0	
41516	1256	836	600	1137	720	434	1122	702	434	735.0	
41517	1506	836	600	1387	720	434	1372	702	434	847.0	
41518	1806	836	600	1687	720	434	1672	702	434	987.0	
41519	1806	1200	600	1668	1084	412	1634	1066	434	1308.0	





OPCIEAS™

PARIS-ORLY 41650-41655

Wall thickness: 52 mm.

Multi-walled door with overall thickness 109 mm with plate thickness 49 mm, Door with 3-sided bolted. Rigid grasp door construction on the hinge side.

Standard option: Double bit key lock VdS class 1 with two keys (key length: 145 mm), Handle: metal, protruding 60 mm, Hinges: external, Door opens to 180°, Bolt down holes: 4pcs. (Ø 16 mm) Colour: RAL 7035 light grey.

CODE	External dimensions in mm			Internal dimensions in mm			Door light		Weight kg	
	Height	Width	Depth	Height	Width	Depth	Height	Width	Depth	
41650	606	636	800	487	520	572	472	502	572	469.0
41651	806	636	800	687	520	572	672	502	572	576.0
41652	1006	636	800	887	520	572	872	502	572	683.0
41653	1206	636	800	1087	520	572	1072	502	572	789.0
41654	800	836	800	681	720	572	666	702	572	686.0
41655	1250	836	800	1131	720	572	1116	702	572	962.0





OPCIEAS™

PARIS-BASTILLE 41700-41705

Wall thickness: 52 mm. Multi-walled door with overall thickness 109 mm with plate thickness 49 mm, Door with 3-sided bolted. Rigid grasp door construction on the hinge side.

Standard option: Double bit key lock VdS class 1 with two keys (key length: 85 mm), Handle: folding handle, plastic, protruding 12 mm, Hinges: internal, Door opens to 90 °, Bolt down holes: 1 piece in the bottom (Ø 16 mm) Colour: RAL 7035 light grey

CODE	External dimensions in mm			Internal dimensions in mm			Door light	Weight kg		
	Height	Width	Depth	Height	Width	Depth	Height	Width	Depth	
41700	606	740	895	480	424	729	458	410	729	598.0
41701	806	740	895	680	424	729	658	410	729	722.0
41702	1006	740	895	880	424	729	858	410	729	845.0
41703	606	1260	860	480	746	694	458	749	694	853.0
41704	806	1260	860	680	746	694	658	749	694	1016.0
41705	1006	1260	860	880	746	694	858	749	694	1179.0





OPCIEAS™

ROM 42001-42019

Wall thickness: 60 mm. Multi-walled door with overall thickness 130 mm with plate thickness 70 mm, Door with 3-sided bolted. Rigid grasp door construction on the hinge side.

Standard option: Handle: metal, protruding 60 mm, Hinges: external, Door opens to 180 °, Bolt down holes: 1 piece in the bottom (Ø 16 mm), Colour: RAL 7035 light grey.

CODE	External dimensions in mm			Internal dimensions in mm			Door light	Weight kg		
	Height	Width	Depth	Height	Width	Depth	Height	Width	Depth	
42001	606	636	510	456	504	304	456	486	304	354.0
42002	806	636	510	656	504	304	656	486	304	447.0
42003	906	636	510	756	504	304	756	486	304	492.0
42004	1006	636	510	856	504	304	856	486	304	536.0
42005	1206	636	510	1056	504	304	1056	486	304	633.0
42006	1506	806	550	1356	674	344	1356	656	344	936.0
42007	1806	806	550	1656	674	344	1656	656	344	1100.0
42008	800	700	550	650	568	344	650	550	344	499.0
42009	1250	700	550	1100	568	344	1100	550	344	721.0
42010	1500	700	550	1350	568	344	1350	550	344	848.0
42011	1950	700	550	1800	568	344	1800	550	344	1019.0
42012	1950	950	550	1796	818	322	1762	800	344	1355.0
42013	1950	1260	550	1796	1128	322	1762	1110	344	1547.0
42014	1806	1486	550	1652	1354	322	1618	1336	344	1780.0
42015	1006	836	700	856	704	494	856	686	494	769.0
42016	1256	836	700	1106	704	494	1106	686	494	942.0
42017	1506	836	700	1356	704	494	1356	686	494	1067.0
42018	1806	836	700	1656	704	494	1656	686	494	1245.0
42019	1806	1200	700	1652	1068	472	1618	1050	494	1641.0





OPCIEAS™

ROM-AXA 42150-42155

Wall thickness: 60 mm. Multi-walled door with overall thickness 130 mm with plate thickness 70 mm, door with 3-sided bolted. Rigid grasp door construction on the hinge side.

Standard option: Handle: metal, protruding 60 mm, Hinges: external, Door opens to 180°, Bolt down holes: 4pcs. (Ø 16 mm), Colour: RAL 7035 light grey

CODE	External dimensions in mm			Internal dimensions in mm			Door light		Weight kg	
	Height	Width	Depth	Height	Width	Depth	Height	Width	Depth	
42150	606	636	800	456	504	529	456	486	529	510.0
42151	806	636	800	656	504	529	656	486	529	630.0
42152	1006	636	800	856	504	529	856	486	529	749.0
42153	1206	636	800	1056	504	529	1056	486	529	869.0
42154	800	836	800	650	704	529	650	686	529	753.0
42155	1250	836	800	1100	704	529	1100	686	529	1064.0





OPCIEAS™

ROM-MAGLIANA 42200-42205

Wall thickness: 60 mm. Multi-walled door with overall thickness 130 mm with plate thickness 70 mm, Door with 3-sided bolted. Rigid grasp door construction on the hinge side.

Standard option: Hinges: external, Door opens to 90°, Bolt down holes: 1 piece in the bottom (Ø 16 mm) Color: RAL 7035 light grey

CODE	External dimensions in mm			Internal dimensions in mm		Weight kg	
	Height	Width	Depth	Height	Width	Depth	
42200	606	740	895	464	393	683	643.0
42201	806	740	895	664	393	683	780.0
42202	1006	740	895	864	393	683	916.0
42203	606	1260	860	464	700	648	950.0
42204	806	1260	860	664	700	648	1134.0
42205	1006	1260	860	864	700	648	1319.0





OPCIEAS™

LONDON 42501-42519

Wall thickness: 60 mm. Multi-walled door with overall thickness 130 mm with plate thickness 70 mm

Door with 3-sided bolted. Rigid grasp door construction on the hinge side.

Standard option: Handle: metal, protruding 60 mm, Hinges: external, Door opens to 180°, Bolt down holes: 1 piece in the bottom (Ø 21 mm), Color: RAL 7035 light grey.

CODE	External dimensions in mm			Internal dimensions in mm			Door light		Weight kg	
	Height	Width	Depth	Height	Width	Depth	Height	Width	Depth	
42501	706	636	510	556	516	306	556	486	304	426.0
42502	806	636	510	656	516	306	656	486	304	471.0
42503	906	636	510	735	484	306	735	486	304	518.0
42504	1006	636	510	856	516	306	856	486	304	565.0
42505	1206	636	510	1056	504	304	1056	486	304	666.0
42506	1506	806	550	1356	686	346	1356	656	344	985.0
42507	1806	806	550	1635	654	346	1635	656	344	1157.0
42508	800	700	550	629	548	346	629	550	344	526.0
42509	1250	700	550	1079	548	346	1079	550	344	759.0
42510	1500	700	550	1350	580	346	1350	550	344	892.0
42511	1950	700	550	1779	548	346	1779	550	344	1074.0
42512	1950	950	550	1796	830	322	1762	800	344	1423.0
42513	1950	1260	550	1796	1108	322	1762	1110	344	1631.0
42514	1806	1486	550	1652	1334	322	1618	1336	344	1871.0
42515	1006	836	700	835	684	496	835	686	494	808.0
42516	1256	836	700	1106	716	496	1106	686	494	963.0
42517	1506	836	700	1356	716	496	1356	686	494	1120.0
42518	1806	836	700	1656	716	496	1656	686	494	1307.0
42519	1806	1200	700	1652	1080	472	1618	1050	494	1720.0





OPCIEAS™

AMSTERDAM 42701-42718

Wall thickness: 78 mm. Multi-walled door with overall thickness 144 mm with plate thickness 80 mm door with 3-sided bolted. Rigid grasp door construction on the hinge side.

Standard option: Handle: metal, protruding 60 mm, Hinges: external, Door opens to 180°, Bolt down holes: 1 piece in the bottom (Ø 21 mm) Colour: RAL 7035 light grey

CODE	External dimensions in mm			Internal dimensions in mm			Door light		Weight kg	
	Height	Width	Depth	Height	Width	Depth	Height	Width	Depth	
42701	842	672	538	656	504	299	650	486	299	576.0
42702	942	672	538	756	504	299	750	486	299	629.0
42703	1042	672	538	856	504	299	850	486	299	682.0
42704	1242	672	538	1056	504	299	1050	486	299	790.0
42705	1542	842	578	1356	674	339	1350	656	339	1158.0
42706	1842	842	578	1656	674	339	1650	656	339	1352.0
42707	836	736	578	650	568	339	644	550	339	641.0
42708	1286	736	578	1100	568	339	1094	550	339	905.0
42709	1536	736	578	1350	568	339	1344	550	339	1051.0
42710	1986	736	578	1800	568	339	1794	550	339	1315.0
42711	1986	986	578	1796	818	317	1762	800	339	1655.0
42712	1986	1296	578	1796	1128	317	1762	1110	339	2034.0
42713	1842	1522	578	1652	1354	317	1618	1336	339	2171.0
42714	1042	872	728	856	704	489	850	686	489	995.0
42715	1292	872	728	1106	704	489	1100	686	489	1180.0
42716	1542	872	728	1356	704	489	1350	686	489	1362.0
42717	1842	872	728	1656	704	489	1650	686	489	1583.0
42718	1842	1236	728	1652	1068	467	1618	1050	489	2066.0





OPCIEAS™

LEVERKUSEN SUPER 43100-43114

Multi-walled door with overall thickness 95 mm with plate thickness 28 mm, Door with 3-sided bolted. Rigid grasp door construction on the hinge side.

Standard option: Double bit key lock VdS class 1 with two keys (key length: 120 mm), Handle: metal, protruding 60 mm, Hinges: external, Door opens to 180°, Bolt down holes: 2 pieces in the bottom (Ø 21 mm) Colour: RAL 7035 light grey

CODE	External dimensions in mm			Internal dimensions in mm			Door light		Weight kg	
	Height	Width	Depth	Height	Width	Depth	Height	Width	Depth	
43100	1550	886	545	1449	774	390	1434	751	413	452.0
43101	1550	886	445	1449	774	290	1434	751	313	417.0
43102	1700	886	545	1599	774	390	1584	751	413	488.0
43103	1700	886	445	1599	774	290	1584	751	313	448.0
43104	1884	886	545	1783	774	390	1768	751	413	527.0
43105	1884	886	445	1783	774	290	1768	751	313	487.0
43106	1884	975	459	1783	863	290	1768	845	303	598.0
43107	1884	975	559	1783	863	390	1768	845	403	634.0
43108	1884	975	696	1783	863	527	1768	845	540	683.0
43109	1884	1128	459	1783	1016	290	1768	998	303	679.0
43110	1884	1128	559	1783	1016	390	1768	998	403	717.0
43111	1884	1128	696	1783	1016	527	1768	998	540	768.0
43112	1884	1282	459	1783	1170	290	1768	1152	303	765.0
43113	1884	1282	559	1783	1170	390	1768	1152	403	805.0
43114	1884	1282	696	1783	1170	527	1768	1152	540	860.0





OPCIEAS™

LEVERKUSEN OFFICE 43200-43214

Multi-walled door with overall thickness 95 mm with plate thickness 28 mm, Door with 3-sided bolted. Rigid grasp door construction on the hinge side.

Standard option: Double bit key lock VdS class 1 with two keys (key length: 120 mm), Handle: metal, protruding 60 mm, Hinges: external, Door opens to 180°, Bolt down holes: 2 pieces in the bottom (Ø 21 mm) Colour: RAL 7035 light grey

CODE	External dimensions in mm			Internal dimensions in mm			Door light	Weight kg		
	Height	Width	Depth	Height	Width	Depth	Height	Width	Depth	
43200	901	975	459	800	863	290	785	845	303	336.0
43201	901	975	559	800	863	390	785	845	403	355.0
43202	901	1128	459	800	1016	290	785	998	303	363.0
43203	901	1128	559	800	1016	390	785	998	403	394.0
43204	901	1282	459	800	1170	290	785	1152	303	399.0
43205	901	1282	559	800	1170	390	785	1152	403	433.0
43206	1045	975	506	944	863	337	929	845	350	373.0
43207	1045	1128	506	944	1016	337	929	998	350	414.0
43208	1045	1282	506	944	1170	337	929	1152	350	455.0
43209	1189	975	459	1088	863	290	1073	845	303	390.0
43210	1189	975	559	1088	863	390	1073	845	403	424.0
43211	1189	1128	459	1088	1016	290	1073	998	303	434.0
43212	1189	1128	559	1088	1016	390	1073	998	403	469.0
43213	1189	1282	459	1088	1170	290	1073	1152	303	477.0
43214	1189	1282	559	1088	1170	390	1073	1152	403	516.0





OPCIEAS™

KÖLN SUPER 44100-44114

Multi-walled door with overall thickness 95 mm with plate thickness 28 mm. Door with 3-sided bolted. Rigid grasp door construction on the hinge side.

Standard option: Double bit key lock VdS class 1 with two keys (key length: 120 mm), Handle: metal, protruding 60 mm , Hinges: external, Door opens to 180°, Bolt down holes: 2 pieces in the bottom (Ø 21 mm), Colour: RAL 7035 light grey

CODE	External dimensions in mm			Internal dimensions in mm			Door light		Weight kg	
	Height	Width	Depth	Height	Width	Depth	Height	Width	Depth	
44100	1550	886	545	1449	774	390	1434	751	413	501.0
44101	1550	886	445	1449	774	290	1434	751	313	466.0
44102	1700	886	545	1599	774	390	1584	751	413	539.0
44103	1700	886	445	1599	774	290	1584	751	313	502.0
44104	1884	886	545	1783	774	390	1768	751	413	586.0
44105	1884	886	445	1783	774	290	1768	751	313	545.0
44106	1884	975	459	1783	863	290	1768	845	303	653.0
44107	1884	975	559	1783	863	390	1768	845	403	696.0
44108	1884	975	696	1783	863	527	1768	845	540	753.0
44109	1884	1128	459	1783	1016	290	1768	998	303	740.0
44110	1884	1128	559	1783	1016	390	1768	998	403	785.0
44111	1884	1128	696	1783	1016	527	1768	998	540	846.0
44112	1884	1282	459	1783	1170	290	1768	1152	303	833.0
44113	1884	1282	559	1783	1170	390	1768	1152	403	880.0
44114	1884	1282	696	1783	1170	527	1768	1152	540	945.0





OPCIEAS™

KÖLN OFFICE 44200-44214

Wall thickness:50 mm. Multi-walled door with overall thickness 95 mm with plate thickness 28 mm
Door with 3-sided bolted. Rigid grasp door construction on the hinge side.

Standard option: Double bit key lock VdS class 1 with two keys (key length: 120 mm), Handle: metal, protruding 60 mm,
Hinges: external, Door opens to 180°, Bolt down holes: 1 piece in the bottom (Ø 21 mm) Colour: RAL 7035 light grey

CODE	External dimensions in mm			Internal dimensions in mm			Door light	Weight kg		
	Height	Width	Depth	Height	Width	Depth	Height	Width	Depth	
44200	901	975	459	800	863	290	785	845	303	367.0
44201	901	975	559	800	863	390	785	845	403	390.0
44202	901	1128	459	800	1016	290	785	998	303	398.0
44203	901	1128	559	800	1016	390	785	998	403	433.0
44204	901	1282	459	800	1170	290	785	1152	303	439.0
44205	901	1282	559	800	1170	390	785	1152	403	477.0
44206	1045	975	506	944	863	337	929	845	350	410.0
44207	1045	1128	506	944	1016	337	929	998	350	456.0
44208	1045	1282	506	944	1170	337	929	1152	350	501.0
44209	1189	975	459	1088	863	290	1073	845	303	429.0
44210	1189	975	559	1088	863	390	1073	845	403	467.0
44211	1189	1128	459	1088	1016	290	1073	998	303	477.0
44212	1189	1128	559	1088	1016	390	1073	998	403	517.0
44213	1189	1282	459	1088	1170	290	1073	1152	303	526.0
44214	1189	1282	559	1088	1170	390	1073	1152	403	569.0





OPCIEAS™

WUPPERTAL SUPER 44600-44614

Wall thickness: 50 mm. Multi-walled door with overall thickness 105 mm with plate thickness 28 mm

Door with 3-sided bolted. Rigid grasp door construction on the hinge side.

Standard option: Double bit key lock VdS class 1 with two keys (key length: 120 mm), Handle: metal, protruding 60 mm,

Hinges: external, Door opens to 180°, Bolt down holes: 1 piece in the bottom (Ø 21 mm) Colour: RAL 7035 light grey

CODE	External dimensions in mm			Internal dimensions in mm			Door light		Weight kg	
	Height	Width	Depth	Height	Width	Depth	Height	Width	Depth	
44600	1550	886	545	1449	774	380	1434	751	403	509.0
44601	1550	886	445	1449	774	280	1434	751	303	474.0
44602	1700	886	545	1599	774	380	1584	751	403	547.0
44603	1700	886	445	1599	774	280	1584	751	303	509.0
44604	1884	886	545	1783	774	380	1768	751	403	586.0
44605	1884	886	445	1783	774	280	1768	751	303	553.0
44606	1884	975	459	1783	863	280	1768	845	293	659.0
44607	1884	975	559	1783	863	380	1768	845	393	701.0
44608	1884	975	696	1783	863	517	1768	845	530	759.0
44609	1884	1128	459	1783	1016	280	1768	998	293	746.0
44610	1884	1128	559	1783	1016	380	1768	998	393	790.0
44611	1884	1128	696	1783	1016	517	1768	998	530	851.0
44612	1884	1282	459	1783	1170	280	1768	1152	293	839.0
44613	1884	1282	559	1783	1170	380	1768	1152	393	886.0
44614	1884	1282	696	1783	1170	517	1768	1152	530	951.0





OPCIEAS™

WUPPERTAL OFFICE 44650-44664

Wall thickness:50 mm. Multi-walled door with overall thickness 105 mm with plate thickness 28 mm

Door with 3-sided bolted. Rigid grasp door construction on the hinge side.

Standard option: Double bit key lock VdS class 1 with two keys (key length: 120 mm), Handle: metal, protruding 60 mm,

Hinges: external, Door opens to 180°, Bolt down holes: 1 piece in the bottom (Ø 16 mm), Colour: RAL 7035 light grey

CODE	External dimensions in mm			Internal dimensions in mm			Door light	Weight kg		
	Height	Width	Depth	Height	Width	Depth	Height	Width	Depth	
44650	901	975	459	800	863	280	785	845	293	375.0
44651	901	975	559	800	863	380	785	845	393	398.0
44652	901	1128	459	800	1016	280	785	998	293	406.0
44653	901	1128	559	800	1016	380	785	998	393	441.0
44654	901	1282	459	800	1170	280	785	1152	293	447.0
44655	901	1282	559	800	1170	380	785	1152	393	485.0
44656	1045	975	506	944	863	327	929	845	340	418.0
44657	1045	1128	506	944	1016	327	929	998	340	464.0
44658	1045	1282	506	944	1170	327	929	1152	340	510.0
44659	1189	975	459	1088	863	280	1073	845	293	437.0
44660	1189	975	559	1088	863	380	1073	845	393	475.0
44661	1189	1128	459	1088	1016	280	1073	998	293	486.0
44662	1189	1128	559	1088	1016	380	1073	998	393	526.0
44663	1189	1282	459	1088	1170	280	1073	1152	293	535.0
44664	1189	1282	559	1088	1170	380	1073	1152	393	578.0





OPCIEAS™

WIEN 44700-44705

Wall thickness: 62 mm. Multi-walled door with overall thickness 114 mm with plate thickness 36 mm
Door with 3-sided bolted. Rigid grasp door construction on the hinge side.

Standard option: Double bit key lock VdS class 1 with two keys (key length: 145 mm) Handle: metal, protruding 60 mm,
Hinges: external, Door opens to 180°, Bolt down holes: 1 piece in the bottom (Ø 16 mm) Colour: RAL 7035 light grey.

CODE	External dimensions in mm			Internal dimensions in mm			Door light		Weight kg	
	Height	Width	Depth	Height	Width	Depth	Height	Width	Depth	
44700	503	595	497	364	457	296	358	454	319	186.0
44701	635	595	497	496	457	296	490	454	319	230.0
44702	822	595	497	683	457	296	677	454	319	280.0
44703	1158	710	497	1019	572	296	1013	569	319	420.0
44704	1343	710	497	1204	572	296	1198	569	319	451.0
44705	1528	710	497	1389	572	296	1383	569	319	520.0





OPCIEAS™

ROM-LIDO 44800-44804

Wall thickness: 60 mm.

Multi-walled door with overall thickness 130 mm with plate thickness 70 mm, Door with 3-sided bolted. Rigid grasp door construction on the hinge side.

Standard option: Handle: metal, protruding 60 mm, Hinges: external, Door opens to 180°, Bolt down holes: 1 piece in the bottom (Ø 16 mm) Colour: RAL 7035 light grey

CODE	External dimensions in mm			Internal dimensions in mm			Door light		Weight kg	
	Height	Width	Depth	Height	Width	Depth	Height	Width	Depth	
44800	776	591	660	514	351	272	499	272	295	631.0
44801	936	591	660	674	351	272	659	272	295	770.0
44802	1298	832	704	1036	592	316	1021	513	339	1340.0
44803	1483	832	704	1221	592	316	1206	513	339	1485.0
44804	1668	832	704	1406	592	316	1391	513	339	1640.0





OPCIEAS™

HAMBURG 45000-45006

Wall thickness: 72 mm. Multi-walled door with overall thickness 132 mm with plate thickness 37 mm, Door with 3-sided bolted. Rigid grasp door construction on the hinge side.

Standard option: Double bit key lock VdS class 1 with two keys (key length: 120 mm), Handle: metal, protruding 60 mm, Hinges: external , Door opens to 180°, Bolt down holes: 2pcs in bottom (Ø 16mm), Colour: RAL 7035 light grey

CODE	External dimensions in mm			Internal dimensions in mm			Door light		Weight kg	
	Height	Width	Depth	Height	Width	Depth	Height	Width	Depth	
45000	489	605	560	273	448	359	252	418	386	168.0
45001	590	605	560	374	448	359	353	418	386	187.0
45002	1050	605	560	769	448	340	730	385	367	323.0
45003	1400	794	560	1109	637	331	1063	557	358	483.0
45004	1600	794	560	1309	637	331	1263	557	358	577.0
45005	1800	794	560	1509	637	331	1463	557	358	708.0
45006	1800	1350	560	1505	1193	331	1453	1103	358	995.0





OPCIEAS™

HAMBURG SUPER 45100-45101

Wall thickness: 72 mm. Multi-walled door with overall thickness 132 mm with plate thickness 37 mm, door with 3-sided bolted. Rigid grasp door construction on the hinge side.

Standard option: Double bit key lock VdS class 1 with two keys (key length: 120 mm), Handle: metal, protruding 60 mm, Hinges: external, Door opens to 180°, Bolt down holes: 1 piece in the bottom (Ø 16 mm) Colour: RAL 7035 light grey.

CODE	External dimensions in mm			Internal dimensions in mm			Door light	Weight kg		
	Height	Width	Depth	Height	Width	Depth	Height	Width	Depth	
45100	1800	1766	560	1505	1609	331	1453	1519	358	1215.0
45101	2033	1766	560	1738	1609	331	1686	1519	358	1340.0





OPCIEAS™

BERLIN 46000-46006

Wall thickness: 72 mm. Multi-walled door with overall thickness 132 mm with plate thickness 37 mm, door with 3-sided bolted. Rigid grasp door construction on the hinge side.

Standard option: Double bit key lock VdS class 1 with two keys (key length: 120 mm), Handle: metal, protruding 60 mm, Hinges: external , Door opens to 180°, Bolt down holes: 1 piece in the bottom (Ø 16 mm) Colour: RAL 7035 light grey

CODE	External dimensions in mm			Internal dimensions in mm			Door light		Weight kg	
	Height	Width	Depth	Height	Width	Depth	Height	Width	Depth	
46000	489	605	560	273	448	359	252	418	386	178.0
46001	590	605	560	374	448	359	353	418	386	198.0
46002	1050	605	560	769	448	340	730	385	367	335.0
46003	1400	794	560	1109	637	331	1063	557	358	497.0
46004	1600	794	560	1309	637	331	1263	557	358	593.0
46005	1800	794	560	1509	637	331	1463	557	358	728.0
46006	1800	1350	560	1505	1193	331	1453	1103	358	1025.0





OPCIEAS™

BERLIN SUPER 46007-46008

Wall thickness:72 mm. Multi-walled door with overall thickness 132 mm with plate thickness 37 mm, door with 3-sided bolted. Rigid grasp door construction on the hinge side.

Standard option: Double bit key lock VdS class 1 with two keys (key length: 120 mm), Handle: metal, protruding 60 mm,Hinges: external, Door opens to 180°, Bolt down holes: 1 piece in the bottom (Ø 16 mm), Colour: RAL 7035 light grey

CODE	External dimensions in mm			Internal dimensions in mm			Door light		Weight kg	
	Height	Width	Depth	Height	Width	Depth	Height	Width	Depth	
46007	1800	1766	560	1505	1609	331	1453	1519	358	1310.0
46008	2033	1766	560	1738	1609	331	1686	1519	358	1460.0





OPCIEAS™

PRAG 46100-46108

Wall thickness: 86 mm. Multi-walled door with overall thickness 135 mm with plate thickness 42 mm, door with 3-sided bolted. Rigid grasp door construction on the hinge side.

Standard option: Double bit key lock VdS class 1 with two keys (key length: 120 mm), Handle: metal, protruding 60 mm, Hinges: external, Door opens to 180°, Bolt down holes: 1 piece in the bottom (Ø 16 mm) Colour: RAL 7035 light grey

CODE	External dimensions in mm			Internal dimensions in mm			Door light		Weight kg	
	Height	Width	Depth	Height	Width	Depth	Height	Width	Depth	
46100	550	632	573	317	448	321	304	436	350	240.0
46101	600	632	573	367	448	321	354	436	350	264.0
46102	1068	619	565	769	435	324	739	390	352	389.0
46103	1418	821	573	1110	637	321	1072	574	350	623.0
46104	1618	821	573	1310	637	321	1272	574	350	700.0
46105	1811	821	573	1503	637	321	1465	574	350	774.0
46106	1821	1377	573	1507	1193	321	1465	1121	341	1139.0
46107	1821	1775	573	1507	1591	321	1465	1519	341	1452.0
46108	2042	1775	573	1728	1591	321	1686	1519	341	1605.0





OPCIEAS™

OSLO 46500-46503

Security class A certified by VDMA issued May 1995.

Wall thickness:80 mm. Multi-walled door with overall thickness 151 mm with plate thickness 27 mm,door with 3-sided bolt work. Rigid grasp door construction on the hinge side.

Standard option: Double bit key lock VdS class 1 with two keys (key length: 120 mm), Handle: metal, 60mm protruding

Bolt down holes: 2pcs in bottom (Ø 16mm), Colour: RAL 7035 light grey

CODE	External dimensions in mm			Internal dimensions in mm			Door light	Weight kg	
	Height	Width	Depth	Height	Width	Depth	Height	Width	Depth
46500	635	635	540	630	400	380	397	397	200.0
46501	635	635	540	755	400	380	522	522	225.0
46502	1270	1270	540	630	800	380	397	397	400.0
46503	1270	1270	540	755	800	380	522	522	450.0





OPCIEAS™

BERGEN 46550-46551

Security class A certified by VDMA issued on May 1995.

Wall thickness: 80 mm, Multi-walled door with overall thickness 151 mm with plate thickness 27 mm, door with 3-sided bolt work. Rigid grasp door construction on the hinge side.

Standard option: Double bit key lock VdS class 1 with two keys (key length: 120 mm), Handle: metal, 60 mm protruding, Bolt down holes: 2pcs in bottom (Ø 16mm), Colour: RAL 7035 light grey

CODE	External dimensions in mm			Internal dimensions in mm			Door light		Weight kg	
	Height	Width	Depth	Height	Width	Depth	Height	Width	Depth	
46550	635	563	630	400	368	397	400	368	397	197.0
46551	635	563	755	400	368	522	400	368	522	222.0





OPCIEAS™

STOCKHOLM 46700-46703

Wall thickness: 80 mm.

Multi-walled door with overall thickness 151 mm with plate thickness 27 mm, Door with 3-sided bolted. Rigid grasp door construction on the hinge side.

Standard option: Double bit key lock VdS class 1 with two keys (key length: 120 mm), Handle: metal, protruding 60 mm, Bolt down holes: 2pcs in bottom (Ø 16mm) Colour: RAL 7035 light grey

CODE		External dimensions in mm			Internal dimensions in mm			Door light	Weight kg	
Height	Width	Depth	Height	Width	Depth	Height	Width	Depth		
46700	635	540	630	400	380	397	397	200.0		
46701	635	540	755	400	380	522	522	226.0		
46702	1270	540	630	800	380	397	397	400.0		
46703	1270	540	755	800	380	522	522	452.0		





OPCIEAS™

GÖTEBORG 46750-46751

Wall thickness: 80 mm, Multi-walled door with overall thickness 151 mm with plate thickness 27 mm door with 3-sided bolt work. Rigid grasp door construction on the hinge side.

Standard option: Double bit key lock VdS class 1 with two keys (key length: 120 mm), Handle: metal, protruding 60 mm, Hinges: external, Door opens to 180°, Bolt down holes: 2pcs in bottom (Ø 16mm), Colour: RAL 7035 light grey

CODE	External dimensions in mm			Internal dimensions in mm			Door light		Weight kg	
	Height	Width	Depth	Height	Width	Depth	Height	Width	Depth	
46750	635	563	630	400	368	397	400	368	397	198.0
46751	635	563	755	400	368	522	400	368	522	223.0





OPCIEAS™

KOPENHAGEN 46760-46763

Wall thickness:101 mm, Multi-walled door with overall thickness 173 mm with plate thickness 48 mm, door with 3-sided bolted. Rigid grasp door construction on the hinge side.

Standard option: Double bit key lock VdS class 1 with two keys (key length: 120 mm),Handle: metal, protruding 60 mm, Hinges: external, Door opens 180°, Bolt down holes: 2pcs in bottom (Ø 16mm), Colour: RAL 7035 light grey

CODE	External dimensions in mm			Internal dimensions in mm			Door light		Weight kg	
	Height	Width	Depth	Height	Width	Depth	Height	Width	Depth	
46760	1143	714	662	887	493	388	887	493	388	433.0
46761	1143	800	730	887	579	456	887	579	456	501.0
46762	1300	800	730	1044	579	456	1044	579	456	560.0
46763	1456	886	798	1200	665	524	1200	665	524	707.0





OPCIEAS™

PARIS-VERSAILLES 46800-46807

Multi-walled door thickness: 52 mm, Multi-walled door with overall thickness 109 mm with plate thickness 49 mm, Door with 3-sided bolt work. Rigid grasp door construction on the hinge side.

Standard option: Double bit key lock VdS class 1 with two keys (key length: 145 mm), Handle: metal, protruding 60 mm, Hinges: external, Door opens 180°, Bolt down holes: 2pcs in bottom (Ø 16mm), Colour: RAL 7035 light grey

CODE	External dimensions in mm			Internal dimensions in mm			Door light		Weight kg	
	Height	Width	Depth	Height	Width	Depth	Height	Width	Depth	
46800	779	684	815	675	568	651	645	516	351	740.0
46801	779	684	950	675	568	786	645	516	351	815.0
46802	1079	684	815	975	568	651	945	516	651	880.0
46803	1079	684	950	975	568	786	945	516	651	950.0
46804	1414	684	815	1310	568	651	1280	516	986	1220.0
46805	1414	684	950	1310	568	786	1280	516	986	1290.0
46806	1714	684	815	1610	568	651	1580	516	1286	1315.0
46807	1714	684	950	1610	568	786	1580	516	1286	1395.0





OPCIEAS™

HELSINKI 46850-46853

Wall thickness: 101 mm, Multi-walled door with overall thickness 173 mm with plate thickness 48 mm door with 3-sided bolted. Rigid grasp door construction on the hinge side.

Standard option: Double bit key lock VdS class 1 with two keys (key length: 120 mm), Handle: metal, protruding 60 mm, Hinges: external, Door opens 180°, Bolt down holes: 2pcs in bottom (Ø 16mm) Colour: RAL 7035 light grey

CODE	External dimensions in mm			Internal dimensions in mm			Door light		Weight kg	
	Height	Width	Depth	Height	Width	Depth	Height	Width	Depth	
46850	1143	714	662	887	493	388	887	493	388	453.0
46851	1143	800	730	887	579	456	887	579	456	524.0
46852	1300	800	730	1044	579	456	1044	579	456	585.0
46853	1456	886	798	1200	665	524	1200	665	524	740.0





OPCIEAS™

ROM-ROMAGNA 46900-46907

Multilayer fireproof wall thickness: 60 mm, Multi-walled door with overall thickness 130 mm with plate thickness 70 mm, Door with 3-sided bolted. Rigid grasp door construction on the hinge side.

Standard option: Lock: class 2 VdS safe lock, Handle: metal, protruding 60 mm, Hinges: external, Door opens 180°, Bolt down holes: 2pcs in bottom (Ø 16mm), Colour: RAL 7035 light grey.

CODE	External dimensions in mm			Internal dimensions in mm			Door light		Weight kg	
	Height	Width	Depth	Height	Width	Depth	Height	Width	Depth	
46900	795	700	853	675	580	647	645	522	647	820.0
46901	795	700	988	675	580	782	645	522	782	895.0
46902	1095	700	853	975	580	647	945	522	647	990.0
46903	1095	700	988	975	580	782	945	522	782	1085.0
46904	1430	700	853	1310	580	647	1280	522	647	1220.0
46905	1430	700	988	1310	580	782	1280	522	782	1335.0
46906	1730	700	853	1610	580	647	1580	522	647	1450.0
46907	1730	700	988	1610	580	782	1580	522	782	1580.0

