



OPCIEAS™

SAFE ROOM DOORS

ROSTOCK 32000-32002 Safe room door

Class: S2 according to PN-EN 14450, Class: B according to VDMA 24992 issued May 1995.

Door is made of steel 3 mm thick, multi-walled 52 mm with plate thickness 6 mm
Bolted 3-sides, Rigid grasp door construction on the hinge side.

Standard option: Lock: VdS class 1 with two keys (120 mm length), Handle: made of metal protruding 60 mm, Hinges: external
, Door opens 180°, Color: RAL 7035 light grey.

CODE	External dimensions in mm			Door light		Weight kg	
	Height	Width	Depth	Height	Width	Depth	
32000	1500	900	240	1386	746	151.0	
32001	1800	900	240	1686	746	171.0	
32002	2000	1000	240	1886	846	205.0	





OPCIEAS™

SAFE ROOM DOORS

WISMAR 32300-32305, Safe room door

Frame with thickness 32 mm, Multi-walled door with overall thickness 52 mm and plate thickness 6 mm. Bolted 3-sides, Rigid grasp door construction on the hinge side it is suitable for mounting on wall with concrete and fixing with the use of anchor bolts.

Standard option: Lock: safe lock with two keys, Handle: made of metal protruding 60 mm, Hinges: external, Door opens to 180°, Bolt down holes: 3pcs, from left side and 3pcs, from the right side Ø 11 mm, Colour: RAL 7035 light grey

CODE	External dimensions in mm			Door light		Weight kg	
	Height	Width	Depth	Height	Width	Depth	
32300	2000	750	120	1936	686	81.0	
32301	2000	750	240	1936	686	93.0	
32302	2000	830	120	1936	766	86.0	
32303	2000	830	240	1936	766	98.0	
32304	2000	1000	120	1936	936	95.0	
32305	2000	1000	240	1936	936	108.0	





OPCIEASTM

SAFE ROOM DOORS

EISENACH 55300-55302 Safe room door

Class: S2 according to PN-EN 14450, Class: B according to VDMA 24992 issued May 1995.

Multi-walled body with thickness 62 mm, multi-walled door with overall thickness 104mm Bolted 3-sides, Rigid grasp door construction on the hinge side.

Standard option: Lock: VdS class 1 with two keys (120 mm length), Handle: made of metal protruding 60mm, Hinges: external, Door opens to 180°, Color: RAL 7035 light grey

CODE		External dimensions in mm		Internal dimensions in mm		Door light		Weight kg	
Height	Width	Depth	Height	Width	Depth	Height	Width	Depth	
55300	1700	900	240	1605	740	1605	740	166.0	
55301	1800	900	240	1705	740	1705	740	175.0	
55302	2000	1000	240	1905	840	1905	840	205.0	





OPCIEAS™

SAFE ROOM DOORS

DRESDEN-FREITAL 55350-55352 Safe room door

Class: I according to EN 1143-1 European standard.

Multi-walled body with thickness 62mm, multi-walled door with overall thickness 104 mm with plate thickness 42mm, bolted multisided locking and rigid grasp door construction on the hinge side.

Standard option: Double bit key lock VdS class 1 with two keys (key length: 120 mm), Handle: made of metal protruding 60 mm, Hinges: external, Door opens to 180°, Color: RAL 7035 light grey.

CODE		External dimensions in mm		Internal dimensions in mm		Door light		Weight kg	
Height	Width	Depth	Height	Width	Depth	Height	Width	Depth	
55350	1700	900	240	1590	740	1590	740	205.0	
55351	1800	900	240	1690	740	1690	740	220.0	
55352	2000	1000	240	1890	840	1890	840	265.0	

