FROMM | PACKAGING SYSTEMS

# Datasheet P329

**Battery powered manual plastic strapping tool**

## Battery powered plastic strapping tool for demanding applications




## Characteristics

| | |
|---|---|
| Strapping qualities: | Polyester (PET) and Polypropylene (PP) plain and embossed |
| Strapping dimensions: | width 16.0 – 19.0 mm / 5/8 – 3/4"<br>thickness 0.65 – 1.35 mm / .026 – .053" |
| Weight incl. battery: | 4.2 kg / 9.3 lbs |
| Tool size with battery: | L351 x W134 x H143 mm / 13.8" x 5.3" x 5.6" |
| Type of seal: | Friction weld sealing |
| Average seal strength: | approx. 75% (dependent on strap quality) |
| Tension force: | 500 – 4000 N / 112 – 900 lbs (adjustable) |
| Tension speed: | 49 – 79 mm/s / 1.9 – 3.1 inch/s |
| Power supply: | Battery Li-Ion 18VDC / 4.0 Ah |
| Suspension bracket: | optional |

## Advantages

- High tension force up to 4000N / 900 lbs
- Tension force and sealing time adjustable with simple knobs
- Tool in both semi-automatic and automatic (single button) version available for efficient operation
- Brushless motor for less maintenance and improved life time
- Improved plates and guides – less effort to remove the tool from the strap
- No tension rocker – easier to remove tool from small package surfaces
- Motor temperature monitoring to protect motor from overheating
- Cycle counter included (special reader required)
- Battery well protected
- Battery charge indicator included
- Simple one-handed operation
- Tool is fully covered for finger protection
- Optional motor cooling fan available to reduce overheating risk

FROMM Holding AG
Hinterbergstrasse 26
CH-6330 Cham
Switzerland

Tel. +41 (041) 741 57 41
Fax +41 (041) 741 57 65
www.fromm-pack.com
hold.ch@fromm-pack.com