



**KUMAR CERAMICS PRIVATE LIMITED**

PRICE LIST NO. : KCPL/04/2013




Decide with Confidence

**MATERIAL GRADE : K-60**

**REFRACTORY SHEATHS ONE END CLOSED**

to withstand temperature upto 1600 C.




OUTER MM	6	8	10	12	15	18	20	22	24	29	32
DIAMETER											
INNER MM	4	5	7	8	11	13	15	17	19	22	25
LENGTH	PRICE IN INR										
OVER UPTO											
100 MM 300 MM	74	102	110	110	134	147	158	182	208	222	232
301 MM 450 MM	89	119	124	124	140	152	167	186	195	234	242
451 MM 610 MM	141	212	232	232	247	257	296	340	362	405	464
611 MM 750 MM	177	267	291	291	306	317	365	418	453	509	528
751 MM 1030 MM	238	356	397	397	430	453	509	587	630	711	748
1031 MM 1200 MM	285	428	623	623	637	672	704	770	813	843	855
1201 MM 1300 MM	362	542	673	673	923	950	973	1015	1073	1129	1146
1300 MM 1500 MM	456	597	741	741	1015	1044	1073	1116	1179	1240	1259

TOLERANCE : +/- 1 MM IN O/D & I/D & +/- 3 MM IN LENGTH.

**MATERIAL GRADE : K-80**

**REFRACTORY SHEATHS ONE END CLOSED**

to withstand temperature upto 1700 C.




OUTER MM	6	8	10	12	15	18	20	22	24	29	32
DIAMETER											
INNER MM	4	5	7	8	11	13	15	17	19	22	25
LENGTH	PRICE IN INR										
OVER UPTO											
100 MM 450 MM	290	323	378	378	430	461	512	572	593	712	741
451 MM 610 MM	486	539	630	630	668	722	802	920	979	1099	1262
611 MM 750 MM	581	647	786	786	831	888	988	1136	1224	1380	1432
751 MM 1030 MM	864	960	1076	1076	1165	1241	1380	1589	1706	1929	2026
1031 MM 1200 MM	1475	1639	1691	1691	1729	1716	1906	2085	2205	2285	2777
1201 MM 1300 MM	1533	1703	1856	1856	2545	2418	2686	2797	2946		
1300 MM 1500 MM	1687	1874	2042	2042	2799	2660	2956	3078	3241		

TOLERANCE : +/- 1 MM IN O/D & I/D & +/- 3 MM IN LENGTH.

**MATERIAL GRADE : K-99**

**REFRACTORY SHEATHS ONE END CLOSED**

to withstand temperature upto 1800 C.



OUTER MM	6	8	10	12	15	18	20	24	32	
DIAMETER										
INNER MM	4	5	7	8	11	13	15	19	25	
LENGTH	PRICE IN INR									
OVER UPTO										
100 MM 450 MM		835	928	1031	1031	1157	1234	1412	1695	2804
451 MM 610 MM		1035	1150	1277	1277	1362	1888	2190	2258	3801
611 MM 750 MM		1590	1767	1962	1962	2120	2759	3210	3390	4673
751 MM 1030 MM		2080	2311	2567	2567	2685	3340	3819	4098	6602
1031 MM 1200 MM		2410	2677	2976	2976	3414	3896	4244	4451	7679
1201 MM 1300 MM		3497	3885	4318	4318	4509	4787	4880	5092	8377

TOLERANCE : +/- 1 MM IN O/D & I/D & +/- 3 MM IN LENGTH.  
 PERMISSIBLE BEND UPTO 1300 MM SHOULD BE ALLOWED UPTO 4 MM.