



UNCONFINED COMPRESSION TESTER-(MOTORISED)-(IS 2720-PART X)

Compliance Standards:

IS : 2720 (PART-X), IS : 4332 (PART-V)

Details:

1. A screw operated load frame **capacity 50 KN (5000 kgf)** with a gear box and motor drive giving **1.25, 1.5 and 2.5mm/min, rates of strain**, Suitable for operating on 230 volts, single phase AC.
2. Cone seating : One pair of cone seating
3. Adapter : Adapter for proving ring and strain dial gauge bracket.
4. Coning tools : **One pair of male/female coning tools for 38 mm dia samples**
5. Split Mould Size :**38 mm x 76 mm - 1 no.**
6. Proving ring : High sensitivity proving ring 250 kgf with Calibration chart
7. Dial gauge : 0.01 mm x 25 mm travel



Note:

1. **Coning tools and split mould for 50 mm, 75 mm and 100 mm dia available at extra cost.**
2. **NABL Calibration of Proving ring and dial gauge at extra cost.**

Corporate Office:

A-1301, BVR Ek, Opp. Hotel Inder Residency,
Near Gujarat College, Ellisbridge,
Ahmedabad-380 006.
Phone : (079) 6621 1234
Website : www.eieinstruments.com

Calibration Laboratory:

B-14, Zaveri Industrial Estate, Opp. Shyam Villa,
Singarva-Kathwada Road,
Kathwada, Ahmedabad-382 430.
Phone : (079) 6604 0660 • Fax : (079) 6604 0600
E-mail : info@eieinstruments.com

GST TIN No. : 24AABCE4018L1ZU
I.T. PAN No. : AABCE 4018L
IEC No. : 0813026598 Dt. 04/03/2014
CIN No. : U29199GJ2004PTC045078
TAN No. : AHME00572F