

# FORK MOUNTED RAM ATTACHMENT



Contact Fork mounted Ram attachment or booms are ideal for handling cylindrical objects with a hollow core, such as rolls, reels and carpets. The unit comes complete with a solid steel lifting tine, manufactured to a specific length to suit your roll length, roll diameter & material type. Our Fork mounted booms comes as standard with heavy duty machined box section for connecting to the truck forks.

All Contact booms come with a tapered nose, this allows the user to easily enter tight core's with the boom pole, without causing damage to the roll.

No real time installation required for this attachment. When fitting the boom to the truck, drive slowly forward until the Fork face contacts the attachment back plate. Raise forks slowly until attachment allowing itself to re-fit & repositioned. When specifying a boom for a reach truck, always check the under carriage clearance. The boom is mounted in inverted condition or at lower side of attachment to allow ground level loads to be lifted.

<b>Model no</b>	<b>Capacity @ 500 mm</b>	<b>Pole Diameter</b>	<b>Pole Length</b>	<b>Weight in Kg</b>
FMRA15_610	1500	115	610	135
FMRA15_915	1500	115	915	140
FMRA15_1220	1500	115	1220	145
FMRA15_1525	1500	115	1525	150
FMRA27_610	2700	150	610	145
FMRA27_915	2700	150	915	150
FMRA27_1220	2700	150	1220	155
FMRA27_1525	2700	150	1525	160