





Faster Heating with Orient Electric's Range of Water Heaters





Fans | Lighting | Appliances | Switches | Switchgear | Wires

### **Orient Electric Limited**

(a CKA Birla Group company) 240, Okhla Industrial Estate, Phase-III, New Delhi-110020

Orient Helpline No.: +91 9667121111 Email: customer.connect@orientelectric.com Website: www.orientelectric.com











# ORIENT ELECTRIC

# A BRAND THAT STRIVES TO BRING THE BEST OF INNOVATION FOR YOU.

For over 70 years, Orient has redefined comfort and innovation, becoming a trusted name in homes worldwide. With a commitment to blending design, technology, and performance, we craft solutions that enhance everyday living. At the heart of our journey is a dedication to our customers-bringing thoughtful innovations that prioritise comfort, efficiency, and sustainability.

With a continuous focus on product quality and service, we have earned the trust of consumers and expanded to over 1,35,000 retail outlets. Our service network continues to grow, with a presence in over 450 cities.

Moreover, with a footprint in more than 30 countries worldwide and across all states in India, Orient Electric Ltd. is one of the most trusted brands in the electrical lifestyle solutions industry. It has rightly earned the 'Superbrand' award on multiple occasions.









# WHY CHOOSE ORIENT ELECTRIC

### WATER HEATERS

Orient Electric Water Heaters are designed to deliver hot water in the shortest time, while keeping electricity consumption to a minimum. At Orient Electric, 'Safety First' isn't just a motto—it's a commitment. Our water heaters are built with advanced manufacturing processes and the highest quality standards to ensure 100% protection. With a wide range of 5-star rated models, Orient Electric combines technology, comfort, and efficiency to elevate everyday living.

### Technology that stands out:

- **Duron Heating Technology** resists corrosion and significantly extends to the life of the heating element even in the toughest hard water conditions.
- **IoT-enabled Technology** that gives you the liberty to operate your water heater from anywhere in the world.
- Whirlflow Technology delivers up to 20% more hot water output for enhanced efficiency and comfort.



Duron Heating Technology For corrosion resistance



Save On Energy
5-star BEE-rated models
cut electricity costs.



Durable Performance Shockproof body, glassline-coated element, and robust anode rod.



Style And Convenience Sleek design, LED indicators, and smart features.



20% More Hot Water Output with Whirlflow technology



Total Safety
5-level shield, precise
thermostat, and
multifunction valve.



Wide Selection Storage, instant, gas, and immersion water heaters.



Top Support
Free installation with
Glassline models.

# WATER HEATER **BUYING GUIDE**

### **WATER TYPE**

Hard water contains high levels of Calcium and Magnesium, causing scaling that reduces water heater efficiency. Choose heaters with HPE technology, Magnesium anode rods, glassline-coated tanks and heating elements to prevent corrosion.



### PRESSURE PUMP **COMPATIBILITY & SAFETY**

For high-rise buildings or pressure pump use, ensure your heater has an 8-bar pressure rating and a pressure release valve to prevent tank damage from over-pressured water.

TYPE	CAPACITY/FAMILY SIZE	APPLICATION			
Instant	3 Litres/1-2 members	Kitchen wash basin			
Water Heater	5.5 Litres/1-3 members	Kitchen wash basin			
Gas Water Heater	6 Litres/1-4 members	Ventilated kitchen & bathroom			
	6-10 Litres/2-3 members	Bathroom - bucket			
Storage	15-25 Litres/2-4 members	Bathroom - shower & bucket			
Water Heater	35-50 Litres/2-5 members	Bathroom - bathtub, shower & bucket			
	70-100 Litres/2-8 members	Bathroom - bathtub, shower & bucket			
Immersion Water Heater	1-1.5KW immersion/1 members	Ventilated & kitchen bathroom			



# STORAGE WATER HEATERS

Indulge in the ultimate bathing experience with our heaters. Designed for high-rise buildings, these models offer superior corrosion resistance, energy efficiency, and a range of stylish options.









### **AQUATOR IOT** STORAGE WATER HEATER

Aquator IoT allows you the convenience of operating it from anywhere, at any time with the Orient Smart application. The water heater saves both your time & electricity with its innovative Smart & Eco modes.

### **CUSTOMISE YOUR EXPERIENCE**

### **REAL-TIME STATUS**

Check the current working status of your water heater.

### **SMART MODE**

Fast heating with the highest default temperature for quick hot water.

### TRACK USAGE

Monitor daily, weekly, and monthly power consumption trends.



### MANUAL MODE

Customise and save temperature settings for different family needs.

### **ECO MODE**

Optimal temperature setting to save energy while keeping water warm.

### TIMER SETTING

Schedule automatic ON/OFF at desired temperatures for a better experience.

### **AQUATOR NEO** STORAGE WATER HEATER

Aquator Neo, with advanced Duron Technology provides superior corrosion resistance, even in hard water conditions. This ensures a significantly longer life of the heating element, reliable performance, and reduced maintenance-offering you lasting comfort, safety, and peace of mind.







Liberty to operate from anywhere with IoT-Enabled operation



Easy operation with Soft Touch Control



40% Longer tank lifespan with Ultra-Diamond Glassline Tank



Corrosion resistant with extended life 27% thicker Magnesium Anode Rod & Glassline coated incoloy heating



Temperature indication with Digital Display




Power & heating indication with colour changing Smart LED



20% More hot water output with Whirlflow technology





















Duron Heating Technology

Polymer Body

Shock-proof & Splash-Proof

20% more hot water output

with Whirlflow technology

with IPX4 High-strength



40% Longer tank lifespan with Ultra-Diamond Glassline Tank



Power & heating indication with colour changing Smart LED



Set temperature according to your need with customized temperature setting



Corrosion resistant with extended life 27% thicker Magnesium Anode Rod & Glassline coated incoloy heating





**UNMATCHED WARRANTY** 











### **AQUATOR NEO**



SWCN25VPG8K2-WG (25L) SWCN15VPG8K2-WG (15L) SWCN10VPG8K2-WG (10L)

### NEW

DURON Duron Heating Technology For corrosion resistance



Shock-proof & Splash-Proof with IPX4 High-strength Polymer Body



20% more hot water output with Whirlflow technology



Warranty: 7 year on Tank, 6 year on Heating Element, 2 year on Product



40% Longer tank lifespan with Ultra-Diamond Glassline Tank



Power & heating indication with colour changing Smart LED



Set temperature according to your need with customized temperature setting



Corrosion resistant with extended life 27% thicker Magnesium Anode Rod & Glassline coated incoloy heating









### **AQUATOR**



SWAT06VPG8K2-WS (6L\*) SWATIOVPG8K2-WS (10L\*) SWATI5VPG8K2-WS (15L) SWAT25VPG8K2-WS (25L)




20% more hot water output with Whirlflow technology



Corrosion resistant with extended life 27% thicker Magnesium Anode Rod & Glassline coated incoloy heating



Power & heating indication with colour changing Smart LED



Warranty: 7 year on Tank, 4\* year on Heating Element, 2 year on Product



40% Longer tank lifespan with Ultra-Diamond Glassline Tank











\*Features might slightly vary as per the capacity for 6L and 10L. Please refer to the spec table for more details.

### **AQUASLIM**



SWTS25HMG8K2-RH (25L) SWTS25HMG8K2-LH (25L) SWTS15HMG8K2-RH (15L) SWTS15HMG8K2-LH (15L)



Energy efficient compact design



Splash-Proof with pre-coated metal IPX4 rated body



20% more hot water output with Whirlflow technology



Warranty: 7 year on Tank, 3 year on Heating Element, 2 year on Product



40% Longer tank lifespan with Ultra-Diamond Glassline Tank



Corrosion resistant with extended life 27% thicker Magnesium Anode Rod & Glassline coated incoloy heating



Set temperature according to your need with customized temperature setting









### **CRYSTA**



SWCR15VPG8K2-SL (15L) SWCR25VPG8K2-SL (25L)




40% Longer tank lifespan with Ultra-Diamond Glassline



Shock-proof & Splash-Proof with IPX4 High-strength ABS Body


Power & heating indication



Warranty: 7 year on Tank, 4 year on Heating Element,

2 year on Product





20% more hot water output with Whirlflow technology

Corrosion resistant with extended life

27% thicker Magnesium Anode Rod &

Glassline coated incoloy heating

element















### **AQUANOVA NEO**



SWCT10VMG8K2-WB (10L) SWCT15VMG8K2-WB (15L) SWCT25VMG8K2-WB (25L)



20% more hot water output with Whirlflow technology



Splash Proof with pre-coated metal IPX4 rated body



Warranty: 7 year on Tank, 6 year on Heating Element, 2 year on Product



40% Longer tank lifespan with Ultra-Diamond Glassline Tank



Set temperature according to your need with customized temperature setting



Corrosion resistant with extended life 27% thicker Magnesium Anode Rod & Glassline coated incoloy heating element









### **AQUANAUT**



SWANIOVPG8K2-WG (10L) SWANI5VPG8K2-WG (15L) SWAN25VPG8K2-WG (25L)

40% Longer tank lifespan with Ultra-Diamond Glassline Tank

Rust-Resistant & Splash Proof

High-strength polymer body

Warranty: 7 year on Tank,

3 year on Heating Element,

2 year on Product



Temperature indication with dial display



20% more hot water output with Whirlflow technology



Corrosion resistant with extended life 27% thicker Magnesium Anode Rod & Glassline coated incoloy heating











### **MAVERICK**



SWMA06VMP8K2-GB(6L) | SWMA10VMP8K2-GB (10L) SWMA15VMP8K2-GB (15L) | SWMA25VMP8K2-GB (25L) SWBA35VMGM2 (35L) | SWBA50VMGM2 (50 L)



Longer Tank Lifespan with HPE technology



20% more hot water output with Whirlflow technology



Splash-proof with pre-coated metal IPX4 rated body



Warranty: 5 year on Tank, 2 year on Heating Element, 2 year on Product



10% Longer heat retention Thick PUF insulation

temperature setting

Set temperature according

to your need with customized



Corrosion resistant with extended life 27% thicker Magnesium Anode Rod & Glassline coated incoloy heating element











35L and 50L available in 3 star rating.

### **ECOSWIFT PRO**



SWEF10VMP8M2-WB (10L) SWEF15VMP8M2-WB (15L) SWEF25VMP8M2-WB (25L)



Longer Tank Lifespan with HPE technology



20% more hot water output with Whirlflow technology



Warranty: 5 year on Tank, 2 year on Heating Element, 2 year on Product



with pre-coated metal IPX4 rated body

Splash Proof



Corrosion resistant with extended life

10% Longer heat retention



27% thicker Magnesium Anode Rod & Glassline coated incoloy heating element









### **RAPIDUS**



IWRP55VPS6M3-WB (5.5L, 3 kW)



Power & heating indication with Neon Indicator

Pressure Release Valve & Anti-siphon hole

Enhanced safety



Longer tank lifespan with High-Grade Stainless-Steel Tank



Better load efficiency with moulded 3-Pin Plug



Warranty: 5 year on Tank, 2 year on Heating Element, 2 year on Product





### **PRIMUS**



IWPM03VPS8M3-WW (3L, 3kW) IWPM03VPS8M4-WW (3L, 4.5kW)







Power & heating indication with LED Indicator



Enhanced safety Pressure Release Valve & Anti-siphon hole



Longer tank lifespan with High-Grade Stainless-Steel Tank



Better load efficiency with moulded 3-Pin Plug



Warranty: 5 year on Tank, 2 year on Heating Element, 2 year on Product





# orient electric \*\*\* GAS WATER HEATERS Planning to save some money on your water heating electricity bills? Bring home Orient Electric's gas water heaters - a smart choice for reducing energy costs while ensuring a continuous supply of hot water. With their instant heating capabilities, these water heaters combine reliability with sleek design, integrating seamlessly into modern homes.

### **VENTO PRO 6L**



GWVP06VML8KN-WK

Faster heating 3-Row burner & Tin-plated Heavy Copper Heat Exchanger



Heat water as per the weather Summer-Winter Mode



Enhanced safety Flame failure device, Auto 20-min Off timer, Overheat & Over-pressure protection



Prompts to replace battery Through Low Battery Indicator



Shuts off ignition during improper usage through safety lock



Suitable for high-rise buildings Pressure compatibility



Assured quality ISI Certified Product



2-year on product

### **BAHUBALI PRO 6L**



GWBP06VML8KN-WG



Faster heating 3-Row burner & Tin-plated Heavy Copper Heat Exchanger



Heat water as per the weather Summer-Winter mode



Enhanced safety Flame failure device, Auto 20-min Off timer, Overheat & Over-pressure protection



Prompts to replace battery through low battery indicator



Shuts off ignition during improper usage through safety lock



Suitable for high-rise buildings Pressure compatibility



2-year on product

### **ARC PLUS**



IM10AP | IM15AP (1KW) (1.5kW)



100% Shock-proof body with IPX7 protection



Faster Heating with Nickel coated heavy Copper heating



Easy maneuvering handle with firm grip



Assured quality ISI Certified Product



Uniform heating with Spiral design heating element



Easy & safe usage with Bucket Clip



Better load efficiency with 3-Pin Moulded plug



Replacement warranty 2 year on product

### **HEAT PLUS**



IM10HP | IM15HP (1KW) (1.5kW)

### Uniform heating heating element



Power & heating indication

Easy maneuvering handle

with Neon Indicator

with firm grip

Assured quality

ISI Certified Product



Black nickel coated SS 304 heating element



Easy & safe usage with Bucket Clip



Better load efficiency with 3-Pin Moulded plug



Replacement warranty 2 year on product

# **HOT STAR**



IM10HS | IM15HS (1KW) (1.5kW)

Uniform heating with spiral design heating element



Power & heating indication with Neon Indicator



Easy maneuvering handle with firm grip



Assured quality ISI Certified Product



Faster Heatina Nickel coated heavy Copper heating



Easy & safe usage with Bucket Clip



Better load efficiency with 3-Pin Moulded plug



Replacement warranty 2 year on product

### **HEAT PRIME**



IM10HT | IM15HT (1KW) (1.5kW)



100% Shock-proof body with IPX7 protection



Black nickel coated SS 304 heating element



Easy maneuvering handle with firm grip



Assured quality ISI Certified Product



Uniform heating with spiral design heating element



Easy & safe usage with Bucket Clip



Better load efficiency with 3-Pin Moulded plug



Replacement warranty 2 year on product

# **STORAGE** WATER HEATERS





### **AQUATOR NEO**

AQUATOR IOT

Model No.         Agustion Neo         Agustion Neo         Agustion Neo         Agustion Neo         Agustion Neo         Caputin No.	Category		Storage (Glassline)	Storage (Glassline)	Storage (Glassline)	Storage (Glassline)	Storage (Glassline)	
Mountaing Pearly   Vertical	Model		Aquator Neo	Aquator Neo	Aquator Neo	Aquator IoT	Aquator IoT	
Copocity (1)         10         10         25         15         25           Restor began between two processing of the position of t	Model No.		SWCNI0VPG8K2-WG	SWCN15VPG8K2-WG	SWCN25VPG8K2-WG	SWATI5VPG8I2-WS	SWAT25VPG8I2-WS	
Miles   Mil	Mounting Position		Vertical	Vertical	Vertical	Vertical	Vertical	
Roted Input Power (NHV)   2   2   2   2   2   2   2   2   2	Capacity (L)		10	15	25 15		25	
Outer Body         High-strength Polymer         Mile with Closes line         Additional Closes         Mile with Closes line         Additional Closes         Additional C	BEE Star Rating		5	5	5	5	5	
Trans   Tra	Rated Input Pow	er (kW)	2	2	2	2	2	
Heating Element	Outer Body							
Device Control   Temperature   Temperature   Temperature   Control fixeb	Inner Tank Coati	ing	M.S with Glass line	M.S with Glass line	M.S with Glass line	M.S with Glass line	M.S with Glass line	
Function Display	Heating Element	t	Copper Tube with PTFE Coating	Copper Tube with PTFE Coating	Copper Tube with PTFE Coating			
Power & Heating Indicator         LED	Device Control		Temperature Control Knob	Temperature Control Knob	Temperature Control Knob			
Puf	Function Display	,	N.A.	N.A.	N.A.	Digital Display	Digital Display	
Trank Anti-Rust Device   Magnesium   Anode Rod   Magnesium   Magnesium   Anode Rod   Magnesium   Anode Rod   Magnesium   Anode Rod   Magnesium   Anode Rod   An	Power & Heating Indicator		LED	LED	LED	LED	LED	
Most Pressure Rating (Barr)         8         2         2         2         2         2			PUF	PUF	PUF	PUF	PUF	
Rotting (Bar)         9 </td <td colspan="2">Tank Anti-Rust Device</td> <td>Magnesium Anode Rod</td> <td>Magnesium Anode Rod</td> <td>Magnesium Anode Rod</td> <td>Magnesium Anode Rod</td> <td>Magnesium Anode Rod</td>	Tank Anti-Rust Device		Magnesium Anode Rod	Magnesium Anode Rod	Magnesium Anode Rod	Magnesium Anode Rod	Magnesium Anode Rod	
Secondary Overheat Thermal Cutout Th			8	8	8	8	8	
Protection   Protection   Pressure Release   Pre		at	Thermostat	Thermostat	Thermostat	Electronic Relay	Electronic Relay	
Protection)         Valve         Non-Return Valve         Non-Return Valve         Non-Return Valve         Non-Return Valve         Drainage Valve         Drainage Valve         Drainage Valve         IPX4         IPX4<		heat	Thermal Cutout	Thermal Cutout	Thermal Cutout	Thermal Cutout	Thermal Cutout	
Protection)         Valve         Non-Return Valve         Derainage Valve         Drainage Valve         Drainage Valve         Drainage Valve         Drainage Valve         Prainage Valve <t< td=""><td></td><td>ure</td><td></td><td></td><td></td><td></td><td></td></t<>		ure						
Protection)         Non-Return valve         Derainage Valve         Drainage Valve         Drainage Valve         Drainage Valve         Drainage Valve         Drainage Valve         Page Valve	MFV (Vacuum Protection)							
Ingress Protection   IPX4		kflow	Non-Return Valve	Non-Return Valve	Non-Return Valve	Non-Return Valve	Non-Return Valve	
Rating         IFA4         IFA			Drainage Valve	Drainage Valve	Drainage Valve	Drainage Valve	Drainage Valve	
Width   365   384   460   390   470		on	IPX4	IPX4	IPX4	IPX4	IPX4	
Dimension (nm)   Depth   350   385   395   385   400   470	Available Colour	rs	White-Silver	White-Silver	White-Silver	White-Silver	White-Silver	
(mm)	Width		365	384	460	390	470	
		Depth	350	385	395	385	400	
Product 2 2 2 2 2 2		Height	380	399	475	390	470	
		Product	2	2	2	2	2	
Warranty (year) Element 6 6 6 4 4		Element	6	6	6	6 4		
Tank 7 7 7 7 7		Tank	7	7	7	7	7	

# **STORAGE** WATER HEATERS





### AQUATOR

CRYSTA

Category		Storage (Glassline)	Storage (Glassline)	Storage (Glassline)	Storage (Glassline)	Storage (Glassline)	Storage (Glassline)
Model		Aquator	Aquator	Aquator	Aquator	Crysta	Crysta
Model No.		SWAT06VPG8K2-WS	SWATIOVPG8K2-WS	SWATI5VPG8K2-WS	SWAT25VPG8K2-WS	SWCRI5VPG8K2-SL	SWCR25VPG8K2-SL
Mounting Posit	ion	Vertical	Vertical	Vertical	Vertical	Vertical	Vertical
Capacity (L)		6	10	15	25	15	25
BEE Star Rating	1	5	5	5	5	5	5
Rated Input Power (kW)		2	2	2	2	2	2
Outer Body		High-strength Polymer	High-strength Polymer	High-strength Polymer	Pre-coated Designer Metal	High-strength ABS	High-strength ABS
Inner Tank		M.S. with Glassline	M.S. with Glassline	M.S. with Glassline	M.S. with Glassline	M.S. with Glassline	M.S. with Glassline
Heating Elemen	nt	Copper With Nickel Coating	Copper With Nickel Coating	Glassline Coated Incoloy	Glassline Coated Incoloy	Glassline Coated Incoloy	Glassline Coated Incoloy
Device Control		Temperature Control Knob	Temperature Control Knob	Temperature Control Knob	Temperature Control Knob	Temperature Control Knob	Temperature Control Knob
Function Displo	ıy	N.A.	N.A.	N.A.	N.A.	N.A.	N.A.
Power & Heatin	ng Indicator	LED	LED	LED	LED	LED	LED
Tank Heat Loss Insulation		PUF	PUF	PUF	PUF	PUF	PUF
Tank Anti-Rust Device		Magnesium Anode Rod	Magnesium Anode Rod	Magnesium Anode Rod	Magnesium Anode Rod	Magnesium Anode Rod	Magnesium Anode Rod
Max Pressure Rating (Bar)		8	8	8	8	8	8
Primary Overho Protection	eat	Thermostat	Thermostat	Thermostat	Thermostat	Thermostat	Thermostat
Secondary Ove Protection	erheat	Thermal Cutout	Thermal Cutout	Thermal Cutout	Thermal Cutout	Thermal Cutout	Thermal Cutout
MFV (Over Pres	sure	Pressure Release Valve	Pressure Release Valve	Pressure Release Valve	Pressure Release Valve	Pressure Release Valve	Pressure Release Valve
MFV (Vacuum Protection)		Vacuum Release Valve	Vacuum Release Valve	Vacuum Release Valve	Vacuum Release Vacuum Release Valve Valve		Vacuum Release Valve
MFV (Water Ba Protection)	ckflow	Non-Return Valve	Non-Return Valve	Non-Return Valve	Non-Return Valve Non-Return Valve		Non-Return Valve
MFV (Tank Maintenance)		Drainage Valve	Drainage Valve	Drainage Valve	Drainage Valve Drainage Valve		Drainage Valve
Ingress Protection Rating		IPX4	IPX4	IPX4	IPX4	IPX4	IPX4
Available Colours		White-Silver	White-Silver	White-Silver	White-Silver	White-Silver	White-Silver
	Width	325	365	390	470	390	470
Dimension (mm)	Depth	315	340	385	400	385	400
	Height	325	365	390	470	390	470
	Product	2	2	2	2	2	2
Warranty (year)	Element	3	3	4	4	4	4
	Tank	7	7	7	7	7	7

# **STORAGE** WATER HEATERS





### AQUANAUT

**AQUANOVA NEO** 

Category		Storage (Glassline)	Storage (Glassline)	Storage (Glassline)	Storage (Glassline)	Storage (Glassline)	Storage (Glassline)
Model		Aquanaut	Aquanaut	Aquanaut	Aquanova Neo	Aquanova Neo	Aquanova Neo
Model No.		SWANIOVPG8K2-WG	SWANI5VPG8K2-WG	SWAN25VPG8K2-WG	SWCTIOVMG8K2-WB	SWCT15VMG8K2-WB	SWCT25VMG8K2-WB
Mounting Position		Vertical	Vertical	Vertical	Vertical	Vertical	Vertical
Capacity (L)		10	15	25	10	15	25
BEE Star Rating		5	5	5	5	5	5
Rated Input Power (kW)		2	2	2	2	2	2
Outer Body Inner Tank		High-strength Polymer	High-strength Polymer	High-strength Polymer	Powder Coated Metal	Powder Coated Metal	Powder Coated Metal
		M.S. with Glassline	M.S. with Glassline	M.S. with Glassline	M.S. with Glassline	M.S. with Glassline	M.S. with Glassline
Heating Element		Copper With Nickel Coating	Copper With Nickel Coating	Copper With Nickel Coating	Glassline Coated Incoloy	Glassline Coated Incoloy	Glassline Coated Incoloy
Device Control		Temperature Control Knob	Temperature Control Knob	Temperature Control Knob	Temperature Control Knob	Temperature Control Knob	Temperature Control Knob
Function Display		Temperature Dial	Temperature Dial	Temperature Dial.	N.A.	N.A.	N.A.
Power & Heating Indicator  Tank Heat Loss		LED	LED	LED	LED	LED	LED
Insulation		PUF	PUF	PUF	PUF	PUF	PUF
Tank Anti-Rust Device		Magnesium Anode Rod	Magnesium Anode Rod	Magnesium Anode Rod	Magnesium Magnesium Anode Rod Anode Rod		Magnesium Anode Rod
Max Pressure Rating (Bar)		8	8	8	8 8		8
Primary Overho Protection	eat	Thermostat	Thermostat	Thermostat	Thermostat	Thermostat	Thermostat
Secondary Ove Protection	erheat	Thermal Cutout	Thermal Cutout	Thermal Cutout	Thermal Cutout	Thermal Cutout	Thermal Cutout
MFV (Over Pres Protection)	sure	Pressure Release Valve	Pressure Release Valve	Pressure Release Valve	Pressure Release Valve	Pressure Release Valve	Pressure Release Valve
MFV (Vacuum Protection)		Vacuum Release Valve	Vacuum Release Valve	Vacuum Release Valve	Vacuum Release Valve	Vacuum Release Valve	Vacuum Release Valve
MFV (Water Ba Protection)	ckflow	Non-Return Valve	Non-Return Valve	Non-Return Valve	Non-Return Valve	Non-Return Valve	Non-Return Valve
MFV (Tank Maintenance)		Drainage Valve	Drainage Valve	Drainage Valve	Drainage Valve	Drainage Valve	Drainage Valve
Ingress Protect Rating	ion	IPX2	IPX2	IPX2	IPX4	IPX4	IPX4
Available Colo	urs	White-Grey	White-Grey	White-Grey	White-Grey	White-Grey	White-Grey
	Width	340	340	360	337	337	358
Dimension (mm)	Depth	355	355	375	352	352	373
	Height	422	520	593	394	496	575
	Product	2	2	2	2	2	2
Warranty (year)	Element	3	3	3	6 6		6
	Tank	7	7	7	7	7	7
			ans and specifications are				

# **STORAGE** WATER HEATERS





### **AQUASLIM**

### **ECOSWIFT PRO**

Category		Storage (Glassline)	Storage (Glassline)	Storage (Polymer)	Storage (Polymer)	Storage (Polymer)	
Model		Aquaslim	Aquaslim	Ecoswift Pro	Ecoswift Pro	Ecoswift Pro	
Model No.		SWTS15HMG8K2-RH SWTS15HMG8K2-LH	SWTS25HMG8K2-RH SWTS25HMG8K2-LH	SWEF10VMP8M2-WB SWEF15VMP8M2-WB		SWEF25VMP8M2-WB	
Mounting Position		Horizontal	Horizontal	Vertical	Vertical Vertical		
Capacity (L)		15	25	10	15	25	
BEE Star Rating		3	3	5	5	5	
Rated Input Pow	ver (kW)	2	2	2	2	2	
Outer Body		Powder Coated Metal	Powder Coated Metal	Powder Coated Metal	Powder Coated Metal	Powder Coated Metal	
Inner Tank Coati	ing	M.S with Glass line	M.S with Glass line	M.S with HPE Technology	M.S with HPE Technology	M.S with HPE Technology	
Heating Element	t	Copper Tube with Nickel Coating	Copper Tube with Nickel Coating	Copper with Nickel Coating	Copper with Nickel Coating	Copper with Nickel Coating	
Device Control		Temperature Control Knob	Temperature Control Knob	N.A.	N.A.	N.A.	
Function Display	,	N.A.	N.A.	N.A.	N.A.	N.A.	
Power & Heating Indicator		LED	LED	LED	LED	LED	
Tank Heat Loss Insulation		PUF	PUF	PUF	PUF	PUF	
Tank Anti-Rust D	Device	Magnesium Anode Rod	Magnesium Anode Rod	Magnesium Anode Rod	Magnesium Anode Rod	Magnesium Anode Rod	
Max Pressure Rating (Bar)		8	8	8	8	8	
Primary Overhed Protection	at	Thermostat	Thermostat	Thermostat	Electronic Relay	Thermostat	
Secondary Overl Protection	heat	Thermal Cutout	Thermal Cutout	Thermal Cutout	Thermal Cutout	Thermal Cutout	
MFV (Over Press Protection)	sure	Pressure Release Valve	Pressure Release Valve	Pressure Release Valve	Pressure Release Valve	Pressure Release Valve	
MFV (Vacuum Protection)		Vacuum Release Valve	Vacuum Release Valve	Vacuum Release Valve	Vacuum Release Valve	Vacuum Release Valve	
MFV (Water Back Protection)	kflow	Non-Return Valve	Non-Return Valve	Non-Return Valve	Non-Return Valve	Non-Return Valve	
MFV (Tank Maintenance)		Drainage Valve	Drainage Valve	Drainage Valve	Drainage Valve	Drainage Valve	
Ingress Protection	on	IPX4	IPX4	IPX4	IPX4	IPX4	
Available Colours		White	White	White-Grey	White-Grey	White-Grey	
	Width	320	320	310	320	355	
Dimension (mm)	Depth	335	335	330	340	375	
	Height	550	860	470	475	510	
	Product	2	2	2	2	2	
Warranty (year)	Element	2	2	2	2	2	
	Tank	7	7	5	5	5	

# **STORAGE** WATER HEATERS



### MAVERICK

Category		Storage (Glassline)	Storage (Glassline)	Storage (Polymer)	Storage (Polymer)	Storage (Polymer)	Storage (Polymer)
Model		Maverick	Maverick	Maverick	Maverick Maverick		Maverick
Model No.		SWMA06VMP8K2-GB	SWMA10VMP8K2-GB	SWMA15VMP8K2-GB	SWMA25VMP8K2-GB	SWBA35VMGM2	SWBA50VMGM2
Mounting Positio	on	Vertical	Vertical	Vertical	Vertical	Vertical	Vertical
Capacity (L)		6	10	15	25	35	50
BEE Star Rating		5	5	5	5	3	3
Rated Input Power (kW)		2	2	2	2	2	2
Outer Body		Powder Coated Metal					
Inner Tank Coati	ing	M.S with HPE Technology					
Heating Element	t	Copper Tube with Nickel Coating					
Device Control		Temperature Control Knob					
Function Display		N.A.	N.A.	N.A.	N.A.	N.A.	N.A.
Power & Heating	g Indicator	LED	LED	LED	LED	LED	LED
Tank Heat Loss Insulation		PUF	PUF	PUF	PUF	PUF	PUF
Tank Anti-Rust Device		Magnesium Anode Rod					
Max Pressure Rating (Bar)		8	8	8	8	8	8
Primary Overhed Protection	at	Thermostat	Thermostat	Thermostat	Thermostat	Thermostat	Thermostat
Secondary Overl Protection	heat	Thermal Cutout					
MFV (Over Press Protection)	ure	Pressure Release Valve					
MFV (Vacuum Protection)		Vacuum Release Valve					
MFV (Water Back Protection)	kflow	Non-Return Valve					
MFV (Tank Maintenance)		Drainage Valve					
Ingress Protectio Rating	on	IPX2	IPX2	IPX2	IPX2	IPX2	IPX2
Available Colour	rs	Grey-Black	Grey-Black	Grey-Black	Grey-Black	Grey-Black	Grey-Black
	Width	360	400	400	375	420	420
Dimension (mm)	Depth	375	420	420	360	400	400
	Height	354	382	472	542	584	740
	Product	2	2	2	2	2	2
Warranty (year)	Element	2	2	2	2	2	2
	Tank	5	5	5	5	5	5

# **INSTANT** WATER HEATERS





**RAPIDUS** 

**PRIMUS** 

Category		Gas	Gas			
Model		Rapidus	Primus			
Model No.		IWRP55VPS6M3-WB	IWPM03VPS8M3-WW / IWPM03VPS8M4-WW			
Mounting Positio	n	Vertical	Vertical			
Capacity (L)		5.5	3			
Rated Input Pow	er (kW)	3	3/4.5			
Outer Body		High-Strength Polymer	High-Strength Polymer			
Inner Tank		Stainless Steel	Stainless Steel			
Heating Element		Heavy Copper	Heavy Copper			
Function Display		N.A.	NA.			
Power & Heating Indicator		Neon	LED			
3-Pin Moulded Plug		Yes	Yes			
Tank Heat Loss I	nsulation	Glasswool	Glasswool			
Max Pressure Ra	ting (Bar)	6.5	8			
Over Pressure Pr	otection	Pressure Release Valve	Pressure Release Valve			
Primary Overhed Protection	at	Thermostat	Thermostat			
Secondary Overl Protection	heat	Thermal Cutout	Thermal Cutout			
Ingress Protection	n	IPXI	IPXI			
Available Colour	s	White-Blue	White			
	Length	250	230			
Dimension (mm)	Width	255	210			
	Height	445	365			
	Product	2	2			
Warranty (year)	Element	2	2			
	Tank	5	5			

# GAS WATER HEATERS





### **VENTO PRO**

**BAHUBALI PRO** 

Category		Gas	Gas		
Model		Vento Pro	Bahubali Pro		
Model No.		GWVP06VML8KN-WK	GWBP06VML8KN-WG		
Mounting Position	on	Vertical	Vertical		
Hot Water Outpu Minute)	ut (Litre Per	6	6		
Outer Body		Powder Coated Metal	Powder Coated Metal		
Buner		Stainless Steel	Stainless Steel		
Heat Exchanger		Tin Plated Copper	Tin Plated Copper		
Solenoid Valve		Single	Single		
Function Display	,	N.A.	N.A.		
Gas Flow Contro	ı	Manual Knob	Manual Knob		
Temperature M	ode	Summer / Winter	Summer / Winter		
Power Indicator		Neon	Neon		
Primary Overhed Protection	at	Thermal Cutout	Thermal Cutout		
Overheat Protec	tion Timer	20 Minute Auto Off	20 Minute Auto Off		
Gas Leakage Pro	otection	Flame Failure Device	Flame Failure Device		
Accidental Igniti Protection	ion	Safety On/Off Switch	Safety On/Off Switch		
Scaling & Blocks Prevention	age	Inlet Mesh	Inlet Mesh		
Available Colou	rs	White	White		
	Length	290	290		
Dimension (mm)	Width	140	140		
	Height	490	490		
	Product	2	2		
Warranty year	Element	2	2		
	Tank	5	5		

# **IMMERSION** RODS









ARC PLUS

**HOT STAR** 

**HEAT PRIME** 

**HEAT PLUS** 

					o i o i Ait				
Category		Immersion	Immersion	Immersion	Immersion	Immersion	Immersion	Immersion	Immersion
Model		Arc Plus	Arc Plus	Hot Star	Hot Star	Heat Prime	Heat Prime	Heat Plus	Heat Plus
Model No.		IM10AP	IM15AP	IM10HS	IM15HS	IM10HT	IM15HT	IM10HP	ІМ15НР
Rated Input Po	wer (kW)	1	1.5	1	1.5	1	1.5	1	1.5
Outer Body		Shockproof PBT Polymer	Shockproof PBT Polymer	Bakelite	Bakelite	Shockproof PBT Polymer	Shockproof PBT Polymer	Bakelite	Bakelite
Heating Element		Heavy Copper with Nickel Coating	Heavy Copper with Nickel Coating	Heavy Copper with Nickel Coating	Heavy Copper with Nickel Coating	SS 304 with black Nickel Coating			
Power Indicator		N.A.	N.A.	Neon	Neon	N.A.	N.A.	Neon	Neon
Water Level Indicator		Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Handle & Bucke	et Clip	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Power Cord (m	etre)	1.6	1.6	1.6	1.6	1.6	1.6	1.6	1.6
Power Plug		6 Amp. 3-Pin ISI Certified	16 Amp. 3-Pin ISI Certified	6 Amp. 3-Pin ISI Certified	16 Amp. 3-Pin ISI Certified	6 Amp. 3-Pin ISI Certified	16 Amp. 3-Pin ISI Certified	6 Amp. 3-Pin ISI Certified	16 Amp. 3-Pin ISI Certified
Available Colours		White-Blue	White-Blue	Black	Black	Black-White	Black-White	Black	Black
	Width	74	74	75	75	70	70	77	77
Dimension (mm)	Depth	67	67	65	65	72	72	65	65
	Height	360	360	360	360	355	355	335	335
Replacement Warranty (Product) Year		2	2	2	2	2	2	2	2

# **NOTES NOTES**