

A Great Fit for New or Existing Desktop Applications!

Value based thermal transfer printing

CITIZEN CL-S321/331
LABEL

Applications

- Retail
- Healthcare
- Pharmacy
- E-Seller
- SME / SMB



Compact Size and Efficient Design

The compact and efficient design helps to reduce desktop space usage and makes the CL-S321 a great fit for all thermal transfer applications.

Simple and Intuitive

Easy to load ribbon, accessible label path and single button control enable clear and trouble-free operation.



Cost-Effective Compatibility

The CL-S321 offers EPL2 compatibility, so you can just plug and print with existing applications. Convenient to use and economically priced, the CL-S321 is a great choice for value-based thermal transfer printing.



3 interfaces as default

With full speed USB 2.0, RS232C serial, 10/100 Ethernet interfaces standard the CL-S321 is flexible and ready to fit into your applications both old and new!



Specifications

| Models | CL-S321 | CL-S331 |
|-------------------------------|--|--------------------------------|
| Technology | Thermal Transfer/Direct Thermal | |
| Resolution | 203 dpi (8 dots per mm) | 300dpi (12 dots per mm) |
| Print Speed (maximum) | 4 inches per second (102 mm/s) | 3 inches per second (76.2mm/s) |
| Print Width (maximum) | 4.25 inches (108 mm) | 4.16 inches (105.7mm) |
| Media Width (min to max) | 1 inch to 4.64 inches (25.4 mm to 118 mm) | |
| Media Thickness (min to max) | 0.003 to 0.008 inches (0.06 to 0.2 mm) | |
| Media Sensor | Fixed label gap and black mark | |
| Media Length (min to max) | 1 inch to 68 inches (25.4 mm to 1727 mm) | |
| Roll Size (max), Core size | 5 inches (127 mm) diameter, 1 / 1.5 inches (25,4 mm / 38,1 mm) core | |
| Interface | USB 2.0, RS-232 and 10/100 Ethernet | |
| Ribbon Size | 1.57 inches (40mm) maximum diameter, 110 metre length, 0.5 inch (12.7mm) cores | |
| Ribbon Winding & Type | Ink side out. Wax, wax/resin or resin type | |
| Case | Hi-Open™ | |
| Mechanism | Self-contained | |
| Panel | One LED, Control key: FEED | |
| Flash (Non-Volatile Memory) | 8MB Flash, 16MB SDRAM | |
| Windows® drivers and software | Supporting XP®, 2003, 2008, Vista™, 7, 8 | |
| Size (W x D x H) and Weight | 224 mm x 254 mm x 170 mm), 2.5 Kg | |
| Printer, Head Warranty | 1 year for Printer; 30 Kms/6 months on head | |

Designs, specifications and availability are subject to change without notice. Errors and omissions excluded.

CITIZEN CL-S321/331

LABEL

Features & Benefits

- EPL2 programming language compatible
- Hi-Open™ housing for easy media loading
- Self-contained mechanism for durable operation
- Compact design
- Single button control panel
- Auto switching power supply, 100-240V, 50-60Hz
- Fixed label sensor
- Standard tear-bar for perforated tags
- USB 2.0, RS-232 serial and 10/100 Ethernet interfaces standard
- Media roll holder

Dealer stamp

Barscan Systems & Ribbons Pvt Ltd.
311, Apollo Chambers,
Mogra Village Road, Andheri (E),
Mumbai - 400 069. India
PH.: - 022-40388100 / 22
Email - barcode@barscansys.com
Website - www.barscansys.com

CITIZEN SYSTEMS JAPAN CO.,LTD.