


## 2/2 DUAL FLOW SOLENOID VALVE FOR LPG DISPENSING

TYPE	PRESSURE

TYPE	PRESSURE

TYPE	PRESSURE
24110	0.5 - 25 bar



### FEATURES

- Bubble tight shut off
- Mounts in any position
- Vibration resistance up to 9g
- Suitable for high speed cycling
- Speed up to 600 cycles/ min
- Life >10 million cycles

### WETTED PARTS

Body	SS 316	Plunger, Insert	SS 430
Internals	SS 316	Spring	SS 302
Guide Assembly	SS 304	Seat, Seals	Viton
Shadow-Ring	Copper	Fastener	SS 304

### SPECIFICATION

Valve Type	2/2 Internal Pilot Diaphragm Operated Dual Flow Solenoid Valve
Body Material	<b>CF8, CF8M (SS CAST)</b>
Orifice	20/2.2
Port Connection	3/4" BSP (F)
Media	LPG
Pressure	0.5 - 25 bar
Seal	Hytrell
Solenoid Voltage, Current	220 V AC
Enclosure	Explosion Proof Ex d
Application	LPG DISPENSING
Model	-

### PORT CONNECTION

FUNCTION	INLET	OUTLET
NC	2	1

Contact Rotex for any other ambient, fluid temperature, media and application.



Can be used for Water, Oil or dispensing of other fluids

ÜT



### OPTION

Body Material	Aluminium Cast
Orifice	12/ 25/ 40/ 50
Connection	-
Media	-
Seal	Viton
Voltage	Any
Current	Any
Enclosure	Weather Proof
Solenoid Size	14
Extended Application	Dispensing of Oil, Water, Fuel in Precise Quantity Dispensing of Air, Gases

### AMBIENT TEMPERATURE

-10 °C to 70 °C

### FLUID TEMPERATURE

-10 °C to 70 °C

### DIMENSIONS

All Dimensions are in mm

