



CRETESTONE
CRETE

CRETOPROOF DI PRIME

(Universal Primer For Waterproofing Coating)

Description

CRETOPROOF DI PRIME is a deep impregnating primer designed by blending special grade of polymers with synthetic binders. Its deep impregnating action and low viscosity helps it to attain better bonding with highly porous cementitious substrates.

Uses

CRETOPROOF DI PRIME is best suitable when used as a primer coat after surface preparations for all types of waterproof coatings. It can also be used as a dust proofer and floor sealer for dust proofing purposes.

Advantages

CRETOPROOF DI PRIME provides the following beneficial properties :

- Helps in sealing all dust and loose particles when used as a primer.
- Can be used as a dust proofer / sealer.
- Can act as a good primer / bond coat for all type of waterproof coatings.
- Has very good bonding with all cementitious substrate.
- Enhances coverage of overcoats.
- Economical and easy to use.

Coverage

CRETOPROOF DI PRIME will give a coverage of 6 -7 sqmt. / Litre / coat

Instructions for Use Surface Preparation

Concrete, mortar and masonry surface must be clean, free from grease, oil and loosely adhering particles. All surface must be as true and flat as possible. Efficient surface preparation is essential to achieve high adhesive quality of the product.

Application Method

Apply CRETOPROOF DI PRIME over the prepared surface using a brush, squeeze or broom. One coat is normally sufficient. Highly porous substrate may require two coat application. After the coat of CRETOPROOF DI PRIME the surface is ready for further top coats.

Packing

CRETOPROOF DI PRIME is available in 1, 5, 10, 20 , 50 & 200 ltr drum

CRETESTONE PRIVATE LIMITED



www.thecrestone.com



info@thecrestone.com



+91 8655093814/15

213, HariOm Plaza, Beside Omkareshwar Temple Opp. National Park Borivali East, Mumbai, Maharashtra 400066



CRETESTONE

Technical Data:

Form	Liquid
Type	Special polymers blended with Synthetic Fibers
Sp. Gravity	1.03 ± 0.02
Shelf Life	One year when unopened
Color	White, Will turn transparent on drying.
Drying time [At 28°C]	2-3 hours

Storage

Store under cover, out of direct sunlight and protect from extremes of temperature. Failure to comply with the recommended storage conditions may result in premature deterioration of the product or packaging.

Note

Field service, where provided, does not constitute supervisory responsibility. For additional information contact your local CRETESTONE representative. CRETESTONE reserves the right to have the true cause of any difficulty determined by accepted test methods.

Disclaimer

Whilst any information contained herein is true, accurate and represents our best knowledge and experience, no warranty is given or implied with any recommendations made by us, our representatives or distributors, as the conditions of use and the competence of any labour involved in the application are beyond our control

CRETESTONE PRIVATE LIMITED



www.thecrestone.com



info@thecrestone.com



+91 8655093814/15

213, HariOm Plaza, Beside Omkareshwar Temple Opp. National Park Borivali East, Mumbai, Maharashtra 400066