



CRETESTONE
SOLUTIONS
CRETE

CRETOPROOF TANK COAT

[Heat Insulation Coating For PVC Tanks]

Description

CRETOPROOF TANK COAT is an innovative coating combining strength, light weight protection and integral insulation ideally designed for Thermal insulation of all sorts of PVC tanks. It is a seamless, monolithic membrane impervious to adverse weathering and extreme temperature fluctuations.

Key Features

- 10-18 Degree variation in surface temperature of tank, during peak summer.
- Keeps water temperature close to ambient.
- All year-round protection: In addition to reducing conductive heat transfer micro spheres reflect away radiant energy or heat from the sun during the summer months and in winter they prevent radiant heat from leaving the building.
- Ease of application -By brush

Advantages

*Durability	Long life cycle
*Aesthetics	Modern with unlimited hues
*Safety or slip resistance	Excellent adhesion
*Cost	Competitive
*Preparation Requirements	Minimal
*Special skills or tools required	None

Technical data

Color	: White
Solar Reflectance Index [SRI]	: < 102
Chemical Base	: Special polymeric dispersion
Cracking	: None
Solid Contents	: 55% ±2
Dry Film Thickness	: 200-250 Microns per coat
Tensile Strength	: 1.54 Mpa
Resistance to alkali	: No sign of cracking, blistering or flaking
Density	: 1.17 [± 5%]

CRETSTONE PRIVATE LIMITED



www.thcretestone.com



info@thcretestone.com



+91 8655093814/15

213, HariOm Plaza, Beside Omkareshwar Temple Opp. National Park Borivali East, Mumbai, Maharashtra 400066



CRETESTONE
SOLUTIONS
CRETE

Some Important Facts

CRETOPROOF TANK COAT is available in white shade, but it could be tinted in different colors as far as white can be.

Application Method

- Clean the substrate and make it free from any dirt or loose particles. Scrub the cleaned surface mildly, using sand paper, to create a rough surface for better adhesion.
- 10-15% dilution with water is recommended to make the material brush able.
- Apply CRETOPROOF TANK COAT in 2 coats application over the cleaned surface with an interval of 3-4 hours between each coat.

Packing

CRETOPROOF TANK COAT is available in 1 kg pack.

Coverage

1 Kg CRETOPROOF TANK COAT is sufficient for coating of 500 ltr capacity PVC Tank in 2 coats.

Storage

Store under cover, out of direct sunlight and protect from extremes of temperature. Failure to comply with the recommended storage conditions may result in premature deterioration of the product or packaging.

Disclaimer

Whilst any information contained herein is true, accurate and represents our best knowledge and experience, no warranty is given or implied with any recommendations made by us, our representatives or distributors, as the conditions of use and the competence of any labour involved in the application are beyond our control.

CRETESTONE PRIVATE LIMITED



www.thecrestone.com



info@thecrestone.com



+91 8655093814/15

213, HariOm Plaza, Beside Omkareshwar Temple Opp. National Park Borivali East, Mumbai, Maharashtra 400066