



WDE-501

Features: -

- 3 in 1 – Dehumidifier, Air-Purifier and Dryer
- Concise appearance design.
- Water full warning signal function; shut-off automatically when the water tank full.
- Continuous drainage option available.
- Automatic humidistat Control.
- Fashionable and elegant appearance; Super low noise.
- Portable easy to carry handle; Easily move on wheels.
- Auto restart function; Auto frost Control.
- Air purifying filter.
- LCD display indicate humidity.
- No screw in the appearance.
- Pad key design.
- Timer on/off 24 hours.
- Color: White.

Technical Specification: -

- | | |
|--|---|
| • Model No.: - | WDE-501 |
| • Moisture removal 30°C, 80%R.H.: - | 50L/Day |
| • Power supply V/Hz: - | 220~240V/50Hz |
| • Rated Power consumption 30°C, 80%R.H.: - | 750W |
| • Maintain level: - | 30% R.H.- 80% R.H. |
| • Ambient Temperature for operation: - | 5-32°C |
| • Approx. Cover Area*: - | 5000-5500 cu.ft |
| • Water tank capacity: - | 7 Litres |
| • Noise level: - | 52 dB(A) |
| • Refrigerant: - | R290 |
| • Net Weight: - | 17.9 kgs |
| • Body dimensions (H x W x D): - | 600 x 388 x 282 mm / 23.62 x 15.27 x 11.10 inch |



WDE-602

Features: -

- 3 in 1 – Dehumidifier, Air-Purifier and Dryer
- Concise appearance design.
- Water full warning signal function; shut-off automatically when the water tank full.
- Continuous drainage option available.
- Automatic humidistat Control.
- With Drain Pump.
- Fashionable and elegant appearance; Super low noise.
- Portable easy to carry handle; Easily move on wheels.
- Auto restart function; Auto frost Control.
- Air purifying filter.
- LCD display indicate humidity.
- No screw in the appearance.
- Pad key design.
- Timer on/off 24 hours.
- Color: White.

Technical Specification: -

- | | |
|--|---|
| • Model No.: - | WDE-602 |
| • Moisture removal 30°C, 80%R.H.: - | 60L/Day |
| • Power supply V/Hz: - | 220~240V/50Hz |
| • Rated Power consumption 30°C, 80%R.H.: - | 650W |
| • Maintain level: - | 30% R.H.- 80% R.H. |
| • Current 30°C, 80%R.H.: - | 2.6A |
| • Air flow: - | 360 m3/h |
| • Ambient Temperature for operation: - | 5-32°C |
| • Approx. Cover Area*: - | 6000-6500 cu.ft |
| • Water tank capacity: - | 7 Litres |
| • Noise level: - | 52 dB(A) |
| • Refrigerant: - | R410 |
| • Net Weight: - | 19 kgs |
| • Body dimensions (H x W x D): - | 615 x 378 x 266 mm / 24.21 x 14.88 x 10.47 inch |



WDE-100

Commercial Dehumidifier

Features:

- Rotary compressor
- Standard colour sheet metal casing,
- Automatic defrost
- Humidity setting
- Sensor fault indicator function
- Washable filter
- Continuous drainage with external hose.
- Automatic humidistat Control.
- Portable easy to carry handle
- Easily move on wheels.

Technical Specification: -

• Model No.:-	WDE-100
• Moisture removal 30°C, 80%R.H.:-	100 L/Day
• Power supply V/Hz:-	220~240V/50Hz
• Rated Power consumption 30°C, 80%R.H.:-	1400W
• Control Type:-	Electric
• Maintain level:-	30% R.H.- 80% R.H.
• Current 30°C, 80%R.H.:-	5 A
• Air flow/Air Circulation:-	700m ³ /hr
• Ambient Temperature for operation:-	5-32°C
• Approx. Cover Area*:-	45~230m ² (height=2.6m)
• Noise level:-	54 dB(A)
• Refrigerant:-	R290
• Net Weight:-	41 kgs
• Body dimensions (H x W x D):-	872 x 540x 388 mm / 34.22 x 21.25 x 15.27 inch



WDE-110P

Commercial Dehumidifier

Features:

- Rotary compressor
- Standard colour sheet metal casing,
- Automatic defrost
- Universal wheels
- Humidity setting
- Sensor fault indicator function
- Three-minute automatic delay protection of the compressor
- Washable filter
- With Drain Pump
- Option for Continuous drainage with external hose.
- Automatic humidistat Control.
- Portable easy to carry handle; Easily move on wheels.

Technical Specification: -

• Model No.:-	WDE-110P
• Moisture removal 30°C, 80%R.H.:-	110L/Day
• Power supply V/Hz:-	220~240V/50Hz
• Rated Power consumption 30°C, 80%R.H.:-	1450W
• Control Type:-	Electric
• Maintain level:-	30% R.H.- 80% R.H.
• Current 30°C, 80%R.H.:-	6.6A
• Air flow/Air Circulation:-	950m ³ /hr
• Ambient Temperature for operation:-	5-38°C
• Approx. Cover Area*:-	100~130m ² (height=2.6m)
• Noise level:-	60 dB(A)
• Refrigerant:-	R410
• Net Weight:-	50 kgs
• Body dimensions (H x W x D):-	1010 x 480 x 410 mm / 39.76 x 18.90 x 16.14 inch



WDE-110S

Commercial Dehumidifier

Features:

- Rotary compressor
- Stainless steel Shell
- Automatic defrost
- Universal wheels
- Humidity setting
- Sensor fault indicator function
- Three-minute automatic delay protection of the compressor
- Washable filter
- With Water Tank & Drain Pump.
- Option for Continuous drainage with external hose.
- Automatic humidistat Control.
- Portable easy to carry handle; Easily move on wheels.

Technical Specification: -

- | | |
|--|--|
| • Model No.: - | WDE-110S |
| • Moisture removal 30°C, 80%R.H.: - | 110L/Day |
| • Power supply V/Hz: - | 220~240V/50Hz |
| • Rated Power consumption 30°C, 80%R.H.: - | 1450W |
| • Control Type:- | Electric |
| • Maintain level: - | 30% R.H.- 80% R.H. |
| • Current 30°C, 80%R.H.: - | 6.6A |
| • Air flow/Air Circulation: - | 950m ³ /hr |
| • Ambient Temperature for operation: - | 5-38°C |
| • Approx. Cover Area*: - | 100~130m ² (height=2.6m) |
| • Noise level: - | 60 dB(A) |
| • Refrigerant: - | R410 |
| • Net Weight: - | 50 kgs |
| • Body dimensions (H x W x D): - | 1010 x 480 x 410 mm / 39.76 x 18.90 x 16.14 inch |



White-Westinghouse®

Dehumidifier

A Trusted American Brand Since 1917.



WDE-121

Features: -

- 3 in 1 –Dehumidifier, Air-Purifier and Dryer.
- Humidity Setting : Continuous -40%-50%-60%
- Visible Water level
- Anti-dust filter.
- Humidity Sensor.
- Auto Defrost, Auto delay restart function,
- Full Water Tank Warning Signal / Auto Stop function.
- Energy saving rotary compressor.
- Extremely Silent.
- Continuous Drainage option available.
- Easier Mobility with Convenient Wheels.
- Recyclable materials for Environmental Conservation.

Technical Specification: -

- | | |
|--|--|
| • Model No.: - | WDE-121 |
| • Moisture removal 30°C, 80%R.H.: - | 12L/Day |
| • Power supply V/Hz: - | 220~240V/50Hz |
| • Rated Power consumption 30°C, 80%R.H.: - | 195W |
| • Maintain level: - | 30% R.H.- 80% R.H. |
| • Current 30°C, 80%R.H: - | 0.8A |
| • Ambient Temperature for operation: - | 5-32°C |
| • Application Area: - | 1200 cu.ft. |
| • Water tank capacity: - | 2.4 Litres |
| • Refrigerant: - | R134a |
| • Net Weight: - | 9 kgs |
| • Body dimensions (H x W x D): - | 468 x 303 x 193 mm / 18.43 x 11.93 x 7.60 inch |



WDE-168S

Commercial Dehumidifier

Features:

- Standard colour sheet metal casing, Anti corrosion evaporator and condenser.
- Dual drainage System with 6 ltrs tank and pump and external hose
- Automatic defrost
- Universal wheels
- Humidity setting
- Sensor fault indicator function
- Three-minute automatic delay protection of the compressor
- Washable filter
- Continuous drainage option available.
- Automatic humidistat Control.
- Portable easy to carry handle; Easily move on wheels.

Technical Specification: -

- | | |
|---|--|
| • Model No.:- | WDE-168P |
| • Moisture removal 30°C, 80%R.H.:- | 168L/Day |
| • Power supply V/Hz:- | 220~240V/50Hz |
| • Rated Power consumption 30°C, 80%R.H.:- | 2820W |
| • Control Type:- | Electric |
| • Maintain level:- | 30% R.H.- 80% R.H. |
| • Current 30°C, 80%R.H.:- | 12A |
| • Air flow/Air Circulation:- | 2000m3/hr |
| • Ambient Temperature for operation:- | 5-38°C |
| • Approx. Cover Area*:- | 200-240m ² (room height =2.6m) |
| • Water tank capacity:- | 6 Litres |
| • Noise level:- | 60 dB(A) |
| • Refrigerant:- | R410 |
| • Net Weight:- | 108 kgs |
| • Body dimensions (H x W x D):- | 1600 x 410 x 600 mm / 62.99 x 16.14 x 23.62 inch |



White-Westinghouse®

Dehumidifier

A Trusted American Brand Since 1917.



WDE-207

Features: -

- 3 in 1 –Dehumidifier, Air-Purifier and Dryer.
- Timer 24 hr count-down, on/off.
- LCD Display indicate temperature and humidity.
- Adjustable humidistat.
- Hygrometer
- Anti-dust filter (Washable)
- Humidity Sensor.
- Auto Defrost, Auto restart function.
- Full Water Tank Warning Signal / Auto Stop function.
- Energy saving rotary compressor.
- Extremely Silent.
- Continuous Drainage option available.
- Easier Mobility with Convenient Wheels.
- Recyclable materials for Environmental Conservation.
- Color : White.
- D-type Plug

Technical Specification: -

- | | |
|--|--|
| • Model No.: - | WDE-207 |
| • Moisture removal 30°C, 80%R.H.: - | 20L/Day |
| • Power supply V/Hz: - | 220~240V/50Hz |
| • Rated Power consumption 30°C, 80%R.H.: - | 420W |
| • Maintain level: - | 30% R.H.- 80% R.H. |
| • Ambient Temperature for operation: - | 5-32°C |
| • Application Area: - | 2000 cu.ft. |
| • Water tank capacity: - | 4 Litres |
| • Refrigerant: - | R290 |
| • Net Weight/ Gross Weight: - | 12.9/14 kgs |
| • Body dimensions (H x W x D): - | 575 x 360 x 240 mm / 22.64 x 14.17 x 9.45 inch |
| • D-type Plug | |



White-Westinghouse®

Dehumidifier

A Trusted American Brand Since 1917.



WDE-303

Features: -

- 3 in 1 –Dehumidifier, Air-Purifier and Dryer.
- Timer 12 hr count-down, on/off.
- LCD Display indicate temperature and humidity.
- Adjustable humidistat.
- Hygrometer/Thermometer.
- Anti-dust filter (Washable)
- Humidity Sensor.
- Auto Defrost, Auto restart function.
- Full Water Tank Warning Signal / Auto Stop function.
- Energy saving rotary compressor.
- Extremely Silent.
- Continuous Drainage option available.
- Easier Mobility with Convenient Wheels.
- Recyclable materials for Environmental Conservation.
- Color : White.
- D-type Plug

Technical Specification: -

- | | |
|--|---|
| • Model No.: - | WDE-303 |
| • Moisture removal 30°C, 80%R.H.: - | 30L/Day |
| • Power supply V/Hz: - | 220~240V/50Hz |
| • Rated Power consumption 30°C, 80%R.H.: - | 565W |
| • Maintain level: - | 30% R.H.- 80% R.H. |
| • Ambient Temperature for operation: - | 5-32°C |
| • Application Area: - | 3000 cu.ft. |
| • Water tank capacity: - | 5 Litres |
| • Refrigerant: - | R290 |
| • Net Weight: - | 16.5 kgs |
| • Body dimensions (H x W x D): - | 612 x 390 x 274 mm / 24.09 x 15.35 x 10.78 inch |
| • D-type Plug | |



WDE-603P

Commercial Dehumidifier

Features:

- Rotary compressor
- Standard colour sheet metal casing,
- Automatic defrost
- Universal wheels
- Humidity setting
- Sensor fault indicator function
- Three-minute automatic delay protection of the compressor
- Washable filter
- With Drain Pump.
- Continuous drainage option available.
- Automatic humidistat Control.
- Portable easy to carry handle; Easily move on wheels.

Technical Specification: -

- | | |
|--|---|
| • Model No.: - | WDE-603P |
| • Moisture removal 30°C, 80%R.H.: - | 60L/Day |
| • Power supply V/Hz: - | 220~240V/50Hz |
| • Rated Power consumption 30°C, 80%R.H.: - | 820W |
| • Control Type:- | Electric |
| • Maintain level: - | 30% R.H.- 80% R.H. |
| • Current 30°C, 80%R.H.: - | 3.5A |
| • Air flow/Air Circulation: - | 550m ³ /hr |
| • Ambient Temperature for operation: - | 5-38°C |
| • Approx. Cover Area*: - | 50~120m ² (height=2.6m) |
| • Noise level: - | 60 dB(A) |
| • Refrigerant: - | R410 |
| • Net Weight: - | 35 kgs |
| • Body dimensions (H x W x D): - | 680 x 372 x 394 mm / 26.77 x 14.65 x 15.51 inch |



WDE-603T

Commercial Dehumidifier

Features:

- Rotary compressor
- Standard colour sheet metal casing,
- Automatic defrost
- Universal wheels
- Humidity setting
- Sensor fault indicator function
- Three-minute automatic delay protection of the compressor
- Washable filter
- With 7 ltrs. Tank.
- Continuous drainage option available.
- Automatic humidistat Control.
- Portable easy to carry handle; Easily move on wheels.

Technical Specification: -

• Model No.:-	WDE-603T
• Moisture removal 30°C, 80%R.H.:-	60L/Day
• Power supply V/Hz:-	220~240V/50Hz
• Rated Power consumption 30°C, 80%R.H.:-	820W
• Control Type:-	Electric
• Maintain level:-	30% R.H.- 80% R.H.
• Current 30°C, 80%R.H.:-	3.5A
• Air flow/Air Circulation:-	550m3/hr
• Ambient Temperature for operation:-	5-38°C
• Water tank capacity:-	7 Litres
• Approx. Cover Area*:-	50~120m ² (height=2.6m)
• Noise level:-	60 dB(A)
• Refrigerant:-	R410
• Net Weight:-	35 kgs
• Body dimensions (H x W x D):-	680 x 372 x 394 mm / 26.77 x 14.65 x 15.51 inch