

TILE..
Buddy™

Jahan Haathi ka zor,
wahan ho
Tile buddy
ka bharosa.



TILE.. Buddy™

Tiles Buddy is a trusted name in the tile adhesive industry, offering high-performance solutions designed for strength, durability, and long-lasting bonding. Our tile adhesives are formulated using advanced technology to ensure excellent adhesion, easy application, and reliable results for both residential and commercial projects. Whether for walls or floors, interior or exterior spaces, Tiles Buddy products deliver superior grip, resistance to moisture, and consistent quality. With a strong focus on innovation and customer satisfaction, Tiles Buddy stands as a dependable partner for builders, contractors, and homeowners seeking premium tile fixing solutions.



TBD-111

GRIP PRO

TILE ADHESIVE



PRODUCT DETAILS

Interior Wall & Floor Tile Adhesive

COVERAGE

Approximately 4.5 to 5m²/20kg @3mm thickness when using a thin trowel

APPLICATION AREAS

Use For Ceramic Floor Tiles & Wall Tiles On Floor & Wall, Use For Vitrified Tiles And Porcelain On Floor

AVAILABLE IN

Packing 20kg
Grey Color

TECHNICAL INFORMATION

Properties	Results	Properties	Results
Appearance	Free Flowing Powder	Open Time	35 min
Color	White & Grey	Adjustability	25 min
Prolife	3 Hours	Trafficable time, Hrs	24

METHOD OF APPLICATION



STEP 1

The Surface Should Be Sound, Clean, And Free From Dirt, Oil Or Grease.



STEP 2

Add 5 To 6 Liters Of Clean Water To Tiles Pro Adhesive & Mix Thoroughly Until A Slum Free Mortar Is Obtained.



STEP 3

Tiles must be pressed firmly in to the adhesive, there should be no air voids beneath the tiles.



STEP 4

It Will Take 24 Hrs To Set The Tiles Grouting Should Preferably Be Carried Out At Least 24 Hours The Completion Of Tiling.



STEP 5

It Has A Pot Life Of About 3 Hours And Operating Time Of 15-20 Minutes At 24-27°C.



STEP 6

Use Clean Clothes Before Grouting Sets.

TBD-555

FLEXLITE

TILE ADHESIVE



PRODUCT DETAILS

Interior Of Wall & Vitrified Tiles Adhesive, Tile-on-tile, Window Farming. Application Areas Use For Applying Ceramic Tiles On Wall Vitrified Tiles On Wall Up To 600x1200 Mm & Floor. Porcelain Tiles, Window Farming Tiles On Tiles On Floor.

COVERAGE

Approximately 4.5 to 5m²/20kg @3mm thickness when using a thin trowel

AVAILABLE IN

Packing 20kg
Grey & White Color

TECHNICAL INFORMATION

Properties	Results	Properties	Results
Appearance	Free Flowing Powder	Open Time	35 min
Color	White & Grey	Adjustability	25 min
Prolife	3 Hours	Trafficable time, Hrs	24

METHOD OF APPLICATION



STEP 1

The Surface Should Be Sound, Clean, And Free From Dirt, Oil Or Grease.



STEP 2

Add 5 To 6 Liters Of Clean Water To Tiles Pro Adhesive & Mix Thoroughly Until A Slum Free Mortar Is Obtained.



STEP 3

Tiles must be pressed firmly in to the adhesive, there should be no air voids beneath the tiles.



STEP 4

It Will Take 24 Hrs To Set The Tiles Grouting Should Preferably Be Carried Out At Least 24 Hours The Completion Of Tiling.



STEP 5

It Has A Pot Life Of About 3 Hours And Operating Time Of 15-20 Minutes At 24+-2°C.



STEP 6

Use Clean Clothes Before Grouting Sets.

TBD-777

MAX GUARD

TILE ADHESIVE



Water Resistant



uv resistance



Chemical Resistance



PRODUCT DETAILS

Interior for wall & vitrified tiles adhesive, Tiles-on-tile, window framing. Application Areas use for applying ceramic tiles on Wall vitrified tiles on wall up to 800 x1600mm/1200x1800mm & floor. Porcelain tiles, window Framing tiles on tiles on floor

COVERAGE

Approximately 4.5 to 5m²/20kg @3mm thickness when using a thin trowel

AVAILABLE IN

Packing 20kg
Grey & White Color

TECHNICAL INFORMATION

Properties	Results	Properties	Results
Apperance	Free Flowing Powder	Open Time	35 min
Color	White & Grey	Adjustability	25 min
Prolife	3 Hours	Trafficable time, Hrs	24

METHOD OF APPLICATION



STEP 1

The Surface Should Be Sound, Clean, And Free From Dirt, Oil Or Grease.



STEP 2

Add 5 To 6 Liters Of Clean Water To Tiles Pro Adhesive & Mix Thoroughly Until A Slum Free Mortar Is Obtained.



STEP 3

Tiles must be pressed firmly in to the adhesive, there should be no air voids beneath the tiles.



STEP 4

It Will Take 24 Hrs To Set The Tiles Grouting Should Preferably Be Carried Out At Least 24 Hours The Completion Of Tiling.



STEP 5

It Has A Pot Life Of About 3 Hours And Ope-rating Time Of 15-20 Minutes At 24+-2'c.



STEP 6

Use Clean Clothes Before Grouting Sets.

TBD-444

ULTRASET

TILE ADHESIVE



Water Resistant



UV resistance



Chemical Resistance



PRODUCT DETAILS

Use for low and high water absorption surfaces use for applying of big size vitrified & porcelain tiles internally and externally. use for applying of low water absorption tiles such as single fired tiles, natural stone marbles etc.

COVERAGE

Approximately 4.5 to 5m²/20kg @3mm thickness when using a thin trowel

AVAILABLE IN

Packing 20kg
Grey & White Color

TECHNICAL INFORMATION

Properties	Results	Properties	Results
Appearance	Free Flowing Powder	Open Time	35 min
Color	White & Grey	Adjustability	25 min
Prolife	3 Hours	Trafficable time, Hrs	24

METHOD OF APPLICATION



STEP 1

The Surface Should Be Sound, Clean, And Free From Dirt, Oil Or Grease.



STEP 2

Add 5 To 6 Liters Of Clean Water To Tiles Pro Adhesive & Mix Thoroughly Until A Slum Free Mortar Is Obtained.



STEP 3

Tiles must be pressed firmly in to the adhesive, there should be no air voids beneath the tiles.



STEP 4

It Will Take 24 Hrs To Set The Tiles Grouting Should Preferably Be Carried Out At Least 24 Hours The Completion Of Tiling.



STEP 5

It Has A Pot Life Of About 3 Hours And Operating Time Of 15-20 Minutes At 24+-2°C.



STEP 6

Use Clean Clothes Before Grouting Sets.

2PART & 3PART



PRODUCT DETAILS

Epoxy Grout is a stain-resistant epoxy grout for floors and walls. It is colorfast, water and chemical-resistant and made of Epoxy Resin Technology making it ideal for ceramic tiles, vitrified tiles, marble, and stone, particularly in stain prone areas like kitchens and bathrooms (both residential and commercial installations). This non-shrinking, fast curing grout is efflorescence-free and provides high-strength, mildew-resistant joints. It is steam cleanable and suitable for use in green buildings. Available in 1kg and 5kg packs.

AVAILABLE IN

Residences, Kitchens, Bathrooms, Swimming pools, Fountains, Hospitals, Restaurants, Showrooms, Industrial areas & high traffic areas.

PACK SIZE

Componets	1 Kg Pack	5 Kg Pack
Resin	200 gm.	1 kg
Hardener	100 gm.	500 gm.
Epoxy Filler Powder	700 gm.	3.5 kg

AVAILABLE COLORS



BLOCK JOINTING &



READY MIX PLASTER



BLOCK JOINTING & READY MIX PLASTER



High Adhesion Of
Fly Ash Block

PRODUCT DETAILS

Used of fly ash block
adhesion

COVERAGE

Depends upon the soze of
block & good craft man ship

AVAILABLE IN
Packing 40kg
Grey Color

TECHNICAL INFORMATION

Properties	Results	Properties	Results
Apperance	Free Flowing Powder	Open Time	35 min
Color	White & Grey	Adjustability	25 min
Prolife	3 Hours	Trafficable time, Hrs	24

METHOD OF APPLICATION



Always clean the surface
before application to remove
any loose particles.



Ensure surface is well
saturated before
application.



Ensure surface is well
saturated before
application.



Use 2.5 parts of Block
Jointing to 1 part water
(measured by volume and
mix to a smooth, workable,
stiff paste.)



Clean the surface from loose particles,
wet the surface before application of
the OVENS ready mix plaster.



Mix 1 part of water to 3 parts of
OVENS ready mix plaster



Do not add any cement or
aggregate to the mortar



Always add powder to
water.



Allow the mix to stand for
2-8 min for te paste to
mature.



For better binding make the
grooves on concrete
surfaces like RCC Pillars & Beams



The mixture should be applied
within 1 hours



Recommended curing time is
2-3 days as per weather
conditions.



Do not add water to the
already mix slurry to extend
the pot life.



Put well mixed block
jointing on the block with
help of trowel, spread
mortar uniformly on the
unit for a min 10mm
bed thickness.



Firmly place the block
with slight shear to
ensure good
transfer & bonding.



Block jointing to be
applied on block and
on corners for good
bonding for the joints.

TILES GROUT



PRODUCT DETAILS

Tile Grout is a high quality fine, polymer modified, water-resistant, cement based powder grout designed for grouting glaze wall tiles, mosaics, vitrified & fully vitrified tiles, floor tiles, industrial floor tiles, etc. (Note: where chemical resistance is hygienic and sterile, it is important use Epoxy Grout)

APPLICATION AREA

Wall, Floors, Indoors & Outdoors
Dry Areas, Work Tops

AVAILABLE IN

Packing 1kg

TECHNICAL INFORMATION

Properties	Results	Properties	Results
Pot life @ 30c, minutes	60	Initial Set & Rt, Hours	2
Open Time, Minutes 30	30	Final Set #RT, Hours	8
Adjustability, minutes	15-20	Shrinkage, %	<0.1

AVAILABLE COLORS



White



Ivory



Light Grey



Wooden



Black



Terra Cotta



Jesalmer



Dark Grey



C. brown



Blue

GROUT ADMIX



PRODUCT DETAILS

Admix is specially designed latex admix to be used with sanded & Unsanded Grout.

COVERAGE

Varies a per application

APPLICATION AREA

Wall, Floors, Indoors & Outdoors
Dry Areas, Work Tops

AVAILABLE IN

Packing 100 ml

TILESCLEANER



Fast Acting Wall & Floor Tiles Cleaner

APPLICATION AREA

Wall, Floors, Interiors, Exteriors,
Day & Wet Areas Showers,
Swimming Pool

NOTE

Do Not Use On Surfaces That Are Not To Acid Such As Marble/terrazo. Do Not Use Your Bare Hand, Use Hand Gloves While Using Of Tiles Care. Highly Reactive To Skin.

AVAILABLE IN

Packing 1 Ltr.



TILE..
Buddy™

TILE BUDDY

Address :

📍 M/s Tile Buddy.
B/h Kachhi Metal, Jetpar Road, At. Bela,
Ta. Morbi Bela.

Mobile No.

☎ +91 77788 49127

Mail

✉ info@filesadhesives.com

Website

🌐 www.filesadhesives.com