

BANTHIA INDUSTRIAL CORPORATION

Material Safety Data Sheet

Section 1: Identification of substance and of the Company:

Product Name: Washed / Hydrous China Clay (Kaolin) Powder
Trade Name:
Application: Paint, Paper, Rubber, Ceramics, Plastic & , Ink, Pigments

Mfg. Company:

BANTHIA INDUSTRIAL COOPERATION
76-D. Harish Chaterjee Street, Bhawanipur,
KOLKATA – 700025
Mob: 9830022663, 9904262151

Section 2: Composition / Data on components Chemical characterization:

PRODUCT	CAS.NR	EINECS NR.	HSN CODE
KAOLIN CLAY/WASHED CHINACLAY POWDER ADVANCED SERIES	-	-	250700 29

Section 3: Hazards Identification:

Hydrous / Washed China clay – China clay powder is a non flammable white powder material. It does not cause burns, skin or eye irritation. A single exposure will not result in serious adverse health effects. Inhalation of high concentrations may cause upper respiratory irritation. Acute exposure is not anticipated. Avoid dust creation. Do not inhale dust from this product. Do not use compressed air or dry sweeping to remove dust from the work area. Use an appropriately equipped vacuum or wet clean-up methods to remove dust.

Potential Health Effects:

A) Inhalation:

a) Kaolin is: Respirable kaolin can cause kaolin is, a fibrosis of the lung. Kaolin is less fibrogenic than crystalline silica. Repeated prolonged inhalation of respirable dust in excess of appropriate exposure limits has caused pneumoconiosis, a lung disease. Not all individuals with pneumoconiosis will exhibit symptoms (signs) of the disease . However pneumoconiosis can be progressive and symptoms can appear at any time, even after years after the exposure has ceased. Symptoms of pneumoconiosis may include but are not limited to the following : shortness of breath, difficulty breathing with or without exertion; coughing; diminished work capacity ; diminished chest expansion ; reduction of lung volume.

B) Eye Contact: Direct contact may cause abrasion of the cornea

C) Skin Contact: Prolonged exposure may cause dryness of the skin and irritation.

D) Ingestion: Accidental ingestion may cause blockage & irritation of the digestive tract

BANTHIA INDUSTRIAL CORPORATION

Section 4: First Aid measures:

Inhalation : If exposure is in excess of prescribed limits, remove the person immediately to fresh air, give artificial respiration as needed , seek medical attention as needed.

Eye contact: Accidental direct contact with eyes may cause, discomfort due to mechanical irritation. Wash the affected eyes copiously with clean water. Skin contact: Wash the affected skin copiously with soap & water

If ingested: Have subject drink water. Do not induce vomiting. Obtain medical assistance immediately.

Section 5: Fire Fighting Measures:

Physical Hazard: Hydrous/washed China clay Powder – non combustible.

Flammable limits in air:	Not flammable
Flashpoint:	Not flammable
Auto ignition temperature:	Not flammable
Extinguishing Agents:	Not required
Unusual Fire and explosion Hazards:	None known
Sensitivity to static discharge:	Not applicable

Section 6: Accidental Release Measures:

Spills: Use dustless methods (vacuum) and place into closable container for disposal, or flush small quantities with water with extreme care. Clean up personnel should use appropriate NIOSH / MSHA approved respirators if exposures are expected above the limits. Water should be used with care as it creates a slipping hazard when mixed with this product. Calcined clay is generally non-toxic to aquatic systems but may high turbidity in storm water. Do not dry sweep.

Section 7: Handling and Storage:

Precautions during Handling and use: Do not breathe dust. Use adequate ventilation and dust collection. Keep airborne dust concentrations below PEL. Do not rely on your sight to determine if dust is in the air.

Section 8: Exposure Controls / Personal Protection:

Local Exhaust: Use sufficient local exhaust to reduce the level of respirable calcined chin clay to below the PEL.

PRODUCT	OSHA PEL15 mg / cubic metre (Total)	ACGIH TLV	NIOSH REL 10 mg / Cubic Metre
KAOLIN CLAY /WASHED CHINA CLAY POWDER ADVANCED SERIES	5 mg/cubic metre (respirable)	-	5 mg/cubic metre (respirable)

BANTHIA INDUSTRIAL CORPORATION

Engineering Controls: Respirable dust levels should be monitored regularly, dust levels in excess of appropriate exposure limits should be reduced by all feasible engineering controls, including (but not limited to) wet suppression, ventilation, process enclosure and enclosed employee work stations. Respiratory protection: For respirable dust levels that exceed the limits appropriate approved filter respirators must be worn.

Section 9: Physical and Chemical Properties:

Appearance: White / Cream white powder

Boiling Point: N / A

Vapour Pressure (mm Hg): None

Vapour Density: None

Solubility in Water: Insoluble in water

Odour: None

Specific Gravity: 2.2 –2.60

Melting Point: > 1700 degree C

Evaporation Rate: None

Section 10: Stability and reactivity:

Stability: Hydrous/washed china clay powder- It is stable under normal storage conditions

Incompatibility: None known

Hazardous Decomposition or by products: None known

Hazardous Polymerization: Will not occur.

Section 11: Toxicological Information:

Calcined / Hydrous/Washed China clay / kaolin – It is not listed as carcinogen by the International Agency for Research on Cancer (IARC), the National Toxicological Program (NTP) or the Occupational Safety and Health Administration (OSHA). The American Conference of Governmental Industrial Hygienists (ACGIH) lists kaolin as Not classifiable as a Human Carcinogen.

Section 12: Ecological Information:

No adverse ecological effects are expected. May affect turbidity of water if discharged in large quantities to lakes or streams.

Section 13: Disposal Considerations: GENERAL:

The packaging and material may be land filled; however, material should be covered to minimize generation of airborne dust.

Section 14: Transport Information:

Hydrous / Washed china clay / kaolin – Washed China clay powder is not a hazardous material for purposes of transportation.

BANTHIA INDUSTRIAL CORPORATION

Section 15: Regulatory Information: TSCA No:

Hydrous/Washed china clay – Washed China Clay does not appear in TSCA inventory requirement list. OSHA: This document based on OSHA communication standard However, please consult applicable local laws

Section 16: Other Information:

Hazardous Material Information system (HMIS)

Health	0*	potential chronic effects
Flammability	0	non flammable
Reactivity	0	non reactive
Protective Equipment	E **	

•prolonged breathing exceeding permissible limits would affect lung function

** Use NIOSH approved dust mask for dusty conditions.

Add:- 76-D. Harish Chaterjee Street, Bhawanipur KOLKATA – 700025
Mob: 9830022663, 9904262151