



Taha International | Taha Fabricators | Taha Services

Scaffolding & Accessories, Formwork, Shuttering Material

Office: Plot No.6, Trimurti Marg, Behind Avery India Co.,
Opp. Raheja Gardens, Thane (W) - 400604. T: +91-73043 14060.

Works: Plot No.3, Radha Krishna Indl. Complex, Pimpas Gaon,
Next to Bhoomi World, Bhiwandi.

tahafabs@gmail.com | taha.int@hotmail.com | taha.services@hotmail.com



Taha International | Taha Fabricators | Taha Services

Scaffolding & Accessories, Formwork, Shuttering Material



INDEX

Introduction of Company.....	01
Props.....	02
Telescopic Spans.....	02
Cuplock Scaffolding System.....	02
Tubular Scaffolding Or H Frame.....	03
Walking Plank.....	03
Adjustable Stirrup Head (Jacks).....	03
H Frame Wheel.....	04
Shikanja.....	04
Concrete Vibrator.....	04
Fix Span.....	05
Wall Form (Falka).....	05
Centering.....	05
Couplers.....	05
Scaffolding Accessories.....	06
Farma.....	06
Wedge Clip.....	07
Mixing Tray.....	07
Cube Moulds.....	07
Harbana.....	07
Structural Material.....	08
Stack Parking.....	10
Cantilever Parking.....	11
Pit Parking.....	12



Scaffoldings Division established in 1990, Taha Fabricators (India) has over the years grown as one of the largest manufacturers & exporters of scaffolding products and scaffolding solutions in India. Synonymous with high quality scaffolding fitting, we have, along with our safe, reliable & durable products, developed a reputation for unmatched excellence among our customers in the building & construction industry.

Our scaffolding fittings, scaffolding products and scaffolding accessories are known for their strength & reliability.

Safe & dependable, our scaffolding fittings have a proven track record of excellence in the construction industry.

We bring to bear an unique combination of knowledge, innovation and experience in every aspect of our scaffolding products & services.


PROPS



Model No.	Outer Tube (mm)	Inner Tube (mm)	Height of use (Mix)	
			Min.	Max.
BS -1	1.5	1.5	1.7	2.75
BS -2	2	2	2.3	3.75
BS -3	2	2.5	2.7	4.25
BS -4	2	3	3.2	4.7

TELESCOPIC SPANS

Type	Size (Mtrs) Min.	Size (Mtrs) Max.
ISOS	1.80	3.00
ISOM	2.40	3.60
IMOM	2.40	4.20
ILOM	3.00	4.80
ILOL	3.00	5.40



Spans are manufactured for a longer life keeping in view their rigid use in the construction

CUPLOCK SCAFFOLDING SYSTEM



Sizes available

vertical	from .5 mtr	1 mtr	1.5 mtr
Ledger	from 0.5 mtr	1 mtr	1.5 mtr
vertical	2 mtr	2.5 mtr	3 mtr
Ledger	2 mtr	2.5 mtr	

We also make custom sizes

TUBULAR SCAFFOLDING OR H FRAME

Scaffolding is available in 3 sizes

1. 2 mtr X 1 mtr
2. 2.4 mtr X 1.2 mtr
3. 1 mtr X 2 mtr with staircase
4. Cross bracing
5. Base plate

Note:

Special sizes can also be supplied



WALKING PLANK 8' X 1' & 10' X 1'

(Made from Square Pipes)



ADJUSTABLE STIRRUP HEAD (JACKS)

Useful to support to height adjustment between two joints. Made in 32mm bright bar with locking nut (C.I) and U head 100 X 1000 with 5 mm thick plate.

Specification:

Size	032 mm X 350 mm
Threading	4 TPI

Ø (mm)	Height (mm)	Type
32	350/450	Solid
36	400/500	Solid
38	650/750	Hollow



H FRAME WHEEL



SHIKANJA

Made from 32 X 6 mm
M.S. Flat
Available in 2, 2.5,
3 & 4 feet



CONCRETE VIBRATOR



Type	Needle (Poker) Type
Vibrating Needle	Two standard sizes of 40mm and 60mm diameter are manufactured. They are interchangeable and can be fitted to the same flexible shaft. 25 diameter needles are also manufactured
Flexible Shaft	One standard length of 6 metre is available . It has an outer hose of reinforced rubber and a steel inner core of high strength
Prime mover	MK 12 1.67 H.P 4 stroke petrol/kerosene engine or single phase, three phase 2 HP Electric motor
Weight App	25 Kg.

FIX SPAN



Length: 9 feet (Standard)
Rest sizes can be made
as per order.

WALL FORM (FALKA)

Height:
2400 mm (Standard)
Width:
from 100mm to 600 mm



CENTERING



Size: 3 X 2 feet
3 X 1.5 feet
3 X 1 feet

COUPLERS



Forge Couplers



Swivel Coupler Light/Heavy
(Sheet Metal)



Fixed Coupler Light/Heavy
(Sheet Metal)

SCAFFOLDING ACCESSORIES



Prop Nut Heavy



Single Clamp



Prop Barel



Tie Rod



Anchor Nut



Wing Nut



Joint Pin



Water Stopper



Mivan Pin



Mivan Wedges

FARMA

Sizes (in Litres)	Dimensions (in mm)	Sizes (in Litres)	Dimensions (in mm)
20 L	300 X 333 X 200	35 L	302 X 302 X 801
25 L	300 X 333 X 250	40 L	300 X 333 X 400
30 L	300 X 333 X 300	45 L	300 X 333 X 450



WEDGE CLIP

Useful for interlocking the wall from plates



MIXING TRAY

Size available: 6 ft. X 4ft.
5 ft. X 4 ft.



CUBE MOULDS

Prepared from cast Iron.
Moulds fixed with base plates.
Size: 150 mm X 150 mm X 150 mm



Prepared from cast Iron and M.S.
Size: 7.06 cm X 7.06 cm X 7.06 cm

HARBANA



Harbana (Single tyre)
2.5 CFT.

Trolley	Fabricated from 16, 14 or 19 gauge
Bucket	M.S. sheet and Angles fitted with single scooter tyre with axle and bearing
Frame	Prepared from angle or pipe
Stand	Two stands and handles are provided for moving smoothly and for resting

STRUCTURAL MATERIAL



Square Pipe

Size: 20mm X 20mm to 100mm X 100mm

Thickness: 2mm to 6mm

Rectangular Pipe

Size: 50mm X 25mm

Thickness: 2mm to 6mm

Size: 60mm X 40mm

Thickness: 2mm to 6mm

Size: 75mm X 25mm

Thickness: 2mm to 6mm

Size: 100mm X 50mm

Thickness: 2mm to 6mm



C- Channel

Size: 75mm X 40mm

100mm X 100mm

I- Beam

Size: 100mm X 50mm

125mm X 65mm

150mm X 75mm

Round Pipe

Size: 48 (Outer Diameter)

Thickness: 2.5mm to 4mm

STACK PARKING



Platform Length - 4.2-4.5 mtr
 Platform Width - 2.2-2.5 mtr
 Height - 2 mtr
 Lifting Capacity - 2 tons
 Electrical Requirement - 3 phase 220 V

CANTILEVER PARKING



Platform Length - 4.2 mtr
 Platform Width - 2.2-2.5 mtr
 Height - 2 mtr
 Lifting Capacity - 2 tons
 Electrical Requirement - 3 phase 220 V



NOTES:

This image shows a single sheet of white paper with horizontal blue ruling lines. The lines are evenly spaced and run across the width of the page. There are no margins, text, or other markings on the paper.