




WIREWOUND ELECTRONICS PVT.LTD.

(As an ISO 9001:2015 & IATF 16949:2016)

Rod Inductors (5X15)



SPECIAL FEATURES

- Compact in size.
- Low core loss.
- High operation frequency.
- High current capacity.
- Low core saturation.
- Vertical mount.
- Operating temperature: -30 to +120 °C
- Shrink tubing protected winding

Sr No	SIZE	Part No	Inductance 1KHz @ 0.3V	Tolerance	Current Rating
1	5X15 ROD	ROD -6012	2uH	±20%	15A
1	5X15 ROD	ROD -6013	3uH	±20%	10A
2	5X15 ROD	ROD -6014	5uH	±20%	10A
3	5X15 ROD	ROD -6015	5uH	±20%	8A
4	5X15 ROD	ROD -6016	6uH	±20%	5A
5	5X15 ROD	ROD -6017	10uH	±20%	4A
• Suppression of switch mode power supplies/UPS. • Discrete high-performance interference suppression filter. • Automotive industry. • Buck converter, LCD, Notebook computer, Handheld notebook. • Digital products, Network communication etc.					

Wirewound -Web- www.wirewound.in/Email Id:- wirewound@gmail.com/Mob-9822261409/7722077394