SHASHWAT "SADA KE LIYE"

Velvet Touch Gypsum Plaster — Official Technical Data Brochure

Product Overview

Shashwat Velvet Touch Gypsum Plaster is a premium, ultra-superfine surface preparation and wall finishing compound engineered specifically for high-end interior spaces. Manufactured from exceptionally pure native gypsum ores (98% purity matrix), it yields a brilliant white, exceptionally smooth aesthetic finish that minimizes structural shrinkage risks while removing traditional intermediate painting steps.

Performance & Functional Advantages

- **Ultra-Smooth Velvet Finish:** Eliminates surface roughness completely, providing a flawless foundation ready for direct premium topcoat application.
- **No Curing Required:** Structural design completely removes the requirement for time-intensive water curing or chemical hydration steps.
- **Zero Shrinkage Cracking:** Controlled volumetric setting properties effectively defend against hairline cracks and macro-shrinkage tension zones.
- **High Coverage Optimization:** Optimized density distribution delivers an efficient structural coverage window of 1.2 sq. ft./kg.
- **Enhanced Insulation Matrix:** Natural core crystalline alignment introduces passive thermal resistance and localized acoustic damping properties.

Technical Product Matrix

Technical Parameter	Verified Specification Value
Brand Variant	Shashwat Velvet Touch
Pack Metric Base	25 kg Industrial Bag
Material System Base	High Whiteness Beta-Hemihydrate Gypsum
Purity Analysis Metric	≥ 98.00%
Setting Profile (Time)	15 Minutes Standard
Calculated Material Yield	1.2 sq. ft. per kg
Intended Surface Matrix	Ceilings, Interior Dry-brick Walls, Monolithic Concrete

Disclaimer: This document is synthesized strictly from public product declarations and technical catalogs issued by Shashwat Wallcare. Site mixing guidelines, ambient environmental factors, and substrate parameters can modify target operational values slightly. Field checks are recommended before bulk installations.