





MT-90005V

Specification:

Power: 1000 Watts

Useful power: 750 Watts

Maximum cutting height: 200 mmMaximum cutting width: 310 mm

Cutting speed: 380/880 m/min

Approximate table dimensions: 500 x 500 mm

• Blade dimensions: 3,500mm X 25 mm (3,500 mm x 25 mm is not be blade length but dimensions);

• Possible widths of the blade(s): 10, 16, 20, 25, 32 mm;

• It is include a protractor for angle cuts, a millimetric guide and have motor protection;

Dimensions and Weight

• Approximate dimensions (L x W x H): 750 x 530 x 900 mm

Approximate weight: 320 kg



STANDARD ACCESSORIES
Instruction Manual
Main Unit









CIRCULAR SAW SLIDING TABLE

MT-8751



- Drive motor power: 3.5 KwSupply voltage: 400 Volts
- Mains frequency: 50 Hz,
- Extraction hole diameter less than 100 mm
- Saw blade rotation speed: 5,800 rpm
- Saw blade diameter: 315 mm
- Saw blade hole diameter 30 mm
- Cutting length 2,000 mm
- Cutting width 3.2 mm
- Dimensions of the work area with extensions: 1,000 mm x 760 mm
- Saw blade inclination angles: 100 mm at 90° and 80 mm at 45°



STANDARD ACCESSORIES
Instruction Manual
Main Unit











CARPENTER'S BENCH

MT-874C



Specification:


- Load capacity: 750Kg
- Working space (without press): 1910 x 615 mm
- Length. front/rear jaw: 700 mm / 460 mm
- Front/rear jaw width: 100 mm / 140 mm
- Board thickness (material to be worked with): 80 mm
- Working height 870 mm
- Approx weight: 150 kg

It is equipped with:

- Two short round hooks
- Two long round hooks
- Drawer











UNIVERSAL TUPIA

MT-368P



Specification:

- Universal combination for woodworking, consisting of five functional groups (saw, molder, surface/ thickness planer and carver)
- Operation with 3 independent engines;
- Circular saw unit;
- Cutting length: 730 mm;
- Saw blade inclination angle: 90° 45°
- Maximum cutting height at 90°: 75 mm;
- Maximum cutting height at 45°: 60 mm;
- Circular saw blade diameter (main): 254x30x3 mm / Z = 36
- Saw blade rotation speed: 4750 rpm;
- Dimensions: Length approx. 2200 mm; Width/depth approx. 1400 mm; Height approx. 1300mm
- Approximate weight: 345kg;
- Input power: 2.2 kW;
- Input power / Planer: 1.5 kW;
- Input power / Molder: 1.4 kW
- Supply voltage: 400 V;
- Network frequency: 50 Hz;
- Saw blade protection (Extraction port diameter): 30 mm
- Feeding speed: 8 m/min;









- Width of the feeding table: 250 mm;
- Feeding table length: 1090 mm
- Max cutter diameter: 140 mm;
- Milling spindle: 30 mm diameter arbor (3 mm cutting depth)
- Height adjustment: 100 mm;
- Speed(s): 4500/6500/8500 rpm
- Planing knife shaft: three blades (250x30x3 mm) Carriage and sliding table:
- Length of the sliding table: 1300 mm;
- Width of the sliding table: 210 mm;
- Sliding table height: 93 mm;
- Table length: 980/600 mm
- Table width: 470/248 mm;
- Table height: 860 mm;
- Minimum working height: 5 mm
- Max working height: 195 mm;

STANDARD ACCESSORIES













TURNING MACHINE WOOD

MT-748TM



Specification:

- Maximum distance between centers (min): 1120 mm
- Maximum diameter over the busbar: 300 mm
- Head: Fixed
- Flat plate: Ø 80 mm
- Tool support support: 150 mm
- Power: 550 W
- Power: 220V/50Hz single phase
- Approx. weight: 40 kg


Accessories (1 unit of each):

- Extraction rod
- 8 mm allen wrench
- 6 mm allen wrench
- 3 mm allen wrench
- Steering wheel crank
- Drag tip
- Rotating tip













AIR COMPRESSOR

MT-958A







Specification:

Reservoir capacity: 200 L

Electrical supply: 220 Volts / 50

Power: 5.5 kW

Mains frequency: 50 Hz

With belt drive

Working pressure: min. 10 bar

With belt drive

Approximate suction capacity: 850 l/min

Filling capacity approx.: 680 l/min

Number of cylinders 2

Number of compressor stages 2

Dimensions and accessories

Approximate length: 1200 mm Width/depth approx.: 700 mm

• Approx. height: 1150 mm Approx. weight: 150 kg Connection: plug/22 mm

10 meter compressed air hose, made of polyurethane and with 8 x 12 eyelet coupling

STANDARD ACCESSORIES Instruction Manual Main Unit









WORKSHOP CABINET

MT-6898



Specification:


- Made from high quality sheet steel with reinforcing profiles on the doors.
- Doors in a firmly welded structure, completely sealed with foam, with lockable latches with 3- point safety cylinders
- 4 (four) galvanized shelves (4 levels), with a minimum loading capacity of 80 kg
- Approximate dimensions (HxWxD): 2000x1000x490mm



Main Unit











PORTABLE ELECTRIC SANDER

MT-25PS




Specification:

- 2 speeds supported,
- Dimensions approx. of tape: 100x560 mm -
- Dimensions approx. useful base: 100x140mm.
- Belt speed 200 330 m/min
- Sanding surface width 75 mm











VIBRATORY GRINDER ORBITAL PORTABLE WITH ELECTRONIC ADJUSTMENT

MT-26PO



Voltage: 220v

Power 180W

Sanding surface: 115 x 107 mmNo-load oscillations: 24,000 rpm

No-load speed: 12,000 rpm

Orbit Diameter: 1.6mm

Sandpaper attachment: ClampDust extraction: With Microfilter

• Weight: 1.2 kg



STANDARD ACCESSORIES
Instruction Manual
Main Unit









TOOL KIT WIRELESS ELECTRICAL

MTK-3015



Specification:


Advisors:

- Two 20V rechargeable batteries,
- 1x Brushless Combi D20
- 1 115 mm D20 brushless angle grinder,
- 1 D20 brushless impact wrench,
- 1 D20 triple base,
- 1 D20 nail/stapler,
- 1 D20 brushless circular saw,
- 1 D20 brushless circular saw,
- 1 D20 3.0Ah battery
- 1 D20 5.0Ah battery,
- 1x D20 fast battery charger,
- 1 x 550 mm tool bag with wheels

STANDARD ACCESSORIES











ELECTRIC PLANER

MT-124E

Specification:

Power: 620 WVoltage: 220 V

Cutting width: 82 mm (3-1/4")Cutting depth: 2.5 mm (3/32")

• Grinding: 9 mm

No load speed: 17,000 rpm



STANDARD ACCESSORIES
Instruction Manual
Main Unit









PORTABLE CIRCULAR SAW

MT-87S



Specification:

- Used for cutting wood, faster and more efficiently
- Ergonomic handle with rubberized area
- Axle lock for changing discs
- With dust outlet
- Adjustments for angled and deep cuts Accessories included:
- 1 circular saw blade 185mm 24D
- 1 parallel guide
- 1 vacuum cleaner adapter
- 1 hex key
- Voltage: 220V
- Power: 1500W
- Charging speed: 5500/min
- Saw blade diameter: 185mm x 24D
- Internal disc hole: 20mm
- Cutting capacity: 90°: 65mm ;45°: 45mm and Angular cuts: 0 45°
- Machine weight: 4.06Kg



FDA CERTIFIED





PORTABLE ELECTRIC TUPIA

MT-321TM


Specification:

Power: 550W

Additional data:

- Number of revolutions (no load): 33000 rpm
- Tweezers Ø: 6 mm Package Contents:
- 1 Straight Acrylic Base
- 1 Parallel Guide
- 1 Guide with Bearing
- 1 Copy Guide
- 2 Fixed Wrenches 10/17 mm
- 16 mm tweezers Product Dimensions:
- Height X Width X Length: 10.8 x 17 x 24 cm
- Weight: 1.5 kg















DISC SAW FOR CUTTING CROSS

MT-108DR



- Cutting capacity, 0° 70 x 270 mm
- Cutting capacity, 45° (miter) 70 x 190 mm
- Cutting capacity, 45° (tilt) 45 x 270 mm
- Miter adjustments 47 ° Left / 47 ° Right.
- Bezel adjustment 45 ° Left / 0 ° Right.
- Speed approx. saw rotation speed: 4,600 rpm
- Saw dimensions 216 x 30 x 1.7 mm
- Cutting depth 70mm
- SDS saw blade lock system
- Weight approx 15 kg
- 2 18V / 8.0Ah batteries

It is include:

- 2 18V / 8.0Ah Batteries (As specified above)
- 1 quick charger (Ex: GAL 1880 CV)
- Support plate
- Dust collection bag



STANDARD ACCESSORIES

Instruction Manual Main Unit



FDA CERTIFIED







SET OF GOUGIES FOR TURNING WOOD

MT-398G



Specification:

Description

• The blades are made of carbon steel and have wooden handles. The set includes 8 of the most common gouge tips. Great for sculpting, carving, and drawing in wood, clay.

Basic Specification:

- Material: Carbon steel and wood
- Size: around 13cm
- Package contents: 10 gouges Set of 18 gouges for wood turning Description









TOOL KIT OF 69 PIECES

MT-78A



Tool box with 69 pieces, consisting of the following items:

- 16 hex keys
- 5 Clips
- 1 6" pliers for sliding joints
- 16" long nose pliers
- 16" diagonal cutting pliers
- 4 Screwdrivers (different dimensions)
- 1-bit extension bar
- 1 Level / 20 bits
- 12 1/4" sockets and 1 12 oz hammer
- 1-bit driver handle and
- 15m measuring tape
- 1 1/4" ratchet wrench with holder (plastic)
- 1 Box



STANDARD ACCESSORIES











SET OF TOOLS 69 PARTS

MT-85C



Specification:

- Manual compass,
- Made of steel,
- With aluminum arms,
- With a firm screw joint that allows opening adjustment.



FDA NSIC CERTIFIED





100 CM CLAMP

MT-99A

Specification:

- Cast iron structure.
- Protective plastic bases to avoid damaging the piece.
- Wooden handle.
- Clamping force of up to 170 kg.



STANDARD ACCESSORIES











60 CM CLAMP

MT-99A

Specification:


- Cast iron structure.
- Protective plastic bases to avoid damaging the piece.
- Wooden handle.
- Clamping force of up to 170kg.



STANDARD ACCESSORIES











30 CM CLIP

MT-99A

Specification:

- Cast iron structure.
- Protective plastic bases to avoid damaging the piece.
- Wooden handle.
- Clamping force of up to 170kg.



STANDARD ACCESSORIES











SET OF TOOLS FOR DRILLING WOOD

MT-487DW



Drill sets in plastic cases, with:

- Eight drills (cylindrical) of 3,4,5,6,7,8,9 and 10mm
- Eight drills (flat) of 10, 12, 14, 16, 18, 20, 25 and 32 mm



STANDARD ACCESSORIES

Instruction Manual Main Unit







5001 -16603 -22609 -22612 Certified Company FDA - GMP - NSIC - MSME - DRUG LICENCE





SQUARE OF 12" CARPENTER

MT-749SC



Specification:

• Made from hardened steel (30 cm)











SET OF FILES WOOD

MT-654FL

Specification:

- 100 08 02, flat file (second cut)
- 170 08 02, triangular file (second cut)
- 210 08 02, half-moon file (second cut)
- 230 08 02, round file (second cut)
- 343 08 02, file (half turn)



STANDARD ACCESSORIES
Instruction Manual
Main Unit











MANUAL CUTTING SCISSORS SHEET METAL

MT-2745

Specification:

• (10 inches)



STANDARD ACCESSORIES
Instruction Manual
Main Unit









HAMMER

MTS-2029



Specification:

- Length 34.00 cm
- Max diameter. of Cape 4.00 cm
- Head Diameter 27.00 mm
- Weight 0.65 kg
- Head Material Steel
- Handle Material Wood











BUBBLE LEVEL 1M

MTSE-55



Specification:

- Level Type Rectangular
- Number of Bubbles 3 bubbles for 0°, 45° and 90°
- Type of Material Aluminum and Thermoplastic
- Dimensions 1000x60x25 mm











SAW

MTS-2033B



Recommended Use - Wood

• Blade thickness: 1.25 mm

Blade length: 450.00 mm

Useful blade length: 450.00 mm
 Handle thickness: less than 3 cm

• Handle material: Wood



STANDARD ACCESSORIES











SET OF TOOLS PNEUMATIC TIRES (8 PIECES)

MT-36TL



Specification:

- 1 compressed air gun
- 1 SD tire inflator
- 1 high quality spiral hose made of polyurethane
- 2 pistols
- 1 3-piece adapter set

STANDARD ACCESSORIES











SET OF DRILLS FOR LONG HOLES

MT-195H



Specification:

- 1 drill with 12.8 mm shank sizes 8, 10, 12, 14 mm
- 1 drill with 15.8 mm shank size 16 mm
- In wooden box,

STANDARD ACCESSORIES
Instruction Manual
Main Unit







HAMMER DRILL PORTABLE

MTK-3019



Specification:

Basic description

- The 850W and 220V 13mm Impact Drill is has variable reversible rotation speed and has a rubberized handle, making work more comfortable and safe.
- Recommended for drilling in wood, masonry and steel.

Specifications:

- Reference WS3174
- Rated power: 850 W
- No-load rotation number: 0-3000 / (R.PM)
- Impact rate: 0-48000/min
- Chuck type: 13mm key chuck
- Maximum drilling capacity in steel: 13 mm
- Maximum drilling capacity in masonry: 16 mm
- Maximum drilling capacity in wood: 30 mm
- Machine size: 300 x 98 x 250 mm

Included Items:

- 1 Chuck key:1/2-13mm
- 1 Auxiliary Handle
- 1 Depth Limiter













JIG SAW

MT-43JS

Specification:

Voltage: 220V

Nominal absorbed power: 450W

No. of empty strokes: 800 - 3,100 cpm

Weight: 1.9 kg

Stroke length: 18 mm

Cutting depth in Wood: 65mm

Aluminum cutting depth: 10mm

Cutting depth in non-alloy steel: 3mm


Vibration emission value ah: 4.5 m/s²



Instruction Manual Main Unit

STANDARD ACCESSORIES









LITERATURE, WOODWORK AND CARPENTRY

MT-1365

Specification:

• Carpentry and Joinery Books, with relevant content related to all items in this lot, three copies for each title

STANDARD ACCESSORIES





