

Section 1: Identification of Product and Supplier			
Product Trade Name	Sangir POLYPROPYLENE Pipes & Fittings		
Product Use	Acid filling stations, Laboratories, Automotive Industry, Nuclear Research Industry, Chemical Industry, Paper Industry, Construction, Textile, Water Purification, Electroplating Plants, Refineries.		
Supplier	Sangir Plastics Pvt. Ltd. 3rd Floor, Mandhana Enclave, Near Canara Bank, Bangur Nagar, Goregaon West, Mumbai, Maharashtra, India. Postal Code: 400104. Tel.: +91 22 28717800 (30 lines) Fax.: +91 22 28741794 (fax) Email: sales@sangir.com		
Emergency (24 Hours)			

Section 2: Hazards Identification				
Statement of	NON-HAZARDOUS PRODUCT NON-DANGEROUS GOODS			
Hazardous Nature				
Poisons Schedule	Not listed.			
Hazard Statements	None required.			
Precautionary	None required.			
Statements				
Other Hazards	Refer to Section 7 Handling and Storage for general precautions for			
Other Hazarus	use.			

Section 3: Composition/Information on Ingredients					
Composition and Form	Manufactured rigid solid tubes of various dimensions for purposes as				
Composition and Form	described in Section 1.				
Chemical Composition	<u>Chemical Name/s</u>	Proportion			
	Polypropylene copolymer	94.5 - 97%			
	Black – pigment-polymer blend	5.50%			
	Dark Grey – pigment-polymer blend	3%			
	Light Grey – pigment-polymer blend	3%			



Section 4: First-Aid Measures			
Swallowed	There are no known health effects for the ingestion of polypropylene. Ingestion is unlikely to occur due to the physical size and dimensions of the products. However, small particles may be generated by sawing or mechanically breaking the products or similar means.		
Eye	Inapplicable to the solid product except for mechanical injury. Dust/small particles from sawing or other mechanical process may affect eyes if not protected. Hydrochloric acid and other fumes emitted during combustion can cause irritation to the eyes. Flush with copious quantities of water and treat symptomatically.		
Skin	Inapplicable to the solid product except for mechanical injury. Dust/small particles from sawing or other mechanical process may affect eyes if not protected. There have not been reports of irritation arising from such dust and small particles. Molten material will adhere to the skin and cause burns. Flush with copious quantities of water and see a doctor for prompt removal of the adhering material and treatment of the burn. Do not remove material or clothing from the skin. As removal may exacerbate the injury.		
Inhaled	Inapplicable to the solid product due to the physical size and dimensions of the products. For inhalation of fumes and gaseous by-products (carbon monoxide, carbon dioxide, etc), remove the patient immediately from exposure and seek medical advice.		
Notes to Physician	Treat symptomatically.		

Section 5: Fire-fighting	Measures
	Water, water-fog or foam to extinguish fire. Carbon dioxide or dry
Extinguishing Media	chemical are suitable but are considered not as efficient due to lack
- -	of cooling capacity.
	Wear fully protective body suit with self-contained breathing
Fire Fighting	apparatus (S.C.B.A.) to prevent contact with fumes and gases
	produced during combustion.
	Combustible and will support combustion. Products of combustion
Fire/Explosion Hazard	are carbon dioxide (asphyxiant), carbon monoxide (toxic) and low
	levels of aldehydes and acetic acid. All are potentially lethal in
	sustained exposure.
Fire Incompatibility	Oxidising agents.



	Wear fully protective body suit with self-contained brea	athing
Personal Protection	apparatus (S.C.B.A.) to prevent contact with fumes and	gases
	produced during combustion and appropriate gloves and footw	ear.

Section 6: Accidental Release Measures				
Minor Spills	Collect products and bundle or secure safely. If necessary, isolate area to prevent damage to /destruction of products by vehicles etc. Broken parts may be sharp and eye protection and gloves are recommended.			
Major Spills	Isolate area as necessary to prevent further damage. Collect products and bundle or secure safely. Broken product and parts may have sharp edges and eye protection and gloves are recommended.			

Section 7: Handling and	Storage
Procedure for Handling	Coils of pipe may have substantial elastic energy. When cutting bands, exercise caution to ensure that springing of the pipe, particularly at the ends, cannot cause injury. Injury can be sustained by rolling of pipes. Unpack crates and bundles on a flat surface and ensure that free stacks are adequately chocked. Do not climb on stacks. Normal safe practices should be employed when working with the material; a well ventilated area and the use of eye and protection, dust masks and gloves are recommended when sawing, grinding (with abrasive wheel) and handling. When heating for bending or other forming, use hot water or air with appropriate safeguards. Use of an open flame is inadvisable.
Storage	Store in appropriate areas (outside or in warehouse) in accordance with site safety requirements. Do not store with oxidising agents.

Section 8: Exposure Controls / Personal Protection				
Exposure Controls	No exposure controls are necessary as products are inert and all additives are encapsulated within the polymer matrix and present no hazard under conditions of normal use and good occupational work practice.			
Personal Protection Eye	Glasses Glasses are recommended in case of accidental knock when handling pipe and especially when working pipes mechanically, sawing etc.			



Hands/Feet	Safety footwo	ear and glo	ves.					
Engineering Controls	Appropriate	controls	for	safe	working	when	handling	and
Engineering controls	mechanically working e.g. sawing.							

Section 9: Physical and Chemical Properties				
Annogrango	Plastic pipes or tubes, 16mm to 630mm in diameter, upto SDR 11.			
Appearance	Colour: blue, white or black			
Odour	Nil			
pH:	Nil effect, insoluble			
Melting point	130 -170°C			
Initial boiling point and				
range	Not applicable			
Flash point	Not applicable			
Evaporation rate	Not applicable			
Flammability	Will burn in contact with flame			
Upper/lower	Not applicable			
flammability	Not applicable			
Vapour pressure	Not applicable			
Vapour density	0.9 – 1.0			
Relative density	insoluble in water			
Solubility	Not applicable			
Partition coefficient	Not applicable			
Auto-ignition				
temperature	Not applicable			
Decomposition	300°C			
temperature				

Section 10: Chemical Stability and Reactivity		
	Stable under normal conditions of storage and use.	
Incompatible materials	Do not store with oxidising agents.	
Hazardous decomposition products	Product will start to decompose if maintained at temperatures of 300°C. Decomposition products are carbon dioxide, carbon monoxides and low levels of aldehydes and acetic acid.	



F/C 002/PP dt. 5-1-2010 Rev 1.5

Section 11: Toxicological Information	
	Not applicable
LD ₅₀ Value	The products are inert and insoluble and consist of a fused polymer
	matrix which also encapsulates all additives.

Section 12: Ecological Information	
Ecotoxicity	No adverse effects on environment have been reported. The product can be physically removed from waterways by means appropriate to the size article. It is recommended that local environmental agencies are notified.

Section 13: Disposal Considerations

Recycle where possible.

Refer to state/territory environmental protection agency/ authority. Normally suitable for disposal as general waste land fill.

Section 14: Transport Information	
Land Transport	Not classified as a dangerous goods.
(Road/Rail)	
Marine Transport	Not classified as a dangerous goods.
Air Transport	Not classified as a dangerous goods.

Section 15: Regulatory Information

There is no safety, health or environmental regulations specific for these products.

Section 16: Other Information

Further information about characteristics of the product can be inferred from the brochure of Sangir Plastics Pvt. Ltd.

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.