

METAL CUTTING SOLUTIONS ANYWHERE ANY APPLICATION
ALL TYPES OF VERTICAL MANUAL BANDSAW MACHINE



Since 1994
AN ISO 9001 : 2008 Company

Model : VBM 150
AVAILABLE MODEL VBM 150 TO VBM 2000



- High Speed
- High Stability
- Extremely Simple Operation
- Minimal Space Requirement
- Low Maintenance and Long Life
- Excellent Cost-to-Performance Ratio

VERTICAL MANUAL BANDSAW MACHINE

Model : VBM 150 / VBM 250 / VBM 300



Since 1994

AN ISO 9001 : 2008 Company

Technical Data	VBM 150	VBM 250	VBM 300
Maximum Job Height (in mm)	150 mm	300 mm	500 mm
Blade to Column Throat (in mm)	250 mm	350 mm	350 mm
Main Drive HP	3 HP	5 HP	5 HP
Table Size (in mm)	500 x 500 mm	600 x 600 mm	500 x 700 mm
Work Table Operation	MANUAL	MANUAL	MANUAL
Blade Tension	MANUAL	MANUAL	MANUAL
Band Speed (Mtr / Min)	20 - 100 mtr / min	20 - 100 mtr / min	30 - 80 mtr / min
No. Of Band Wheels	2	2	2
Blade Size (in mm)	3000 X 27 X 0.9	3760 X 27 X 0.9	4100 X 34 X 1.1
Coolant Motor HP	0.13 HP	0.13 HP	0.13 HP
Floor Space Size (LxWxH) in MM	1000 X 1000 X 1610	1000 X 1000 X 1610	1000 X 1000 X 1610
Net Weight (Appx. in Kg)	750	1100	1950

Note : Vertical Bandsaw Machines are Customizable according to the Customer's requirements. Accordingly, all parameters will be changed as per the requirements.

Machine for Special Purpose Application

- For Tool Room Cutting including Relief Angle on Stamping Dies
- Die Cast Runner and Riser Cutting
- Aluminum Cylinder Head Cutting
- Aluminium Cast Slab Ends Cutting Online
- Circle Cutting Machines for Ferrous, Non Ferrous and Non Metals
- Versatility for Special Purpose Applications
- Destructive Testing of Radial Tyre for Cords spacing
- Destructive Testing of Automobile Engine Block
- Rail Slitting for Points & Cross Expansion Joints
- Graphite Block Cutting
- Scrapper Notch Cutting for Sugar Industries
- Silica Slab Cutting for Solar Chips

STANDARD ACCESSORIES

- Fully Welded, Heavy Duty Structure, Vibration Free Construction
- Adjustable Cutting Feed (Optional)
- Improved Blade Guide Mechanism with Carbide & Bearings
- Less Tooling Cost due to Higher Blade life
- Less Power Consumption due to Continuous Cutting
- Good Parallelism in Cutting due to Adjustable Blade guide
- Hydraulic Blade Tension (Optional)
- Variable Frequency Drive
- Tilting Table on RH / LH (Optional)

VERTICAL
BAND SAW MACHINE
Model : VBM - 150



Note : 1. Above Specification, Data & Design are subject to change without prior notice for Modification & Improvement
2. Optional Accessories shown in Machine Photographs are at an extra cost.

Made For Heavy Duty Application

359/B-360/2, Makarpura GIDC,
Vadodara-390010, Gujarat, India.

+91-9879611699
www.multicut.in | sales@multicut.in