

HTP-550
(1/2" Impact Wrench)



Torque : 550 N.M
Bolt Capacity : M16
Air Consumption : 4.2 CFM
Free Speed : 7500 RPM
Weight : 2.6 kg

HTP-238
(1/2" Impact Wrench - Stubby)



Torque : 680 N.M
Bolt Capacity : M16
Free Speed : 10000 RPM
Weight : 1.4 kg
Length : 109 MM

HTP- 2800
(1" Impact Wrench)



Torque : 2800 N.M
Bolt Capacity : M38
Air Consumption : 7.0 CFM
Free Speed : 3500 RPM
Weight : 14 kg

SI-1860
(1" Impact Wrench)



Torque : 2500 N.M
Bolt Capacity : M41
Air Consumption : 13.8 CFM
Free Speed : 4700 RPM
Weight : 10.9 kg

I-30
(3/8" Impact Wrench - Butterfly)



Torque : 102 N.M
Bolt Capacity : M10
Air Consumption : 6 CFM
Free Speed : 10000 RPM
Weight : 0.95 kg

CDR-118
(3/8" Reversible Drill)



Chuck Capacity : 10 MM
Air Pressure : 6 CFM
Free Speed : 1800 RPM
Air Consumption : 6 CFM
Weight : 1.12 kg

CDR-208
(1/2" Reversible Drill)



Chuck Capacity : 13 MM
Air Pressure : 6 Bar
Free Speed : 800 RPM
Air Consumption : 5 CFM
Weight : 1.95 kg

RY-311
(3/8" Straight Drill)



Chuck Capacity : 10 MM
Air Pressure : 6 Bar
Free Speed : 2600 RPM
Air Consumption : 6 CFM
Weight : 0.90 kg

CDG-210R-A1
(1/4" Die Grinder)



Collect Size : 6 MM
Air Consumption : 6 CFM
Free Speed : 24000 RPM
Length : 178 MM
Weight : 0.60 kg

CDG-215
(Extension Die Grinder)



Collect Size : 6 MM
Horse Power : 0.5 HP
Air Consumption : 6.0 Bar
Free Speed : 21000 RPM
Weight : 0.80 kg

CDG-220R-A1
(1/4" Angle Die Grinder)



Collect Size : 6 MM
Air Consumption : 3 CFM
Free Speed : 18000 RPM
Length : 178 MM
Weight : 0.8 kg

CDG-4108
(Extension Die Grinder)



Collect Size : 6 MM
Horse Power : 0.5 HP
Air Consumption : 8.0 Bar
Free Speed : 18000/21000 RPM
Weight : 1.8 kg

MG80
(Pencil Die Grinder)



Collect Size : 3 MM
Air Consumption : 4 CFM
Air Pressure : 6 Bar
Free Speed : 70000 RPM
Weight : 0.20 kg

RP-207
(1/2" Ratchet Wrench)



Torque : 95 N.M
Bolt Capacity : 13 MM
Air Consumption : 3 CFM
Free Speed : 160 RPM
Weight : 1.39 kg

S30
(POP Rivet with vacuum)



Strok Length : 19 mm
Air Pressure : 6.2 Bar
Rivet Capacity : 2.4-4.8 mm
Air Consumption : 6.0 CFM
Weight : 1.36 Kg

S70
(POP Rivet)



Strok Length : 26 mm
Air Pressure : 6.2 Bar
Rivet Capacity : 4.0-6.4 mm
Air Consumption : 6.0 CFM
Weight : 1.36 Kg

HTP-10B
(Belt Sander)



Belt Size : 10 X 330 mm &
Free Speed : 16000 RPM
Air Consumption : 6.0 CFM
Weight : 0.9 Kg
Length : 260 MM

HTP-20B
(Belt Sander)



Belt Size : 20 X 520 mm
Free Speed : 16000 RPM
Air Consumption : 6.0 CFM
Weight : 1.2 Kg
Length : 340 MM

Hitech SI-2210
(Disc Sander)



Pad/Disc Size : 4" & 5"
Free Speed : 10000 RPM
Air Inlet : 1/4"
Air Consumption : 3.9 CFM
Weight : 0.99 Kg

RY-0319A
(Non Vacuum Disc Sander)



Pad/Disc Size : 5" & 6"
Free Speed : 10000 RPM
Air Inlet : 1/4"
Air Consumption : 6 CFM
Weight : 1.10 Kg

<p>RY-4S (4" Angle Grinder)</p>  <p>Wheel Capacity : 100 MM Free Speed : 12000 RPM Air Consumption : 8 CFM Weight : 1.20 Kg Length : 188 MM</p>	<p>4015 B (Straight Grinder)</p>  <p>Wheel Capacity : 150 X 25 Free Speed : 6000 RPM Spindel Thared : M-16 Weight : 6.2 Kg Length : 535 MM</p>	<p>HTP2000 (Nut Insert machine)</p>  <p>Insert Size : M3-M12 Air Pressure : 6.2 Bar Air Consumption : 6.0 CFM Free Speed : 2000 RPM Weight : 2.2 Kg</p>	<p>HTP750 (Nut insert)</p>  <p>Insert Size : M5 & M6 Air Pressure : 6.2 Bar Air Consumption : 8 CFM Free Speed : 750 RPM Weight : 1.8 Kg</p>
<p>CSD-50 (Adjustable Clutch Screw Driver)</p>  <p>Capacity : 4 mm Free Speed : 1700 rpm Max Torque : 1-3.5 Nm Air Consumption : 4 CFM Weight : 0.60 Kg</p>	<p>CSD-56 (Adjustable Clutch Screw Driver)</p>  <p>Capacity : 6 mm Free Speed : 1800 rpm Max Torque : 5-13 Nm Air Consumption : 5 CFM Weight : 1.13 Kg</p>	<p>CSD-81 (Pistol Adj. Clutch Screw Driver)</p>  <p>Capacity : 8 mm Free Speed : 800 rpm Max Torque : 5-17 Nm Air Consumption : 5 CFM Weight : 1.20 Kg</p>	<p>TP-30B (Auto Shut off Screw Driver)</p>  <p>M/C Screw Dia. : M 1.7 to M 2.2 Rang : M 1 to M 11 Torque : 1-8 Kgf.cm Free Speed : 1000 RPM Air Consumption : 1-8 CFM</p>
<p>SI-1070 (Impact Driver)</p>  <p>Max. Torque : 35 NM Bolt Capacity : 06 MM Free Speed : 11000 RPM Air Consumption : 2.1 CFM Weight : 0.65 Kg</p>	<p>HTP-20 (Pistol type Air Tapping Tool)</p>  <p>Tapping Cap : M13 Forward Speed : 320 RPM Reverse Speed : 580 RPM Length : 330 MM Weight : 2.9 Kg</p>	<p>HTP-400 (Streight type Air Tapping Tool)</p>  <p>Tapping Cap : M6 Forward Speed : 700 RPM Reverse Speed : 1500 RPM Length : 290 MM Weight : 2.1 Kg</p>	<p>HTP800 (Tapping Tool)</p>  <p>Tapping Cap : M3-M12 Air Pressure : 6.2 Bar Air Consumption : 8 CFM Free Speed : 800 RPM Weight : 1.6 Kg</p>
<p>B-281R (Air Scissors)</p>  <p>Cutting Capacity : 1.2 MM - Steel : 1.4 MM - Alu Free Speed : 2500 RPM Air Consumption : 8 CFM Weight : 1.1 Kg</p>	<p>703 (Chipping Hammer)</p>  <p>Strock : 76.2 BPM : 1900 + 5% Air Consumption : 35 CFM Weight : 7.33 Kg Length : 378 MM</p>	<p>Hitech H-30 R (Air Hammer)</p>  <p>Chisel Shank : 0.401 In Piston Strock : 92 MM BPM : 2200 Air Consumption : 6 CFM Weight : 2.2 Kg</p>	<p>Hitech B-13 (Air Saw & Filer)</p>  <p>Cutting Capacity : 2 MM - Steel : 3 MM - Alu Stroke : 10 MM BPM : 5000 Weight : 0.8 Kg</p>
<p>ADQ-19 (Pneumatic Strapping Tool)</p>  <p>Strap Material : Pet Strap, PP Strap Strap Width : 12-19 MM Strap Tension : 2800 N Strapping Speed : 5m/min Weight : 3.8 Kg</p>	 <p>• Pressure at the working : 90psi/6.3 bar • Max Hose Length : 10m • Lubrication : Daily Lubricating Oil</p>		

Hi-Tech Pneumatic

Head Office : C-201, Siddharath Annexe-3, Nr. Hotel Plazzo, N.H No .8, Vamali, Vadodara 390008. (M) : + 91 96240 74440
E-mail :- devangt@hitechpneumatic.com

Branch Office : 1, Shlip Goverdhan Industrial Estate, Opp. IDFC Bank, Kathwada, Ahmedabad 382430. (M) : + 96240 14440
E-mail :- niravt@hitechpneumatic.com

Branch Office : 26, Sanghavi Tower, Nr. Gujarat Gas Circle, Adajan, Surat 395009. (M) : + 96240 93939
E-mail :- sales@hitechpneumatic.com