

# Octabrid Video Recorder

Model: **iV-OV0404H2-V2**



iV-Pro® Model - iV-OV0404H2-V2 is a 4 Channel 8MP Pro HD Octabrid Video Recorder that delivers high resolution up to 8MP HD recording videos that supports 4K Cameras. The new Octabrid supports H.265+ Video Compression for more space storage and better performance. Octabrid technology features channel type settings to change from AHD to iP-HD Mode and Mix Mode.

It also supports 10/100 Ethernet connection for a smooth video playback. Its Connectivity includes HD HDMI Output, VGA, Cloud Technology, Wi-Fi & 4G, and many more features, along with software support for Computers and Mobile Apps.

## Features



- 4 Channel 8MP dedicated HD Octabrid Video Recorder
- 5 in 1 technology supports AHD,TVi, CVi, CVBS and XVi
- Supports multiple channel mode choices, with up to 4K iP-HD
- Advanced H.265+ technology for maximum recording time
- Graphical User Interface function operated from mouse or remotely
- Supports 2 Sata Drives of 8TB each with total capacity up to 16TB
- Instant backup on pen drives and external storage drives
- Easy access from computers and mobile phones with 4G and Wi-Fi
- New Intelligent Ai features: Face and Human Detection with Mobile Notification

# Technical Specifications:



Model	iV-OV0404H2-V2
MAIN PROCESSOR	Quad-core embedded processor
OPERATING SYSTEM	Embedded LINUX
AHD VIDEO INPUT	4 X 8MP (4K)
AUDIO INPUT/OUTPUT	4 Channel Input/1 Channel Output, RCA
INTERFACE	HD-HDMI; 1 VGA
RESOLUTION	8MP; 5MP; 4MP; 3MP; 2MP; 1MP
DISPLAY SPLIT	1/4
OSD	Camera title; Time; Video loss; Camera lock; Motion detection; Recording
COMPRESSION	H.264/ H.265+
RECORDING RESOLUTION	4K; 1980p; 1580p; 1080p; 720p and CIF
FRAME RATE	1–15/25 fps
VIDEO BIT RATE	16 kbps ~ 20 Mbps, per channel
RECORDING MODE	Schedule (Regular/Continuous, Motion Detection, Alarm); Manual; Stop
VIDEO DETECTION	Motion Detection—MD Zones: 396 (22 × 18); Video Loss; Camera Blank
CUSTOM MODE	AHD to iP-HD Signal conversion with choice
INTELLIGENT AI	Face & Human Detection with alarm perimeters
ALARM INPUT	None
SYNC PLAYBACK	4*8MP
SEARCH MODE	Search by Time/calendar/event/channel
PLAYBACK FUNCTION	Play; Pause; Stop; Rewind; Fast play; Slow play; Next File; Previous File; Next Camera; Previous Camera; Full Screen; Repeat; Shuffle; Backup selection; Digital Zoom
BACKUP MODE	USB Device; Network
ETHERNET	1 RJ-45 port (10/100 Mbps)
SMART PHONE COMPATIBILITY	iPhone; iPad; Android
INTERNAL HDD	2 SATA Ports; up to 16TB
EXTERNAL HDD	Support Via USB
USB PORTS & RS232 PORTS	3 (2 rear USB3.0; 1 front USB2.0), 1 Port for Communication
POWER CONSUMPTION	17.5 W max (without HDD), 100~240 VAC, 50/60 Hz
OPERATING TEMPERATURE & DIMENSIONS	14°F to 131°F (–10°C to 55°C) (LXBXH)mm 320X244X50
WEIGHT (WITHOUT HDD)	2.85 KG

# Connection Diagram:



✉ info@ivpro.in 🌐 www.ivpro.in




scan this QR Code

**Customer Care**  
care@ivpro.in




Specifications are subject to change without notice.  
iV-Pro is a trademark of iView Technologies Co, India & Hongkong.  
Copyright 2017 iView Technologies Co. All rights reserved.

# Connection Diagram:



✉ info@ivpro.in 🌐 www.ivpro.in



 **Customer Care**  
care@ivpro.in



Specifications are subject to change without notice.  
iV-Pro is a trademark of iView Technologies Co, India & Hongkong.  
Copyright 2017 iView Technologies Co. All rights reserved.