



India's Leading solution provider in Wet Processing technology, guarantees high spec sand products, ready for market-use.

AESHAWASH™
SAND CLASSIFICATION AND
DEWATERING SYSTEM

Customized solution to our user specification requirement and raw material properties to match new product standards.



Key Features

- Class Leading Cyclone to control accurately silt cut point to set product specs.
- High efficient grading of two output sand product to deliver quality.
- User centric solution on Low & Easy Maintenance, easy access and low operating cost.
- Compact & Combined solution to perform in every application, reduces space and installation time.
- Max. amount of water recyclability to reduce environmental impacts.

Technical Specification of the AESHAWASH outlined below

AESHAWASH	Cyclone Size	Total Power (HP)	Production Capacity (t/hr)	Water in Circuit (m ³)	Screen Area (m)
AW-30	250	18	25	70	0.9x1.8
AW-50	325	25	45	120	1.2x2.4
AW-80	400	30	70	200	1.5x2.6
AW-100	500	38	90	250	1.5x3.0
AW-150	2x500	50	125	350	1.8x3.5
AW-200	2x625	65	170	450	2x4
AW-250	4x400	85	230	600	2.2x4.5

Capacity available from 30 - 250 TPH

*Details may vary based on application

Head Office

"Our excellent washing solution to value addition in your product, will help you start and grow your business across industry horizon.

Plot No. 0358, Road No.7, GIDC Kathwada
Ahmedabad (IN).
+91-9426529038 / 9537284409
info@aeshaindia.com
www.aeshaindia.com/aeshawash