




POS-615

POS System

Essae[®]
...for Excellence



Powered by the latest 6th generation Core i3/i5 Processor. Delivers exceptional Performance & Power even in the most demanding applications.




Technical Specifications

Model	POS-615B	POS-615C	
CPU	Intel Baytrail J1900 QUAD CORE 2.00 GHz Processor Embedded, Low Power, FANLESS Processor, 2 MB Cache Memory Intel	Intel Core i3 3.20 Ghz processor 3 MB Cache Memory	Intel Core i5 2.20 Ghz Processor 6 MB Cache Memory
Chipset	Baytrail J1900 with Integrated Graphic Chipset	Intel H1 10 Chipset	
Operator Display			
Size	38.1 cm (15") TFT LCD with LED Backlight, Anti-glare		
Maximum Resolution	1024 x 768		
Brightness	350 nits		
Touch Screen	Projected Capacitive Touch (PCAP) - True FLAT		
Memory			
Storage Memory	128 GB Solid State Disk (SSD) or 500 GB HDD		
System Memory	4 GB DDR3L RAM (expandable upto 8 GB)	4 GB DDR4 RAM (expandable upto 16 GB)	
External Interface Ports			
USB	5		
Serial (DB9)	3	4	
Network	1 x Gigabit LAN	2 x Gigabit LAN	
Display Port	1 x VGA	1 x HDMI	
Audio	1 x Line-in, 1 x Line-out		
Factory Options	Wi-Fi LAN Module (Mini-PCIe)		
Environmental			
Operating Temperature	50 C ~ 400 C		
Storage Temperature	-200 C ~ 550 C		
Power Adapter	DC 12 V / 5 A, 60 W		
Dimension (W x D x H)	40 tilt angle : 382 mm x 220 mm x 356 mm 840 tilt angle : 382 mm x 294 mm x 300 mm		
Optional Accessories			
Printer	High Speed POS Thermal Printer, 79.5 mm paper, 220 mm/sec, auto-cutter (Serial+USB+LAN) interface		
Cash Drawer	5-Bill/8-Coin Metal Cash Drawer with Lock & Key and micro-switch		
MSR	3 Track-OPOS Compliant, USB interface		
Customer Display	26.4 cm (10.4") Touch (PCAP) LCD, USB Interface (rear mounted) Display resolution: 800 x 600		
Mounting Options	VESA-Compliant Wall Mount Kit		
Net Weight (without accessories)	6.1 kg (approx)		
Housing	Front Cover : ABS Plastic, Back Cover : Aluminium, Stand ABS Plastic		
Operating System			
Operating System Supported (Both 32-bit & 64-bit versions)	Windows 10 IoT Enterprise 2016 LTSB Entry Windows Embedded POS Ready 7 Linux (subject to confirmation)	Windows 10 IoT Enterprise 2016 LTSB Value Windows Embedded POS Ready 7 Linux (subject to confirmation)	

Accessories



26.4 cm (10.4") LCD
Customer Display



MSR

Essae-Teraoka Pvt. Ltd.

410, 100ft Road, 4th Block,
Koramangala, Bengaluru-560 034
info@essae.com
http://www.essae.com

+91 80 2511 3021
1-800-425-3111
0-78488 12346

Essae[®]
...for Excellence

Your **Essae** representative

Note: Specifications are subject to change without notice. Other names and logos used are property of respective brands.

Form No.CAT-POS-615-060 R06