



54, Annapurna Industrial Estate, Tilak Road,  
Ghatkopar (E), Mumbai - 400 077 India  
Tel: +91-22-21029911  
E-mail: sales@excellaelectronics.com



## DC - DC CONVERTER

### TECHNICAL SPECIFICATION

<b>MODEL</b>	EE48-48V05A
<b>INPUT</b>	
I/P	48V DC
Range	40-65V DC
Fuse Protection.	
I/P MOV	
Soft Start	
Inrush current	---
<b>OUTPUT</b>	
Nominal Voltage	48V DC
Voltage Range	V
Current	5A
Line Regulation	+/- 0.5%
Load Regulation	+/- 1%
Ripple	+/- 1% (P-P)
Noise	+/- 1%
Protections	a) Overload Protection auto recovery type. b) Short circuit protection auto recovery type. c) OVP Protection Latching type.
Current Limit.	
<b>ENVIRONMENTAL</b>	
Operating temperature upto 50° C.	
Humidity	< 95% Rh
IP 21	
<b>GENERAL</b>	
Isolation	Input to Output KV Input to Earth -KV Output to Earth- V
MTBF	50K Hrs to MIL
<b>INDICATIONS LED</b>	a) Input OK b) Output OK c) Output OVP
<b>MECHANICAL</b>	
Dimension	195W X 130D X 95H mm
Cooling type	Fan
Weight	1.4 Kgs
<b>OPTIONAL</b>	
Redundancy by external diode.	