

EAC—18 TOP / BOTTOM / SIDE DISCHARGE- SINGLE/ THREE PHASE

Low Cost Cooling & Dust Free Environment for Factories &



Voltage	: SINGLE PHASE/THREE PHASE, 240 / 415V 50 Hz
Power Consumption	: 1000W
Noise	: < 70 dB
Airflow Rate	: 18000 m ³ / h
Static Pressure	: 30 mm
Water consumption	: 15-20 L/h
Water Tank Capacity	: 30 L
Net Weight	: 80 Kg
Gross Weight	: 100 Kg
Physical Size	: 127 x 127 x 119 cm

EAC—22 TOP / BOTTOM / SIDE DISCHARGE – THREE PHASE

Perfect Air Cooling Systems for Commercial Applications



Voltage	: THREE PHASE, 415 / 50 Hz
Power Consumption	: 2000 W
Noise	: < 70 dB
Airflow Rate	: 22500 m ³ / h
Static Pressure	: 30 mm
Water consumption	: 20-25 L/h
Water Tank Capacity	: 30 L
Net Weight	: 90 Kg
Gross Weight	: 120 Kg
Physical Size	: 127 x 127 x 119 cm

EAC-27 TOP / BOTTOM / SIDE DISCHARGE - THREE PHASE

Premium Cooling Systems with Low Sound Level



Voltage	: THREE PHASE, 415 / 50 Hz
Power Consumption	: 3000 W
Noise	: < 70 dB
Airflow Rate	: 27000 m ³ / h
Static Pressure	: 30 mm
Water consumption	: 25-30L/h
Water Tank Capacity	: 30 L
Net Weight	: 100 Kg
Gross Weight	: 140 Kg
Physical Size	: 127 x 127 x 119 cm

EAC-30 TOP/ BOTTOM/ SIDE DISCHARGE

High Static & High Air Flow Machine for Industries



Voltage	: THREE PHASE, 415 / 50 Hz
Power Consumption	: 3000 W
Noise	: < 70 dB
Airflow Rate	: 30000 m ³ / h
Static Pressure	: 35 mm
Water consumption	: 25-35 L/h
Water Tank Capacity	: 30 L
Net Weight	: 125 Kg
Gross Weight	: 155 Kg
Physical Size	: 125 x 125 x 142 cm

KT 35 B/KT 45 B/KT 60 B (CENTRIFUGAL) SIDE DISCHARGE-THREE PHASE

S.S. Construction for Long Life & High Static



Voltage	: THREE PHASE, 415 V / 50 Hz
Power Consumption	: 11000 W / 13000 W / 16000 W
Noise	: < 70 dB
Airflow Rate	: 30000 / 45000 / 60000 m ³ / h
Static Pressure	: 55 mm
Water Tank Capacity	: 80 / 100 / 100 L
Net Weight	: 450 / 585 / 650 Kg
Physical Size	: 180 x 180 x 140 cm 224 x 210 x 185 cm 220 x 210 x 180 cm