




PICTURE	DESCRIPTION	Cartons (CM) L*W*H	N.W (KG)	G.W (KG)
	<p>Rated Voltage: 220-240V/50Hz/60Hz 110V/60Hz  Rated Power: 1500W  Rated Capacity: 4-6kg  Tray Size: 200*450*20mm  Tray Qty: 4  Drying Area: 0.4m<sup>2</sup>  Product Size: 700*630*900mm  Net Weight: 80kg  Control Method: Digital Control  Noise Level: 60dB</p> <p>Features:</p> <ul style="list-style-type: none"> <li>•Imported Compressor;</li> <li>•Advanced Drying Tech;</li> <li>•Intelligent Temp Control;</li> <li>•Real Time Temperature Display;</li> <li>•Convenient Operation;</li> <li>•Clear Observation;</li> </ul>	82*72*135	80	150

PICTURE	DESCRIPTION	Cartons (CM) L*W*H	N.W (KG)	G.W (KG)
	<p>Rated Voltage: 220-240V/50Hz/60Hz 110V/60Hz  Rated Power: 2000W  Rated Capacity: 6-8kg  Tray Size: 310*440*30mm  Tray Qty: 4  Drying Area: 0.55m<sup>2</sup>  Product Size: 810*730*1180mm  Net Weight: 120kg  Control Method: Digital Control  Noise Level: 60dB</p> <p>Features:  •Imported Compressor;  •Advanced Drying Tech;  •Intelligent Temp Control;  •Real Time Temperature Display;  •Convenient Operation;  •Clear Observation;</p>	84*83*152	120	205

PICTURE	DESCRIPTION	Cartons (CM) L*W*H	N.W (KG)	G.W (KG)
	<p>Rated Voltage: 220-240V/50Hz/60Hz 110V/60Hz  Rated Power: 2000W  Rated Capacity: 8-10kg  Tray Size: 310*440*30mm  Tray Qty: 6  Drying Area: 0.82m<sup>2</sup>  Product Size: 810*730*1180mm  Net Weight: 130kg  Control Method: Digital Control  Noise Level: 60dB</p> <p>Features:  •Imported Compressor;  •Advanced Drying Tech;  •Intelligent Temp Control;  •Real Time Temperature Display;  •Convenient Operation;  •Clear Observation;</p>	84*83*152	130	215

PICTURE	DESCRIPTION	Cartons (CM) L*W*H	N.W (KG)	G.W (KG)
	<p>Rated Voltage: 220-240V/50Hz/60Hz 110V/60Hz  Rated Power: 2200W  Rated Capacity: 10-12kg  Tray Size: 265*435*30mm  Tray Qty: 8  Drying Area: 0.92m<sup>2</sup>  Product Size: 810*730*1180mm  Net Weight: 140kg  Control Method: Digital Control  Noise Level: 60dB</p> <p>Features:  •Imported Compressor;  •Advanced Drying Tech;  •Intelligent Temp Control;  •Real Time Temperature Display;  •Convenient Operation;  •Clear Observation;</p>	84*83*152	140	230