



Dry Single-plate Solenoid Brake



With guideway

型號 MODEL		TJ-B1-0.6	TJ-B1-1.5	TJ-B1-2.5	TJ-B1-5	TJ-B1-10	TJ-B1-20	TJ-B1-40						
靜摩擦轉矩 (kgm/Nm)		0.55(5.5)	1.1(11)	2.2(22)	4.5(45)	9(90)	17.5(175)	35(350)						
動摩擦轉矩 (kgm/Nm)		0.5(5.0)	1.0(10)	2.0(20)	4(40)	8(80)	16(160)	32(320)						
功率 Power [24V](W) at 20°C		11	15	20	25	35	45	60						
徑方向 Radius	A	63	80	100	125	160	200	250						
	C1	80	100	125	150	190	230	290						
	C2	72	90	112	137	175	215	270						
	C3	35	42	52	62	80	100	125						
	D	12 15	15 20	20 25	25 30	30 40	40 50	50 60						
	E	27.5	31	41	49	65	83	105						
軸方向 Shaft	H	18	20	22	24	26	30	35.1						
	J	3.5	4.3	5	5.5	6	7	8						
	K	2	2.5	3	3.5	4	5	6						
	L	25.55	28.8	32.9	37.3	42.5	50.5	59.6						
	M	15	20	25	30	38	45	54						
	P	7.5	9.5	8.9	9	11.5	9.5	15.5						
	Y	5	6	7	7	9.5	9.5	11.5						
	m	2-M4	2-M5		2-M6	2-M8		2-M10						
	a	0.2(±0.05)				0.3(+0.05/-0.1)			0.5(-0/-0.2)					
	b	4	5	5	5	7	7	7	10	10	12	12	15	
t	1.8	2.3	2.3	2.3	2.3	3.3	3.3	3.3	3.8	3.8	3.8	3.8	5	
重量 Weight (kg)	0.32		0.58		1.07		1.97		3.45		7.1		12.2	
保護帶子 Protective band	470KD07		GD80KD10				GD80KD14							

型號 MODEL		TJ-B2-0.6	TJ-B2-1.5	TJ-B2-2.5	TJ-B2-5	TJ-B2-10	TJ-B2-20	TJ-B2-40						
靜摩擦轉矩 (kgm/Nm)		0.55(5.5)	1.1(11)	2.2(22)	4.5(45)	9(90)	17.5(175)	35(350)						
動摩擦轉矩 (kgm/Nm)		0.5(5.0)	1.0(10)	2.0(20)	4(40)	8(80)	16(160)	32(320)						
功率 Power [24V](W) at 20°C		11	15	20	25	35	45	60						
徑方向 Radius	A	63	80	100	125	160	200	250						
	C1	80	100	125	150	190	230	290						
	C2	72	90	112	137	175	215	270						
	C3	35	42	52	62	80	100	125						
	D	12 15	15 20	20 25	25 30	30 40	40 50	50 60						
	E	27.5	31	41	49	65	83	105						
軸方向 Shaft	H	18	20	22	24	26	30	35						
	J	3.5	4.3	5	5.5	6	7	8						
	K	2	2.5	3	3.5	4	5	6						
	L1	37	44.8	53	61.3	73.5	87.2	102.6						
	L2	25.5	28.8	33	37.3	42.5	51.2	59.6						
	M	15	20	25	30	38	45	54						
	P	7.5	9.5	9	9	9.5	10.5	15.5						
	T	6	8	10	12	14	18	22						
	Y	5	6	7	7	9.5	9.5	11.5						
	m	2-M4	2-M5		2-M6	2-M8		2-M10						
	a	0.2(±0.05)				0.3(+0.05/-0.1)			0.5(-0/-0.2)					
	b	4	5	5	5	7	7	7	10	10	12	12	15	
	t	1.8	2.3	2.3	2.3	2.3	3.3	3.3	3.3	3.8	3.8	3.8	3.8	5.3
	重量 Weight (kg)	0.32		0.5		0.9		1.97		3.45		7.1		12.2
保護帶子 Protective band	470KD07		GD80KD10				GD80KD14							