

WHEEL DIA (INCH/MM) A	TREAD WIDTH (INCH/MM) B	CASTOR		HEIGHT (MM) C	PLATE SIZE (MM) D X E	BOLT HOLE CENTRE (MM) F X G	BOLT HOLT DIA. (MM) H	APPROX. LOAD CAPACITY FOR IDEAL WORKING CONDITION (KGS.)				
		FORK BASE	CODE					RBCI	PPWR	PPWS	PC	CI
4" (100)	1.1/2" (38)	ROUND	LRF	140	125 X 85	100 X 50	13	100	105	125	160	200
4" (100)	2" (50)	SQUARE	LSF	140	125 X 85	100 X 50	13	150	160	200	215	250
6" (150)	1.1/2" (38)	SQUARE	LSF	190	125 X 85	100 X 50	13	150	170	220	275	350
6" (150)	2" (50)	SQUARE	LSF	190	125 X 85	100 X 50	13	170	200	250	300	400
6" (150)	2" (50)	ROUND	HRF	200	150 X 105	120 X 60	14.5	175	225	275	350	450
6" (150)	3" (75)	SQUARE	HSF	200	150 X 105	120 X 60	14.5	225	250	325	400	500
8" (200)	2" (50)	ROUND	HRF	250	150 X 105	120 X 60	14.5	225	250	325	400	500
8" (200)	3" (75)	SQUARE	HSF	250	150 X 105	120 X 60	14.5	275	325	400	500	600
10" (250)	2" (50)	SQUARE	HSF	300	150 X 105	120 X 60	14.5	275	325	400	500	600