

Stainless-Steel Pipe Platform



Features:

- * Sand-blasted welded stainless-steel construction and brushed stainless steel load plate(1.4301/AISI304).
- * Hermetically sealed stainless-steel load cell could provide long lasting water proof function.
- * Rugged and durable construction makes the platform suitable in heavy duty application.
- * Comprehensive product line with various weight ranges and platform sizes.
- * Multi-functions of load platform combined versatile accessories can meet your exact requirements.

Accessories:

* Scale stand



Stainless steel
(for fastening the terminal on the weighing platform)

* Roller top



Stainless steel
(for wet environments)
Hot galvanized
(For dry environments)

* Ball top



Stainless steel
(for wet environments)
Hot galvanized
(For dry environments)

Specifications:

Model	Dimensions (mm)	Loadcell	Weight Range							
			6kg	15kg	30kg	60kg	150kg	300kg	600kg	
RNS2430	240x300	B9H	*	*						
RNS3040	300x400	BM6E			*	*	*			
RNS4050	400x500	BM6E				*	*	*		
RNS4660	460x600	BM6G				*	*	*	*	
RNS6080S	600x800	BM6G				*	*	*	*	*
RNS6080H*	600x800	B6F					*	*	*	*
RNS3030	300x300	B9H	*	*	*	*	*			
RNS4040	400x400	BM6E			*	*	*			
RNS5050	500x500	BM6E				*	*	*		
RNS6060	600x600	BM6G				*	*	*	*	
RNS8080S	800x800	BM6G				*	*	*	*	*
RNS8080H*	800x800	B6F					*	*	*	*
Verification Division Value			2g	5g	10g	20g	50g	100g	200g	
Accuracy Level: C3										
Working Temperature: -20°C~+50°C										
Relative Humidity: ≤95% (Need no condensation)										
IP Rating: Load cell IP67, IP68, IP69k										
Load Cell: ZEMC										



Model	L	W	H	L1	L2	W1	W2	H1	ΦD
RNS2430	300	240	112	310	240	250	180	65	54
RNS3040	400	300	112	410	340	310	240	65	54
RNS4050	500	400	112	510	440	410	340	60	54
RNS4660	600	460	140	610	540	470	400	68	54
RNS6080S	800	600	155	815	740	615	540	94	54
RNS6080H	800	600	175	820	740	620	540	94	54
RNS3030	300	300	112	310	240	310	240	65	54
RNS4040	400	400	112	410	340	410	340	65	54
RNS5050	500	500	112	510	440	510	440	68	54
RNS6060	600	600	140	610	540	610	540	75	54
RNS8080S	800	800	155	815	740	815	740	97	54
RNS8080H	800	800	175	820	740	820	740	97	54

* Non-standard products can be designed upon customer's requirements, or manufactured as client's drawings.

- All kinds of non-standard platforms & accessories can be customized.
- Different brands load cells are optional. Zemic load cell is installed if no special requirements.