

DATASHEET

SELECTABLE BATTERY CHARGER

PIPL-4810BCDS



A-426, Road No – 28, Wagle Estate MIDC
Thane-400604, Maharashtra, INDIA.
MOB:+91-8097707496/ +91-7208560460
Email:info@powertronindia.com
Web: www.powertronindia.com

600W BATTERY CHARGER

❖ FEATURES :

1. Wide input supply range.
2. Built in EMI filter, low ripple noise.
3. Protection: Short circuit / Over load / Over voltage.
4. 100% Full Load Burn in test.
5. High efficiency, long life and high reliability.
6. Miniature size.



❖ SPECIFICATION:

MODEL NO:		PIPL-4810BCDS
OUTPUT	BATTERY VOLTAGE	12VDC / 24VDC / 36VDC / 48VDC
	FLOAT VOLTAGE	13.5VDC / 27.0VDC / 40.5VDC / 54.0VDC
	BOOST VOLTAGE	14.4VDC / 28.8VDC / 43.2VDC / 57.6VDC
	RATED CURRENT	10A
	RATED POWER	600W
	RIPPLE & NOISE (max)	<1%Of Rated Voltage
	VOLTAGE ADJ.RANGE	USING SELECTOR SWITCH
	VOLTAGE TOLERANCE	Rated Voltage
	LINE REGULATION	<+/-1%
INPUT	LOAD REGULATION	<+/-1%
	VOLTAGE RANGE	180-270VAC
	FREQUENCY RANGE	50Hz
PROTECTION	EFFICIENCY	>85%
	OVERLOAD	Above 105% Rated Output Power Protection Type:Constant Current,Recovers automatically after fault condition is removed
	OVERVOLTAGE	125%-150%Rated Output Voltage Protection Type: Hiccup Mode, Recovers automatically after fault condition removed.
INDICATION	LED	AC OK / FLOAT ON / BOOST ON / BATT REV.
METERING	DIGITAL	OUTPUT V & I
ENVIRONMENT	WORKING TEMP.	(-5DegC To 55DegC.)
	WORKING HUMIDITY	20 To 90% RH Non Condensing.
	STORAGE TEMP./HUMIDITY	(-10 To 85DegC 10 To 95%RH)
	VIBRATION	(-10 To 500 Hz,2G,20min/Sweep,Period-1Hr,Each along X,Y,Z axes.
SAFETY & EMC	SAFETY STANDARD	Designed To Meet UL60950-1
	WITH STAND VOLTAGE	I/P-O/P:2KVDC,I/P-Earth:2KVDC
	ISOLATION RESISTANCE	I/P-O/P,I/P-Earth:100MOhms/500VDC.
OTHERS	EMI & EMC	Designed To Meet EN55022,EN61000-4-2.
	ENCLOSURE PROTECTION	IP-20
	COOLING	FORCED COOLING
	DIMENSION(L*W*H)	265*160*250mm(L*W*H)
NOTE	WEIGHT	4.8Kg
	1. All parameters NOT specially mentioned are measured at typical input, rated load and 25Deg C ambient temperature. 2. Ripple & noise are measured at 20MHz of bandwidth by using a 12"twisted pair-wired terminated with a0.1uF & 47uF parallel capacitor. 3. Tolerance includes set up tolerance, line regulation and load regulation. 4. The power supply is considered a component which will be installed into final equipment. The final equipment must be recon formed that it still meets EMC directives. 5. Specifications are subject to change without prior notice due to constant improvement in design & technology.	

SMPS IDC DC Converters | Adapters | Electro Plating Rectifier | POE SMPS | Battery chargers | DC AC Converter
DC Regulator Power supply | LED Driver | Inverter | CVT | Servo controlled Voltage Stabilizer | Transformer