

# DATASHEET

## BATTERY CHARGER

### PIPL-2450BCD



A-426, Road No – 28, Wagle Estate MIDC,  
Thane-400604, Maharashtra, INDIA.  
MOB:+91-8097707496/ +91-7208560460  
Email:info@powertronindia.com  
Web: www.powertronindia.com

#### 1500W BATTERY CHARGER

##### ❖ FEATURES :

1. Wide input supply range.
2. Built in EMI filter, low ripple noise.
3. Protection: Short circuit / Over load / Over voltage.
4. 100% Full Load Burn in test.
5. High efficiency, long life and high reliability.
6. Miniature size.



##### ❖ SPECIFICATION:

MODEL NO:		PIPL-2450BCD
OUTPUT	BATTERY VOLTAGE	24VDC
	FLOAT VOLTAGE	27.0VDC
	BOOST VOLTAGE	28.8VDC
	RATED CURRENT	50AMP
	RATED POWER	1500W
	RIPPLE & NOISE (max)	<1%Of Rated Voltage
	VOLTAGE SELECTION	SWITCH
	VOLTAGE TOLERANCE	Rated Voltage
	LINE REGULATION	<+/-1%
INPUT	LOAD REGULATION	<+/-1%
	VOLTAGE RANGE	180-270VAC
	FREQUENCY RANGE	50Hz
PROTECTION	EFFICIENCY	>85%
	OVERLOAD	Above 105% Rated Output Power Protection Type:Constant Current,Recovers automatically after fault condition is removed
	OVERVOLTAGE	125%-150%Rated Output Voltage Protection Type: Hiccup Mode, Recovers automatically after fault condition removed.
INDICATION	LED	AC OK / FLOAT ON / BOOST ON / BATT REV.
ENVIRONMENT	WORKING TEMP.	(-5DegC To 55DegC.)
	WORKING HUMIDITY	20 To 90% RH Non Condensing.
	STORAGE TEMP./HUMIDITY	(-10 To 85DegC 10 To 95%RH)
	VIBRATION	(-10 To 500 Hz,2G,20min/Sweep,Period-1Hr,Each along X,Y,Z axes.
SAFETY & EMC	SAFETY STANDARD	Designed To Meet UL60950-1
	WITH STAND VOLTAGE	I/P-O/P:2KVDC,I/P-Earth:2KVDC
	ISOLATION RESISTANCE	I/P-O/P,I/P-Earth:100MOhms/500VDC.
	EMI & EMC	Designed To Meet EN55022,EN61000-4-2.
OTHERS	ENCLOSURE PROTECTION	IP-20
	COOLING	FORCED COOLING
	DIMENSION(L*W*H)	410*190*335 MM
	WEIGHT	11.0KG
NOTE	1. All parameters NOT specially mentioned are measured at typical input, rated load and 25Deg C ambient temperature. 2. Ripple & noise are measured at 20MHz of bandwidth by using a 12"twisted pair-wired terminated with a0.1uF & 47uF parallel capacitor. 3. Tolerance includes set up tolerance, line regulation and load regulation. 4. The power supply is considered a component which will be installed into final equipment. The final equipment must be recon formed that it still meets EMC directives. 5. Specifications are subject to change without prior notice due to constant improvement in design & technology.	

SMPS IDC DC Converters | Adapters | Electro Plating Rectifier | POE SMPS | Battery chargers | DC AC Converter  
DC Regulator Power supply | LED Driver | Inverter | CVT | Servo controlled Voltage Stabilizer | Transformer