

Mahavir Pulling & Lifting Machine Heavy Duty

Adjustable handle
for easy operation.

Backward lever & Forward lever
placed in tandem providing a slim design and assuring power transfer along the center.

Spare shear pins
Two spare shear pins located in the carrying handle.

Built-in shearing pin
prevent overload. It functions at approx. 50% overload and the pins can be replaced without removing the load.

Anchor bolt
offers numerous and versatile connection possibilities with load hooks, sling ropes and sling chains.

Stamped serial number
for easy identification.

High strength cast aluminum alloy body
Light weight, simple to operate. Smooth contour design with large flat bottom surface for increased stability in horizontal as well as vertical working position.

Galv. steel wire rope mounted on a reel
every ropes is operationally tested to 150% of the rated capacity and is issued with an individual test certificate.



Specifications

Rated Capacity (T)	Pulling Capacity (T)	Rated forward travel (mm)	Rope diameter (mm)	Standard length of rope (m)	Net weight (kg)	Rated forward hand power (N)	Max. Overall size (mm)
0.8	1.2	≥ 52	8	20	15	≥ 331	428 x 64 x 235
1.6	2.4	≥ 55	11	20	27	≥ 445	428 x 64 x 235
3.2	4.8	≥ 28	16	20	46	≥ 441	545 x 97 x 286
5.4	8	≥ 30	20	20	95	≥ 745	660 x 116 x 350