

#### **Seed Coating Machines - Technical Data** Automatic Automatic Automatic Power Compressed Machine Batch batch requirement 3ph. 440V 50Hz chemical Capacity quantity measurement model dosing exit requirement & feeding (Kg.) 75-125 12 tons Yes Yes Yes 7 HP Yes **RAS-12T60** 50-75 **RAS-6060** 6 tons Yes Yes 10 HP Yes Yes 20-40 RAS-3560 4 tons 10 HP Yes Yes Yes Yes RAS-1560 10-20 2 tons Yes Yes 5 HP Yes Yes 2-10 3 HP RAS-1060-FA 1 tons Yes Yes Yes Yes 3 HP RAS-1060-A 2-10 0.9 tons Yes No No Yes RAS-1060-SA 2-10 0.8 tons No No 2.5 HP No Yes 2 HP RAS-1060-M 2-10 0.6 tons No No No No LAB COATER 10-100 gr. Yes

#### Product Dependent

Optional: Variable Frequency Drive (VFD) for Main Disc speed control.

## **NEW PRODUCTS**



**PACKING SYSTEM** 



**COTTON PKG. AUTOMATION** 



**IJP CONVEYOR** 



**LAB COATER** 



**FEEDING CONVEYOR** 



ONLINE DRYER

#### Authorized Dealer / Distributor :

### **RELIANCE** AUTOMATION SOLUTIONS

Plot No. 14-170/D, APIIC Industrial Park, Behind SBH, Patancheru, Hyderabad - 502 319, A.P. India, Ph: +918455-240356, Tele/Fax: +918455-240357 e-mail: contact@relianceautomations.com www.relianceautomations.com

# High Performance Seed Coating Machines for Field Crops and Vegetable Seeds











Reliance Automation offers high performance RAS brand Seed Coating Machines of following capacities to assist small to large seed processing companies. These treaters are used for coating value added seeds with costly seed treating materials like chemicals, polymers & colours.

0

G

M

Н

N

E

S














#### **Digital Seed Feeding Unit:**



- Features & Benefits:
- Batch size is controlled by digital load cells.
- ★ Instant batch size selection.
   ★ Pneumatic feeding system for accurate feeding.
- Pneumatic dump gate.



- ★ Machined housing with PU Peddler.
- ★ High precision Geared Motor for Peddler

## **Motorised Seed Feeding Unit:**



#### **Pneumatic Dump Gate**



- Pneumatic cylinder for opening and closing of the gate.
- Perfect matching with the shell with absolutely no gaps.
  - ★ Rotostat action ensures uniform coating.
  - ★ Cast steel disc with PU coated top surface.
  - ★ Separate drive for spinning disc (optional)
  - ★ Adjustable baffles for effective treatment.
  - ★ Dual seal protection for bearing housing.
  - ★ VFD drive to handle variety of seeds.

## **High Precision Disc Assembly**



#### **Dosing Pump - DP 16**



- Non contact / valve less pump.
- Consistent and accurate dosing.
- ★ Flow rate adjustable from;
  \* 200 ml to 8000ml/min for DP 16
- 60ml to 3000ml/min for DP 10 20ml to 1000ml/min for DD 08
- 25 to 30% saving in the chemical compared to conventional treators.

**Digital Dosing Pump - DD 08** 



#### **Control Panel**



- Separate control panel.
- ★ Auto/Manual options.
- ★ Programmable Logic Controller (PLC). ★ HMI operator friendly panel to change
- the settings based on requirement (optional).
  - ★ Motorized stirrer for slurry preparation

  - ★ Continuous slurry mixing arrangement.
     ★ Tank Capacity: 400L, 250L, 150L & 50 L suitable for various models.
  - ★ SS 304 Tank.



