

COATED FABRICS

DATA SHEET

	SPECIFICATION NO.:	1047	
DESCRIPTION	POLYMER COATING	BASE FABRIIC	TYPICAL APPLICATION
Single side Silicone coated Glass fiber vapor barrier fiabric	Silicone Rubber	Glass Fibre	Vapour Barrier Fabric
Property	Unit	Test Method	Result
Base Fabric Mass	g/m2	ASTM 3776	200
Construction	Threads/Inch		
Weave	NA		Plain
Fabric Thickness	mm		0.21
Coating Mass	g/m2	ASTM 3776	480
Overall Mass	g/m2	ASTM 3776	1030
Width	mm		1000
Finished Thickness	mm		0.8
End Use Specs	Non permeability to vapours		

TECHNICAL DATA SHEETS

The data presented in this leaflet are in accordance with the present state of our knowledge, but do not absolve the user from carefully checking all supplies immediately on receipt. We reserve the right to alter product within the scope of technical progress or developments. The recommendations made in this leaflet should be checked to preliminary trials because of conditions during processing over which we have no control, especially where other companies' raw materials are being used. The recommendations do not absolve the user from the obligation of investigating the possibility of infringement of third parties rights and, if necessary, clarifying the position. Recommendations for use do not constitute a warranty, either express or implied, of the fitness or suitability of the product for a particular purpose.

Elastomeric , Rubber coated Textiles			