

<b>COATED FABRICS</b>			
<b>DATA SHEET</b>			
<b>SPECIFICATION NO.:</b>	<b>1008M</b>		
<b>DESCRIPTION</b>	<b>POLYMER COATING</b>	<b>BASE FABRIIC</b>	<b>TYPICAL APPLICATION</b>
Coated Glass Fiber Aluminium Foil Fabrics	Neoprene	Glass Fibre	For fire -proof packet, suit, Bags & gloves. Pkg. material for moisture barrier, water proof , radiant heat resistance.
Property	Unit	Test Method	Result
Base Fabric Mass	g/m <sup>2</sup>	ASTM 3776	400
Construction	Threads/Inch		
Weave	Plain		Satin
Fabric Thickness	mm		0.33
Coating Mass	g/m <sup>2</sup>	ASTM 3776	105
Overall Mass	g/m <sup>2</sup>	ASTM 3776	520
Width	mm		1500
Finished Thickness	mm		0.41
End Use specs	Radiant heat reflective and flame retardant.		
<b>TECHNICAL DATA SHEETS</b>			
The data presented in this leaflet are in accordance with the present state of our knowledge, but do not absolve			

the user from carefully checking all supplies immediately on receipt. We reserve the right to alter product within the scope of technical progress or developments. The recommendations made in this leaflet should be checked to preliminary trials because of conditions during processing over which we have no control, especially where other companies' raw materials are being used. The recommendations do not absolve the user from the obligation of investigating the possibility of infringement of third parties rights and, if necessary, clarifying the position. Recommendations for use do not constitute a warranty, either express or implied, of the fitness or suitability of the product for a particular purpose.

--	--	--	--

Elastomeric , Rubber coated Textiles