

Sugar Mill Cleaner



Features:-

Self contained unit with trolley.

Heavy Duty 3 Phase Supply Motor with 2800 R.P.M.

Provided With Branded push button starter switch having Overload Relay.

Flexible shafts are easily connected & disconnected

Model No.	Motor H.P.	Speed (RPM)	Electric Supply
TC - 30	3.0	2800	3 PH
TC - 50	5.0		440 V
Tc - 75	7.5		50 HZ

Sugar Mill Flexible Shaft



Features:-

Heavy Duty Flexible shaft for sugar mill (Dry Application)

Inner core made up of multi layer spring Steel wires in opposite direction

Tempered Inner core

Glavanised strip outer casing with anti - friction lining.

Ball Bearing hand Piece

Inner Core mm (Inch)		12 - 13 (1/2")	15 - 16 (5/8")	19 - 20 (3/4")
Outer Casing mm (inch)		25 - 26 (1")	31 - 32 (1.1/4")	34 - 35 (1.3/8")
Length		Model No.	Model No.	Model No.
Mtrs	Feet			
7.50	25.00	IFS-105-25	IFS-106-25	IFS-107-25
9.00	30.00	IFS-105-30	IFS-106-30	IFS-107-30
10.00	33.00	IFS-105-33	IFS-106-33	IFS-107-33
12.00	40.00	IFS-105-40	IFS-106-40	IFS-107-40
15.00	50.00	IFS-105-50	IFS-106-50	IFS-107-50
18.00	60.00	IFS-105-60	IFS-106-60	IFS-107-60
20.00	65.00	IFS-105-65	IFS-106-65	IFS-107-65