





ZOLYTECH TECHNICAL PARAMETERS


Power	12KW
Main shaft speed	600-1200rpm
Dimension (L*W*H)	6900*4000*2300mm
Production speed	20-300m/h
Quilting width	2400mm
Quilting thickness	≤ 30mm
Stitch length	3-8(mm)
Needle type	22/140, 21/130
Space between needles	6.35mm(FRONT), 101.6(BACK)
Space between needle rows	76.2,76.2(6)
Max horizontal movement	(330.2mm)
Voltage	380V/50Hz
Gross weight	4800KG
Pressure plate adjustment range	2-9mm

ZOLYTECH PATTERN COLLECTION









www.quilting-machine.com 50





CUSTOMIZE YOUR << SMART FACTORY

VALUES OF THE TURN-KEY PROJECT



Reduce labor

Equipment investment payback period generally controlled within 2 years.



Convenient management

Fully digital data makes easier to understand.



Talents recruiting

High technology can attract talents more.



Space saving

Reduce excessive storage time, quick turnover.



Brand value

An intelligent factory creating infinite brand possibilities.




Enhanced quality

Real-time monitoring through fully automated big data.

www.quilting-machine.com 08









ZOLYTECH TECHNICAL PARAMETERS

DAILY PRODUCTION OF 600PCS MATTRESSES - ROBOT MATTRESS PRODUCTION LINE THE WHOLE SET ONLY TAKES 15 PEOPLE

Production efficiency	50 seconds per mattress, producing 500 pcs mattresses in 10 hours
Mattress specification	1800*2000mm, 1500*2000mm,1200*2000mm
Mattress thickness	200-250mm
Mattress composition	bottom fabric + pocket spring +sponge + top fabric

Intelligent equipment composition	Pocket spring machines "Seets + Assembling machine" 3sets - Robot gripper systems "2sets + Automatic glue spraying machine "2sets - Machine "Seets + Automatic glue spraying machine "2sets - Seets -
Workers needed	15
Area needed	2300 square meters









ZOLYTECH TECHNICAL PARAMETERS

DAILY PRODUCTION OF 600PCS MATTRESSES - ROBOT MATTRESS PRODUCTION LINE HIGH-END PILLOW TOP MATTRESS PRODUCTION LINE

Production efficiency	45 seconds per mattress produce 600 pcs triple side high-end mattresses in 8 hours
Mattress specification	1800*2000mm, 1500*2000mm, 1200*2000mm
Mattress thickness	200-400mm three sided mattress
Mattress composition	Bottom fabric + pocket spring bed core + tiger mouth+ filler (sponge + latex, etc.)+ top fabric

Intelligent equipment composition	Automatic glue spraying system * 4sets Robot gripper systems * 3sets + Automatic glue spraying machine * 3sets Automatic tape edge machines * 6+4sets Full automatic kraft paper packaging system * 1set
Workers needed	18
Area needed	1500 square meters