

GasAlert **MaxXT II**

multi-gas detector



Go the distance, and save

GasAlertMax XT II is the smart, simple, economical way to compliance. Workers feel safe and incidents are minimized so everyone will be able to do more. That means savings realized from business continuity and productivity.

Simple operation, with SmartSample pump.

GasAlertMax XT II reliably monitors up to four hazards and combines straightforward one-button operation with our robust, motorized pump for intelligent, remote sampling, ideal for confined spaces. The GasAlertMax XT II is fully compatible with MicroDock II automated test and calibration system.



**WATER
RESISTANT**



- Minimize costs and training with one-button operation
- More accurate sampling results with SmartSample pump technology
- Compact, comfortable and field tough

BWT
Technologies
by Honeywell

Wear yellow. Work safe.

H₂S

CO

O₂

LEL

Standard features of BW products:

- Continuous LCD shows real-time gas concentrations
- Compact and lightweight design makes it comfortable to wear
- Water-resistant
- Simple automatic calibration procedure; compatible with BW MicroDock II automatic test and calibration station
- Full function self-test of sensor, battery status, circuit integrity and audible/visual alarms on start up
- Bright wide-angled visual alarm bars
- Built-in concussion-proof boot

GasAlertMax XT II Specifications		
Size	5.1 x 2.8 x 2.0 in. / 13.1 x 7.0 x 5.2 cm	
Weight	11.5 oz. / 328 g	
Temperature	-4 to 122°F / -20 to 50°C	
Humidity	10 - 100% RH (non-condensing)	
Alarms	- Visual, vibrating, audible (95dB) - Low, High, STEL, TWA, OL (over limit), Low Battery, Pump	
Tests	Audible/visual alarms on activation, sensors, battery, pump and circuitry (continuous)	
Typical battery life	13 hours @ 32°F / 0°C 8 hours @ -4°F / -20°C Recharges in 6 hours	
Pump draw	Sample from up to 75 ft. / 23 m	
User options	Confidence beep Force calibration when overdue Safety (sensor) lock Sensor configuration Latching alarms Detector identification Safe display mode Low alarm acknowledge Calibration IR lock Language choices (five) Location selection Set custom start-up message Force block test Confidence interval Force bump test when overdue Datalog interval	
Ratings Ingress Protection	EMI/RFI: Complies with EMC Directive 2004/108/EC IP66/67	
Certifications and approvals	 Class I, Div. 1, Gr. A, B, C, D IECEX: Ga Ex ia IIC T4 ATEX:  II 1 G Ga Ex ia IIC T4  Br Ex ia IIC T4	
Warranty	Full two year warranty including all sensors	

Additional GasAlertMax XT II features:

- Integrated sampling pump with reliable diaphragm technology
- Best in class block detection with semi-conductor pressure sensor
- Multi-language support in English, French, German, Spanish and Portuguese
- Conveniently manage your detector with Fleet Manager II
- Equipped with standard datalogging and event logging

Options and Accessories



MicroDock II compatible



Belt holster



Multi-unit cradle charger




Concussion-proof boot

For a complete list of accessories, please contact BW Technologies by Honeywell.

Sensor Specifications		
Gas	Measuring Range	Resolution
H ₂ S	0-200 ppm	1 ppm
CO	0-1000 ppm	1 ppm
O ₂	0-30.0%	0.1%
Combustible gases	0-100% LEL 0-5.0% v/v	1% 0.1%
Alarm setpoints for all sensors are user adjustable. Setpoint(s) are automatically displayed during instrument start-up.		

Locally available from





Thank you for reading this data sheet.

For pricing or for further information, please contact us at our UK Office, using the details below.



UK Office

Keison Products,

P.O. Box 2124, Chelmsford, Essex, CM1 3UP, England.

Tel: +44 (0)1245 600560

Fax: +44 (0)1245 600030

Email: sales@keison.co.uk

Please note - Product designs and specifications are subject to change without notice. The user is responsible for determining the suitability of this product.