



DRY INK BATCH CODER

Model	PPBC 600
Voltage (V/Hz)	220 / 50
Power (W)	180
Printing Speed (pcs./min)	100
Object size (mm)	L:50-500 W30~300
Printing type	Solid Ink coding
Dimension (LxWxH) (mm)	440x465x300
Net Weight (kg)	26



SHRINK TUNNEL

Model	PP 3020	PP 4525	PPS 4535 L
Tunnel size (WxH) mm	300x200	450x250	450x350
Voltage (V / Hz)	220/50	220/50-380/50	380/50
Power Consumption (kw)	4.5	6.5	9.6
Conveyor Loading (kg)	10	10	30
Heating Furnace (LxWxH) mm	900x300x50-200*	900x450x50-200*	1200x450x50-350*
External Dimension (LxWxH) mm	1200x500x800	1200x650x1240	1200x650x1340
Speed (m / min)	0~10	0~10	0~10
Heating Time (Minutes)	10	10	10
Cooling Time (minutes)	15	15	15
Net Weight	70	90	120

* Height Adjustable

ELECTRO MAGNETIC INDUCTION CAPPER

Model	PPIS-100 (Manual Model)
Voltage (V/Hz)	AC 220/50
Power (W)	500
Heal Diameter	20-135
Delivering Speed	N/A
Vessel height	Absoluteness
Dimension (LxWxH) (mm)	340x290x150
Weight (kg)	5
Capacity	0-50 pc. / min



SHRINK CHAMBER

Model	PPSC 5544
Voltage (V / Hz)	Ac 220/50
Power (kw)	4
Packing speed (pcs/h)	700 ~ 1000
Max Packaging Dimension (LxWxH) mm	500x375x250
Dimension (LxWxH) mm	1945x795x1080
Weight (kg)	80

