



## SRM-120 (100 Watts RMS)

Single 12" Two-Way

Studiomaker represents new range of **stage monitor** for the ultimate performance and simplicity, sturdy & rugged carpet covered bass reflex cabinet with side handles and corners built around high quality 12" 100 watt dual cone speaker and high frequency horn driver. Features high efficiency, high sound pressure level and powerful bass. An On/Off switch for the piezo horn is provided to limit extended HF if desired.

**Ideal for stage shows, large gatherings, institutes and outdoor PA programmes.**

For Elegant and Luxury outlook, Customer has option to choose from StudioMaker's high quality **Sand Texture Paint Finish** (resistant against splash of water, scratch and high temperature) which comes with same design and specifications.

**OPTIONAL**



## SRM-200 (200 Watts RMS)

Single 12" Two-Way

**Multi angle cabinet** acoustically designed in Trapezoidal way fitted with single 12" dual cone speaker with neodymium horn tweeter, the enclosure is formed by 18mm plywood with carpet cover wrap-around high tensile pressed-steel grill which provides better protection towards components, easy to carry side handles, corners for safety, unmatched power of 200 watts with low distortion & high sound pressure level makes it **ideal to use for PA indoor and outdoor live performances, stage music venues.** An On/Off switch for the piezo horn is provided to limit extended HF if desired.

SPECIFICATION	SRM-120DX	SRM-200
Power Input	100Watts RMS	200Watts RMS
Nominal Impedance	8Ω	8Ω
Frequency Response	55Hz-20000Hz	55Hz-20000Hz
Rated SPL	97dB (1W/1M), 117dB Max	98dB (1W/1M), 121dB Max
Low Frequency Speaker	1x12" Dual Cone Spkr 100W, 1½" Voice Coil, MS Frame, 134 mm Magnet	1x12" Dual Cone Spkr 200W, 2" Voice Coil, MS Frame, 155mm Magnet
High Freq. Unit	1xPiezo Horn 3"x7" with protection	1x Horn 4"x10" + 40W Neodymium HF Driver with protection
Input Connectors	¼" Phone Jack, Terminal Strip+HF Cut Switch	¼" Phone Jack, Terminal Strip+HF Cut Switch
Dimensions	Width 406mm(16" in) Depth 393mm (15.5" in) Height 552mm (22" in)	Width 558mm(22" in) Depth 406mm (16" in) Height 400mm (16" in)
Weight	14 Kg.	16 Kg.





## SRX-250 (200 Watts RMS)

Dual 12" Two-Way

Introducing two 12" 100 Watt each full range dual cone speaker & Piezo horn tweeter, designed for maximum output, optimal coverage and minimum distortion. Fitted in acoustically treated 18mm plywood enclosure with carpet cover. Easy to carry side handles. Stand mount bracket is provided at the bottom. Transducers are covered under the high tensile pressed-steel grill for protection. An On/Off switch for the piezo horn is provided to limit extended HF if desired.

**Ideal for use in sound reinforcement system and PA applications such as Educational Institutes, Religious places etc.**

For Elegant and Luxury outlook, Customer has option to choose from StudioMaker's high quality **Sand Texture Paint Finish** (resistant against splash of water, scratch and high temperature) which comes with same design and specifications.

**OPTIONAL**



## SRX-350 (400 Watts RMS)

Dual 12" Two-Way

Professional 2-way speaker system consist of dual 12" Mid-Bass dual cone speaker with high quality neodymium compression driver for high performance automobile design, the highest possible power capacity. The heavily braced 18 mm plywood enclosure assures tight, solid bass. Premium grade carpet covering. Designed with two metal side handles for easy handling. Wrap-around 16 gauge steel grill for protection. Metal corners for safety **Especially suitable for subwoofer-equipped systems, large PA outdoor gatherings, mobile DJs and institutions.**

SPECIFICATION	SRX-250	SRX-350
Power Input	200 Watts RMS	400Watts RMS
Nominal Impedance	16Ω	4Ω
Frequency Response	55Hz-20000Hz	40Hz-20000Hz
Rated SPL	100dB (1W/1M), 123dB Max	100dB (1W/1M), 125dB Max
Low Frequency Speaker	2x12" Spkr 100W Each, 1.5" Voice Coil, 134 mm Magnet	2x12" 200W each Dual Cone Spkr, 2" Voice Coil, MS Frame, 155mm Magnet
High Freq. Unit	1xHorn 3"x7"+Piezo HF Driver with Protection	1x Horn 4"x10" + 40W Neodymium HF Driver with protection
Input Connectors	¼" Phone Jack, Terminal Strip+HF Cut Switch	2xSpeakon
Dimensions	Width 400mm(20" in) Depth 330mm (19" in) Height 857mm (48" in)	Width 444mm(18" in) Depth 406mm (16" in) Height 1016mm (40" in)
Weight	22.2 Kg.	31 Kg.



**SRX-425 (400 Watts RMS)****SRX-325 (200 Watts RMS)****Dual -12" Two-Way**

Combining the performance of Low, Mid & High System comes with two 12" LF Speakers and one high frequency neodymium compression horn driver housed in an acoustically treated bass reflex trapezoidal premium grade carpet covered enclosure.

Studiomaker ensures the finest quality of transducers which delivers superb high level music and powerful bass with smooth, clear mids and highs.

**Ideal for indoor and outdoor sound re-inforcement applications, DJ's variety music programs etc.**

**OPTIONAL**

For Elegant and Luxury outlook, Customer has option to choose from StudioMaker's high quality **Sand Texture Paint Finish** (resistant against splash of water, scratch and high temperature) and Attractive Front Color Variants are also available, which comes with same design and specifications.

- ◆ Constructed of top quality hardcore  $\frac{3}{4}$ " (19mm) plywood.
- ◆ Wrap-around 16-gauge steel grill lined with acoustically transparent foam for protection and appearance.
- ◆ Differential drive woofers with high grade ferrite magnets. Easy to carry side handles.
- ◆ High quality compression driver with horn for horizontal and vertical coverage of high sound pressure level at low distortion.
- ◆ In-built crossover protection for safety of hf driver.
- ◆ Affordable advance designs with high performance and wide coverage.



SPECIFICATION	SRX-425	SRX-325
<b>Power Input</b>	400 Watts RMS	200 Watts RMS
<b>Nominal Impedance</b>	4Ω	16Ω
<b>Frequency Response</b>	42Hz-20000Hz	52Hz-20000Hz
<b>Rated SPL</b>	100dB (1W/1M), 124dB Max	100dB (1W/1M), 124dB Max
<b>Low Frequency Speaker</b>	2x12" Spkr 200W Each, MS Frame, 2" Voice Coil, 155 mm Magnet	2x12" Spkr 100W Each, MS Frame, 1.5" Voice Coil, 134 mm Magnet
<b>High Freq. Unit</b>	1xHorn 4"x10" + 40W Neodymium HF Driver with Protection	1xHorn 3"x7" + Piezo Horn HF Driver with Protection Circuit
<b>Input Connectors</b>	2xSpeakon	2xSpeakon
<b>Dimensions</b>	Width 406mm(16" in) Depth 406mm (16" in) Height 939mm (37" in)	Width 406mm(16" in) Depth 406mm (16" in) Height 939mm (37" in)
<b>Weight</b>	30.5 kg.	29 kg.





## SRX-12.4/812/1212 DX

Four 12" Two-Way (400/800/1200 Watts RMS)

For the ultimate in performance and simplicity, sturdy & rugged carpet covered bass reflex cabinet with heavy duty metal side handles and corners to protect from uncertain falls. Built around 4 nos of high quality 12" dual cone speakers and 2 nos high frequency horn drivers. Features high efficiency, high sound pressure level and powerful bass.

- ◆ Constructed of top quality hardcore  $\frac{3}{4}$ " (19mm) plywood.
- ◆ Wrap-around 16-gauge steel grill lined for protection and appearance.
- ◆ Two neodymium high frequency horn drivers for long throw and coverage.
- ◆ Four nos high quality 12" 200/300 watt dual cone full range, HF drivers with high grade ferrite magnets.

**Ideal for large gatherings, mobile DJs, indoor and outdoor PA applications.**

For Elegant and Luxury outlook, Customer has option to choose from Studiomaker's high quality **Sand Texture Paint** Finish (resistant against splash of water, scratch and high temperature) which comes with same design and specifications.

**OPTIONAL**



## SRM-300/400/600

Single 15" Two-way (300/400/700 Watts RMS)

The SRM Series from Studiomaker comes with multi cabinet design, compact, portable system which consist of single 15" Mid-Bass Speaker with neodymium compression horn driver. Large open ducts minimize port turbulence and the heavily braced enclosure assures smooth & clear performance that at home in main PA or stage monitor applications. The high frequency performance makes an outstanding choice for **high level music playback.**

- ◆ Constructed of top quality hardcore  $\frac{3}{4}$ " (18mm) plywood with premium grade carpet cover.
- ◆ Wrap-around 16-gauge steel grill lined with acoustically transparent foam for protection and appearance.
- ◆ Differential drive woofers with high grade ferrite magnets. Easy to carry side handles.

SPECIFICATION	SRX-12.4/12.4DX	SRX-812.4/1212.4	SRM-300/400	SRM-600
<b>Power Input</b>	400 Watts RMS	800/1200 Watts RMS	300/400 Watts RMS	700Watts RMS
<b>Nominal Impedance</b>	8Ω	8Ω	8Ω	8Ω
<b>Frequency Response</b>	40Hz-20000Hz	38Hz/36Hz-20000Hz	45/44Hz-20000Hz	43Hz-20000Hz
<b>Rated SPL</b>	103dB (1W/1M), 130dB Max	104dB/105dB (1W/1M), 131dB/132dB	100/101dB (1W/1M), 123/124dB Max	102dB (1W/1M), 126dB Max
<b>Low Frequency Speaker</b>	4x12" Dual Cone Spkr 100 W each, MS Frame, 1.5" Voice coil, 134mm Magnet	4x12" Dual Cone Spkr 200 W/300W each, MS Frame, 2"/2.5" Voice coil, 155mm Magnet	1x15" Spkr 300/400W, 3" Voice Coil, MS Frame, 185/190 mm Magnet	1x15" Spkr 600W, 4" Voice Coil, AL Frame, 220 mm Magnet
<b>High Freq. Unit</b>	2xHorn 3"x7" + Piezo HF Driver with Protection	2xHorn 3"x7" + Neodymium HF Driver with Protection	1xHorn 8"x12", Neodymium/Ferrite 40/60W HF Driver with protection	1xHorn 8"x12", Ferrite Magnet 100W HF Driver with protection
<b>Input Connectors</b>	2xSpeakon	2xSpeakon	2xSpeakon	2xSpeakon
<b>Dimensions</b>	Width 800 mm (31" in) Depth 356 mm (14" in)/406 mm (16" in) Height 914 mm (36" in)	Width 800 mm (31" in) Depth 406 mm (16" in) Height 914 mm (36" in)	Width 755mm(30" in) Depth 504mm (20" in) Height 469mm (18½" in)	Width 755mm(30" in) Depth 504mm (20" in) Height 469mm (18½" in)
<b>Weight</b>	53.7 kg./55.7 kg.	58.7 kg./60.7 kg.	25.8 Kg./27.3Kg.	29.1 Kg.





## SRX-220 (200 Watts RMS)

### Single 15" Two-Way

The single 15" two way bass reflex offers highest level of performance available from a portable pole or tripod mountable speaker. System consist of single 15" dual cone full range speaker with Piezo horn tweeter. Housed in acoustically treated enclosure. Stand-mounting adapter is provided at the bottom, Easy to carry side handles, corners to protect from uncertain falls. Front Steel grille for protection and appearance. Premium grade carpet finishing.

**The system is usually demanded in sound reinforcement system and PA Applications.**

For Elegant and Luxury outlook, Customer has option to choose from StudioMaker's high quality Sand Texture Paint Finish (resistant against splash of water, scratch and high temperature) which comes with same design and specifications.

**OPTIONAL**



## SAX-300 (300 Watts RMS)

### Single-15" Three-Way

Studiomaker SAX 300 is a professional 3-way speaker system with constant horizontal and vertical coverage patterns consisting of one high efficiency, high SPL 15" LF speaker, 1" HF compression driver and two Piezo Tweeters for excellent high frequency response. The system is housed in rugged bass Reflex Trapezoidal Enclosure made of 19mm plywood and carpet covered. Easy to carry side handles and corners for protection. An On/Off switch for the piezo tweeter is provided to limit extended HF if desired. The speaker is ideal for PA as well as music performances.

SPECIFICATION	SRX-220	SAX-300
Power Input	200 Watts RMS	300Watts RMS
Nominal Impedance	8Ω	8Ω
Frequency Response	50Hz-20000Hz	40Hz-20000Hz
Rated SPL	98 dB (1W/1M), 122dB Max	100dB (1W/1M), 125dB Max
Low Frequency Speaker	1x15" Dual Cone Spkr 200W, 2" Voice Coil, MS Frame, 155 mm Magnet	1x15" 300W, Mid Bass Speaker 3" Voice Coil, (A.L. Frame) 190 mm Magnet
High Freq. Unit	1xHorn 3"x7" + Piezo, HF Driver with protection	1xHorn 4"x10"+40Watt. HF Driver, 2xPiezo, 3" Tweeter with protection and cut-off switch
Input Connectors	2xSpeakon	2xSpeakon
Dimensions	Width 482 mm (19" in) Depth 431 mm (17" in) Height 729 mm (29" in)	Width 540mm(21.2 in) Depth 450mm (17.7" in) Height 762mm (30" in)
Weight	22.4 Kg.	30.1 Kg.





## SAX-525 (400 Watts RMS)

Single 15" Two-Way

Combining the performance of Low, Mid & High Systems, the SAX-525 comes with one 15" LF Speakers and one high frequency titanium compression horn driver housed in an acoustically treated bass reflex trapezoidal premium grade carpet covered enclosure.

StudioMaker ensures the finest quality of transducers which delivers superb high level music and powerful bass with smooth, clear mids and highs.

**Ideal for indoor and outdoor sound re-inforcement applications, DJ's variety music programs etc. Available in 600W also.**

For Elegant and Luxury outlook, Customer has option to choose from StudioMaker's high quality Sand Texture Paint Finish (resistant against splash of water, scratch and high temperature) which comes with same design and specifications.

OPTIONAL



## SRX-600 (650 Watts RMS)

Dual-15" Two-Way

Professional 2-way speaker system delivers excellent performance by itself. Two 15" high performance loudspeakers and a high frequency titanium compression horn driver housed in an acoustically treated bass reflex trapezoidal carpet covered enclosure. The large mouth horn design delivers smooth, natural reproduction especially in the critical mid-range. Tough and non-resonant steel side handles for ease of mobility. Steel side corners to avoid damage from uncertain falls.

**The system is designed for applications in DJ and live performances, music playback, sound reinforcement system, high power outdoor PA applications etc.**

SPECIFICATION	SAX-525	SRX-600
Power Input	400 Watts RMS	650 Watts RMS
Nominal Impedance	8Ω	4Ω
Frequency Response	40Hz-20000Hz	40Hz-20000Hz
Rated SPL	100dB (1W/1M), 125dB Max	102dB (1W/1M), 129dB Max
Low Frequency Speaker	1x15" Spkr 300W Each, AL Frame, 3" Voice Coil, 190 mm Magnet	2x15" Spkr 300W Each, MS Frame, 2.5" Voice Coil, 185 mm Magnet
High Freq. Unit	1xHorn 8"x12" + 60W HF Driver, with Protection Circuit	1xHorn 12"x18"+40Watt. HF Driver+ Protection Circuit
Input Connectors	2xSpeakon	2xSpeakon
Dimensions	Width 444mm(17½" in) Depth 457mm (18" in) Height 736mm (29" in)	Width 571mm(22½" in) Depth 450mm (18" in) Height 1206mm (47½" in)
Weight	30.3 kg.	48.1 kg.



**SRX-400 (400 Watts RMS)****SRX-500 (600 Watts RMS)****Dual-15" Two-Way**

The most affordable of the Studiometer SRX series has two 15" full range dual cone speakers with compression horn driver which delivers the smooth high fidelity of sound, long throw, articulate sonic quality. Enclosed in heavily braced enclosure assure tight and solid bass with carpet covered. Tough and non-resonant steel side handles for ease of mobility. Steel side corners to avoid damage from uncertain falls.

**The system is designed for applications in live performances, music playback and re-inforcement of speech.**

**OPTIONAL**

For Elegant and Luxury outlook, Customer has option to choose from StudioMaker's high quality **Sand Texture Paint Finish** (resistant against splash of water, scratch and high temperature) and Attractive Front Color Variants are also available, which comes with same design and specifications.



- ◆ Acoustically superior 3/4" (18mm) hardcore plywood enclosure construction for ruggedness and low-end performance.
- ◆ Wrap-around 16-gauge steel grill for protection and appearance.
- ◆ Precision Transducers with high grade ferrite magnets.
- ◆ High quality compression driver with horn for horizontal and vertical coverage of high sound pressure level at low distortion.
- ◆ In-built crossover protection for safety of hf driver.
- ◆ Affordable advance designs with high performance and wide coverage.

SPECIFICATION	SRX-400	SRX-500
<b>Power Input</b>	400 Watts RMS	600 Watts RMS
<b>Nominal Impedance</b>	8Ω	4Ω
<b>Frequency Response</b>	40Hz-20000Hz	42Hz-20000Hz
<b>Rated SPL</b>	101 dB (1W/1M), 127dB Max	102 dB (1W/1M), 128dB Max
<b>Low Frequency Speaker</b>	2x15" Dual Cone Spkr 200W, 2" Voice Coil, MS Frame, 155 mm Magnet	2x15" Spkr 300W each, 2.5" Voice Coil, MS Frame, 185 mm Magnet
<b>High Freq. Unit</b>	1xHorn 4"x10" +Piezo HF Driver with protection	1xHorn 4"x10" + Neodymium HF Driver with protection
<b>Input Connectors</b>	2xSpeakon	2xSpeakon
<b>Dimensions</b>	Width 584 mm (23" in) Depth 457 mm (18" in) Height 1219 mm (48" in)	Width 577 mm (23" in) Depth 457 mm (18" in) Height 1219 mm (48" in)
<b>Weight</b>	48.5 Kg.	49 Kg.



**SRX-725 (700 Watts RMS)****SRX-800 (800 Watts RMS)****Dual-15" Two-Way**

Combining the performance of Low, Mid & High System comes with two 15" LF Speakers and one high-frequency titanium compression horn driver housed in an acoustically treated bass reflex trapezoidal premium grade carpet covered enclosure.

Studiomaker ensures the finest quality of transducers which delivers superb high-level music and powerful bass with smooth, clear mids and highs.

**Ideally suited to sound reinforcement, DJ Programmes, music playback or speech.**

**OPTIONAL**

For Elegant and Luxury outlook, Customer has option to choose from StudioMaker's high quality **Sand Texture Paint Finish** (resistant against splash of water, scratch and high temperature) and Attractive Front Color Variants are also available, which comes with same design and specifications.

- ◆ Constructed of top quality hardcore  $\frac{3}{4}$ " (19mm) plywood.
- ◆ Wrap-around 16-gauge steel grill lined with acoustically transparent foam for protection and appearance.
- ◆ Differential drive woofers with high grade ferrite magnets.
- ◆ High quality compression driver with horn for horizontal and vertical coverage of high sound pressure level at low distortion.
- ◆ In-built crossover protection for safety of hf driver.
- ◆ Affordable advance designs with high performance and wide coverage.



SPECIFICATION	SRX-725	SRX-800
<b>Power Input</b>	700 Watts RMS	800 Watts RMS
<b>Nominal Impedance</b>	4Ω	4Ω
<b>Frequency Response</b>	40Hz-20000Hz	38Hz-20000Hz
<b>Rated SPL</b>	101dB (1W/1M), 128dB Max	102dB (1W/1M), 129dB Max
<b>Low Frequency Speaker</b>	2x15" Spkr 300W Each, MS Frame, 3" Voice Coil, 190 mm Magnet	2x15" Spkr 350watt Each, 3" Voice coil, AL Frame, 190mm Magnet
<b>High Freq. Unit</b>	1xHorn 8"x12"+60Watt. HF Driver+ Protection Circuit	1xHorn 8"x12"+60 Watt. HF Driver+ Protection Circuit
<b>Input Connectors</b>	2xSpeakon	2xSpeakon
<b>Dimensions</b>	Width 508mm(20" in) Depth 482mm (19" in) Height 1219mm (48" in)	Width 508mm(20" in) Depth 482mm (19" in) Height 1219mm (48" in)
<b>Weight</b>	52 kg.	53 kg.



**SRX-804** (800 Watts RMS)**SRX-807** (900 Watts RMS)

Dual-15" Two-Way

**Studiomaker introduces new range of Attractive front color variants to match with ambient.**

With its new cabinet design the system combines both outlook and quality. A high efficiency professional 2-way Speaker system has superb low frequency response, long throw and excellent sound intelligibility. Two 15" high performance LF loudspeakers and high frequency compression horn driver with safety protection, housed in an acoustically treated bas reflex trapezoidal carpet covered enclosure. Strong grill for speaker protection. Heavy duty metal handles provide ease of mobility. Metal corner protect from uncertain falls & breakage.

**Ideal for outdoor music programmes, auditoria, religious gatherings, live concerts, DJ etc.**

**OPTIONAL**

For Elegant and Luxury outlook, Customer has option to choose from StudioMaker's high quality **Sand Texture Paint Finish** (resistant against splash of water, scratch and high temperature) and Attractive Front Color Variants are also available, which comes with same design and specifications.

- ◆ Constructed of top quality hardcore  $\frac{3}{4}$ " (19mm) plywood.
- ◆ Wrap-around 16-gauge newly designed pressed-steel grill for protection and appearance.
- ◆ High-power, clean sound, low frequency drivers with high grade ferrite magnets.
- ◆ Enclosure angles for many applications.
- ◆ Affordable advance new design with red color leather finish on front speaker baffle for attractive look.
- ◆ Long throw horn for high frequency compression driver with crossover protection to provide high sound pressure level with very uniform horizontal and vertical coverage.



SPECIFICATION	SRX-804	SRX-807
Power Input	800 Watts RMS	900 Watts RMS
Nominal Impedance	4Ω	4Ω
Frequency Response	38Hz-20000Hz	37Hz-20000Hz
Rated SPL	103dB (1W/1M), 129dB Max	104dB (1W/1M), 130dB Max
Low Frequency Speaker	2x15" Spkr 350 watt each, AL Frame, 3" Voice coil, 190mm Magnet	2x15" Spkr 400 watt each, AL Frame, 3" Voice coil, 190mm Magnet
High Freq. Unit	1xHorn 8"x12"with 60 Watt HF Driver +Protection circuit	1xHorn 8"x12"with 100 Watt HF Driver +Protection circuit
Input Connectors	2xSpeakon	2xSpeakon
Dimensions	Width 533mm(21" in) Depth 558mm (22" in) Height 1219mm (48" in)	Width 533mm(21" in) Depth 558mm (22" in) Height 1219mm (48" in)
Weight	55 kg.	61.5 kg.



**SRX-825 (800 Watts RMS)**

Dual-15" Two-Way

**Studiomaker introduces new range of Attractive front color variants to match with ambient.**

A high efficiency professional 2-way PA Speaker system has superb low frequency response, long throw and excellent sound intelligibility and cost effective system. Two 15" high performance LF loudspeakers and high frequency compression horn driver with safety protection feature housed in an acoustically treated bas reflex trapezoidal carpet covered enclosure. Strong grill for speaker protection. Heavy duty metal handles provide ease of mobility and transportation. Metal corner protect from uncertain falls & breakage.

**Ideal for outdoor music programmes, auditoria, religious gatherings, live concerts, DJ etc.**

**OPTIONAL**

For Elegant and Luxury outlook, Customer has option to choose from StudioMaker's high quality **Sand Texture Paint Finish** (resistant against splash of water, scratch and high temperature) and Attractive Front Color Variants are also available, which comes with same design and specifications.

- ◆ Constructed of top quality hardcore ¾" (19mm) plywood.
- ◆ Wrap-around 16-gauge steel grill lined with acoustically transparent foam for protection and appearance.
- ◆ High-power, clean sound, low frequency drivers with high grade ferrite magnets.
- ◆ Enclosure angles for many applications.
- ◆ Affordable advance new design with gray colour leather finish on front speaker baffle for attractive look.
- ◆ Long throw horn for high frequency compression driver with crossover protection to provide high sound pressure level with very uniform horizontal and vertical coverage.



SPECIFICATION	SRX-825
<b>Power Input</b>	800 Watts RMS
<b>Nominal Impedance</b>	4Ω
<b>Frequency Response</b>	38Hz-20000Hz
<b>Rated SPL</b>	102dB (1W/1M), 130dB Max
<b>Low Frequency Speaker</b>	2x15" Spkr 350W Each, AL Frame, 3" Voice Coil, 190 mm Magnet
<b>High Freq. Unit</b>	1xHorn 8"x12"+60Watt. HF Driver+ Protection Circuit
<b>Input Connectors</b>	2xSpeakon
<b>Dimensions</b>	Width 508mm(20" in) Depth 482mm (19" in) Height 1219mm (48" in)
<b>Weight</b>	54 kg.