

## C frame Hydraulic Press



### Technical Specification of C frame Hydraulic Press

MODEL	BHC-5	BHC-10	BHC-20	BHC-30	BHC-50	BHC-75	BHC-100
CAPACITY (TONS)	5	10	20	30	50	75	100
PISTON SIZE (MM)	80	100	130	150	180	230	250
STROKE (MM)	250	250	300	300	300	350	400
DAYLIGHT (MM)	300	300	400	400	400	500	550
SHUT HEIGHT (MM)	50	50	100	100	100	150	150
TABLE SIZE (L x W)	350x300	400x300	500x350	550x350	600x400	700x500	800x550
APPROACH SPEED (MM/SEC)	20-25	20-25	25-28	25-28	30-35	30-35	30-35
PRESSING SPEED (MM/SEC)	5-8	5-8	4-6	4-6	4-6	3-5	3-5
RETURN SPEED (MM/SEC)	25-30	30-35	35-40	35-40	50-55	60-65	60-65
ELECTRIC MOTOR (HP)	0.5	1	2	3	5	7.5	10
NO. OF CYLINDERS	1	1	1	1	1	1	1

## H frame Hydraulic Press

### **BASANT INDUSTRIES**

369, Industrial Area "B", Ludhiana – 141003. (INDIA)  
Ph. 9914337888, 9780600008, Email: [info@basantbi.com](mailto:info@basantbi.com)



### Technical Specification of H frame Hydraulic Press

MODEL	BHH-20	BHH-50	BHH-75	BHH-100	BHH-150	BHH-200	BHH-250	BHH-300	BHH-400	BHH-500
CAPACITY (TONS)	20	50	75	100	150	200	250	300	400	500
PISTON SIZE (MM)	130	180	230	250	300	350	400	450	500	550
STROKE (MM)	300	300	350	400	450	500	550	600	650	700
DAYLIGHT (MM)	400	400	500	550	650	700	800	850	950	1000
SHUT HEIGHT (MM)	100	100	150	150	200	200	250	250	300	300
TABLE SIZE (L xW)	350x400	450x500	500x550	600x600	650x650	800x800	850x850	900x900	1000x1000	1000x1000
APPROACH SPEED (MM/SEC)	25-28	30-35	30-35	30-35	30-35	30-35	30-35	30-35	30-35	30-35
PRESSING SPEED (MM/SEC)	4-6	4-6	3-5	3-5	3-5	3-5	3-5	3-5	3-5	3-5
RETURN SPEED (MM/SEC)	35-40	50-55	60-65	60-65	65-70	75-80	85-90	85-90	95-100	100-110
ELECTRIC MOTOR (HP)	2	5	7.5	10	15	20	25	30	40	50
NO. OF CYLINDERS	1	1	1	1	1	1	1	1	1	1

## BASANT INDUSTRIES

369, Industrial Area "B", Ludhiana – 141003. (INDIA)  
Ph. 9914337888, 9780600008, Email: [info@basantbi.com](mailto:info@basantbi.com)